

ARDEX MC™ RAPID

Installation Options

Option 1: ARDEX Underlayment or patch at 1/4" (6 mm) or less

- Allow ARDEX MC™ RAPID cure for 4 to 24 hours
- Install ARDEX P 82™ Ultra Prime, cure for 3 to 24 hours
- Install ARDEX Underlayment at 1/4" or less

Option 2: ARDEX Underlayment or patch more than 1/4" (6 mm)

- Allow ARDEX MC™ RAPID cure for 4 to 24 hours
- Install a second coat of ARDEX MC RAPID; sand broadcast; cure 4 hours
- Install up to the recommended thickness for ARDEX Underlayment or Patch

Option 3: ARDEX K 60™ ARDITEX

- Allow ARDEX MC™ RAPID cure for 4 hours
- Install ARDEX K 60™ within the next 4 hours
- No primer, no sand, install ARDEX K 60 within the 4 hour window after the ARDEX MC™ RAPID has cured

Key Features

- 100% solids epoxy resin system
- Solvent-free
- Available in a 22 lb. (10 kg) unit

Performance

- ASTM E96 perm rating: 0.06 perms
- Maximum pH tolerance
- Tenacious bond to substrate
- RH readings up to 100%



Use under all standard commercial and residential floor coverings on interior substrates below, on or above grade.

AF 109 10/14

**INSTALLATION
OPTIONS**



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com