



ARDEX TECHNICAL UPDATE

Update 124
April 13, 2018
To: ARDEX Sales Professionals, Sales Managers; corporate select, social media, web
From: ARDEX Technical Department

ARDEX MC RAPID for Epoxy Coatings and Epoxy Terrazzo

We are pleased to announce that, after extensive testing, we are expanding our recommendations to allow for the installation of high-build epoxy coating systems and epoxy terrazzo systems directly over ARDEX MC RAPID™. Note the following conditions:

1. The ARDEX MC RAPID must be installed at a minimum thickness of 14 mils and must receive a sand broadcast to refusal.
2. Epoxy coating systems must be installed at a minimum thickness of 1/8" (125 mils / 3 mm). Epoxy terrazzo systems are commonly installed at a minimum thickness of 3/8" (375 mils / 9 mm).
3. The epoxy system must be suitable for installation over a sand-broadcasted, epoxy surface.

Should you have any questions on this information, or if we can be of further assistance, please contact the ARDEX Technical Service Department.

A handwritten signature in black ink, appearing to read "T. Schneider".

Tivona Schneider
Technical Communications Supervisor

ARDEX AMERICAS 400 ARDEX Park Drive Aliquippa PA 15001
P: 724-203-5000 F: 724-203-5001 www.ardexamericas.com