

ARDEX GUIDE SPECIFICATION

ARDEX N 23™ MICROTEC® Rapid Set Natural Stone and Tile Mortar

Installation Materials for Tile and Stone Applications

SECTION 09 30 00

ARDEX TILE & STONE INSTALLATION MATERIALS AND SYSTEMS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings, general provisions of the Contract, and other related construction documents such as Division 01 specifications apply to this Section

1.2 SUMMARY

- A. This Section includes the installation of porcelain tiles with a polymer modified thin-to-thick bed mortar.
 - 1. ARDEX N 23™ MICROTEC® Rapid Set Natural Stone and Tile Mortar
- B. Complete ARDEX product and system installation details are provided in their corresponding Technical Brochure available at www.ardexamericas.com.
- C. Related Sections include the following:
 - 1. Division 09 Tile & Stone Sections

1.3 REFERENCES

- A. AMERICAN NATIONAL STANDARDS INSTITUTE (A.N.S.I.)
 - 1. A-118.4 Modified Dry-Set Cement Mortar
 - 2. A-118.11 EGP Latex-Portland cement mortar
 - 3. A-108.01 General Requirements for Subsurfaces and Preparations by Other Trades
 - 4. A-108.5 Installation of Ceramic Tile with Dry-Set Portland Cement Mortar or Latex-Portland Cement Mortar
- B. TILE COUNCIL OF AMERICA, INC.
 - 1. Handbook for Ceramic Tile Installation

C. INTERNATIONAL STANDARDS ORGANISATION (ISO)

1. ISO 13007 C2 FTE S1– Ceramic Tile-Grouts & Adhesives

1.4 SUBMITTALS

- A. Product Data: Submit manufacturer's product data, a Revit file with applicable materials meeting the Revit Content Style Guide, and installation instructions for each material and product used. Include manufacturer's Safety Data Sheets.
- B. Qualification Data: For Installer

1.5 QUALITY ASSURANCE

- A. Installer Qualifications:
 1. Installer is a five-star member of the National Tile Contractors Association or a Trowel of Excellence member of the Tile Contractors' Association of America.
 2. Installer's supervisor for Project holds the International Masonry Institute's Foremans Certification.
 3. Installer employs Ceramic Tile Education Foundation Certified Installers or installer recognized by the U.S. Department of Labor as Journeyman Tile Layers.
- B. Manufacturer Experience: Provide products of this section by companies which have successfully specialized in production of this type for not less than 5 years. Contact Manufacturer Representative prior to installation.

1.6 DELIVERY, STORAGE AND HANDLING

- A. Deliver products in original packaging, labeled with product identification, manufacturer, batch number and shelf life.
- B. Store products in a dry area with temperature maintained between 50° and 85°F (10° and 29°C) and protect from direct sunlight.
- C. Handle products in accordance with manufacturer's printed recommendations.

1.7 PROJECT CONDITIONS

- A. Do not install material below 50°F (10°C) surface and air temperatures. These temperatures must also be maintained during and for 48 hours after the installation of products included in this section. Install quickly if substrate is warm and follow warm weather instructions available from the ARDEX Technical Service Department.

PART 2 - PRODUCTS

2.1 MORTAR

A. Acceptable Products:

1. ARDEX N 23™; Manufactured by ARDEX AMERICAS USA, (724) 203-5000, www.ardexamericas.com

B. Performance and Physical Properties: Meet or exceed the following values for material cured at 70° F+/-3°F (21° C+/-3°C) and 50% +/-5% relative humidity:

1. Open Time: Up to 30 Minutes
2. Pot Life: Approx. 60 minutes
3. Use for interior
4. ISO 13007: C2 FTE S1
5. Meets or Exceeds ANSI A 118.11 & ANSI A 118.4

PART 3 – EXECUTION

3.1 PREPARATION

A. Subfloors: Prepare substrate in accordance with manufacturer’s instructions.

1. Prior to proceeding please refer to ANSI A 108.01 “General Requirements for Subsurface” and the TCNA’s “Handbook for Ceramic Tile Installation” for detailed information. Substrate and ambient temperatures must be a minimum of 50°F (10°C).
2. All subfloors must be clean and completely free of all contaminants, including dust, oil, grease, wax, sealers, paint, varnish, etc. Prepare floor as required by mechanical means. Do not use chemicals to clean the floor.
3. Examine substrates and conditions under which materials will be installed. Do not proceed with installation until unsatisfactory conditions are corrected.
4. Coordinate installation with adjacent work to ensure proper sequence of construction. Protect adjacent areas from contact due to mixing and handling of materials.

B. APPLICATION OF INSTALLATION MATERIALS

Install Tile with Mortar

1. Install tiles following the general office outline procedure set forth in ANSI A108.5.

2. Comply with manufacturer's printed instructions for mixing of material, installation, and cure. For questions contact the ARDEX Technical Services Department at (724) 203-5000.

3.2 FIELD QUALITY CONTROL

- A. Where required, contact manufacturer for field sampling methods and procedures.

3.3 PROTECTION

- A. Protect the installation from abuse by other trades by the use of plywood, Masonite or other suitable protection course.

END OF SECTION