

ARDEX OVP™

Finishing Compound for Overhead and Vertical Concrete Walls

Trowelable finishing compound for tilt up walls, pre cast or poured in place concrete panels, and other concrete or masonry surfaces. Use for filling and smoothing overhead and vertical surfaces prior to sealing or painting. Tougher and more durable than traditional gypsum and latex patches.

Key Features

- Deep fill and skim coat
- Long pot life for large jobs
- High yield, non-shrinking, sandable
- Interior and exterior
- Portland cement-based
- Available in gray and white

Installation

- **Packaging:** 20 lb bag (9 kg)
- **Coverage over smooth surface:**
 - 133 sq. ft. (12.35 m²) at 1/16"
 - 66.6 sq. ft. (6.18 m²) at 1/8"
 - 33.3 sq. ft. (3.09 m²) at 1/4"
 - 300 sq. ft. (27.87 m²) at a skim coat
- **Pot life:** 90 minutes
- **Working time:** 30 minutes
- **Seal or paint:** 2 to 3 hours

Performance

- **VOC:** 0



AVAILABLE IN GRAY AND WHITE



AMERICAS

+1-724-203-5000
888-512-7339

www.ardexamericas.com

AF158 5/17

ENGINEERED CONCRETE
REPAIR SYSTEMS