

ARDEX Primers

Improves the adhesion of ARDEX products. Specific substrate preparation requirements are provided in the individual Technical Brochures for each ARDEX product.

ARDEX P 51™

Install over: standard absorbent dry concrete substrates and other substrates in specialized applications; over wood use ARDEX GS-4™ or ARDEX Liquid BackerBoard®. Non-porous substrates must be primed with ARDEX P 82™ Ultra Prime.

Key Features

- Solvent-free
- Concentrated primer - dilutes with water
- Seals the substrate
- Interior use

Installation

- **Packaging:** 1 gallon (3.79 L) plastic bottle / 4 gallon (15.14 L) plastic pail
- **Coverage:** 400 to 600 sq. ft. per gallon (37 to 55 m²)
- **Dry time:** Min. 3 hours, max. 24 hours; 1 to 3 hours between coats if double priming

Performance

- **VOC:** 0 g/L

ARDEX P 82™

Install over: smooth, non-absorbent substrates such as ceramic and other stone tiles, terrazzo, epoxy and metal decking; ARDEX P 82 is also used over wooden subfloors, including plywood and strip wood, as well as over cutback and other non-water-soluble adhesive residues.

Key Features

- Solvent-free
- Waterborne two-component
- Seals the substrate
- Interior use

Installation

- **Packaging:** Two 1/2 gallon containers (1.89 L)
- **Coverage:**
 - 300 to 400 sq. ft. per gallon over wood substrates
 - 400 to 500 sq. ft. per gallon over burnished concrete and over ceramic and quarry tile
 - 500 to 600 sq. ft. per gallon over epoxy, metal, and other smooth, non-porous surfaces
- **Dry time:** Min. 3 hours, max. 24 hours

Performance

- **VOC:** 0 g/L



AF 133 11/14

ARDEX PRIMERS



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com