

SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : **ARDEX P 82™ ULTRA PRIME - Resin (Part A)**
Product Code : 70011780
Trade Name/Synonyms : ARDEX P 82 Resin
Material Use : For the installation of ARDEX underlayments over non-porous, wood and metal substrates and adhesive residue on concrete.
Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.
Manufacturer's name and address:



ARDEX L.P.
400 Ardex Park Dr.
Aliquippa, PA 15001 USA

Information Telephone No. : (888) 512-7339 or (724) 203-5000
Website Address : <http://www.ardexamericas.com>
24 Hr Emergency Telephone # : **CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)**

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

: Skin sensitizer, Category 1.
Eye irritant, Category 2B.
Skin irritant, Category 2.
Specific Target Organ Toxicity (Single Exposure), Respiratory; Category 3

GHS Pictograms

:



Signal Word

: Warning

Hazard Statements

: Causes skin and eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary Statements

: Do not get in eyes, on skin or on clothing. Avoid breathing vapors or dust. Avoid prolonged contact with skin. Use in well-ventilated area. Wash thoroughly with soap and water after handling. If skin irritation or rash occurs, get medical attention/advice. Contaminated work clothes must not be allowed out of the workplace. Wash contaminated clothing before reuse. Keep container tightly closed. Store in a well-ventilated place. Store locked up. Dispose of contents/container according to local/regional/national regulations. Do not pour product down drains.

During normal usage of the product as recommended, airborne dusts will not be present. See Section 7 (Handling and Storage) for further details.

Hazards Not Otherwise Classified: None

% With Unknown Acute Toxicity : Up to 50% by weight of this product is comprised of ingredients with unknown acute inhalation toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Limestone	1317-65-3	10.00 – 30.00
2,2-bis(4-hydroxyphenyl)propane, polymer with (chloromethyl)oxirane epoxy resin	25068-38-6	5.00 – 10.00
Aliphatic glycidyl ether	2461-15-6	1.00 – 5.00
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	1.00 – 5.00
Crystalline silica	14808-60-7	0.10 – 1.00

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

SECTION 4 – FIRST AID MEASURES

- General** : Call a Poison Center or doctor if you feel unwell.
- Inhalation** : Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a doctor/physician.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Flush affected skin with soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention.
- Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- Ingestion** : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
- Notes for Physician** : Treat symptomatically.

Signs and symptoms of short-term (acute) exposure

- Inhalation* : May cause minor, temporary irritation to respiratory tract. Symptoms may include coughing.
- Skin* : May cause skin irritation. Symptoms may include redness and itching. Prolonged or repeated overexposure to dusts/vapors may cause skin sensitization.
- Eyes* : Causes irritation to eyes. Symptoms may include redness, itching, blurred vision or pain.
- Ingestion* : Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.

Effects of long-term (chronic) exposure

- : Prolonged inhalation may cause adverse lung effects with symptoms including coughing and shortness of breath. Some individuals may experience a sensitization reaction of the skin after an initial exposure. Subsequent exposures may cause a hypersensitive skin reaction (rash, swelling).

Indication of need for immediate medical attention or special treatment

- : Difficulty breathing persists after removing the person to fresh air.
Any exposure to the eye which causes irritation.
Blue color of the skin (cyanotic) after exposure.
Ingestion.

SECTION 5 – FIRE FIGHTING MEASURES

- Suitable extinguishing media** : Carbon dioxide, dry chemical powder, alcohol-resistant foam or water fog.
- Unsuitable extinguishing media** : water jet; may cause fire to spread
- Hazardous combustion products** : Carbon monoxide, carbon dioxide, and other toxic vapors and gases that are common to thermal degradation of organic compounds.
- Special fire-fighting procedures/equipment** : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.
- Environmental precautions** : Do not allow material to enter drains or contaminate ground water system.

Fire hazards/conditions of flammability

: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

: Not flammable

NFPA Rating:

: 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
Health: 2 Flammability 1 Reactivity 0 Special Hazards 0

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions

: Wear personal protective equipment resistant to the chemicals in the product. Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.

Protective equipment

: Refer to Section 8 for additional information on acceptable personal protective equipment.

Emergency Procedures

: This product does not contain any chemicals that must be reported to the EPA in the event of a spill or release. For advice on chemical spills with this product, call the emergency number listed in Section 1.
US CERCLA Reportable quantity (RQ): None reported.

Methods and materials for containment and cleaning up

: Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.

Prohibited materials

: Avoid strong oxidizing agents.

Environmental precautions

: Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system.

Reference to other sections

: See Section 13 for disposal information.

SECTION 7 – HANDLING AND STORAGE

Safe handling procedures

: Observe good hygiene standards. Use only with adequate ventilation. Do not eat, drink or smoke in the work area. Wash thoroughly after handling. Avoid contact with skin and eyes. Avoid repeated or prolonged skin contact. Avoid breathing vapors of this product. Sanding and grinding dusts may be harmful if inhaled. When removing this product from existing flooring (i.e. during a renovation), wear safety goggles and respiratory protection from dust. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.

Storage requirements

: Store in a cool, dry, well-ventilated area. Store locked up. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.

Incompatible materials

: Avoid strong oxidizing agents.

Special packaging materials

: Always keep in containers made of the same materials as the supply container.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Permissible Exposure Limits

: No exposure limits have been established for the product itself. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Limestone	1317-65-3	N/Av	N/Av	15 mg/m ³ (Total dust); 5 mg/m ³ (respirable)	N/Av

2,2-bis(4-hydroxyphenyl)propane, polymer with (chloromethyl)oxirane epoxy resin	25068-38-6	N/Av	N/Av	N/Av	N/Av
Aliphatic glycidyl ether	2461-15-6	N/Av	N/Av	N/Av	N/Av
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	N/Av	N/Av	N/Av	N/Av
Crystalline silica	14808-60-7	0.025 mg/m ³ (respirable fraction)	N/Av	0.05 mg/m ³ (respirable) (Final rule limit)	N/Av

- Engineering Controls** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor or mist generated from the handling of this product.
- Personal Protection Equipment**
- Eye / face protection** : Chemical goggles must be worn when using this product. Additionally, a face shield is recommended if splashing is possible.
- Skin protection** : Wear chemical resistant protective clothing and impervious gloves. Materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended.
- Body protection** : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact.
- Respiratory protection** : If work process generates excessive quantities of vapor or dust, or exposures in excess of any PEL, wear a NIOSH approved organic vapor respirator.
- Site safety equipment** : An eyewash station and safety shower should be made available in the immediate working area.
- General hygiene considerations** : Avoid contact with eyes, skin and clothing. Do not breathe vapors/dust. Do not eat, drink or smoke when using this product. Clean all equipment and clothing at end of each work shift.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|---|------------------------------|---|-----------------|
| Physical state | : Liquid | Appearance | : Pink liquid |
| Odor | : slight | Odor threshold | : N/Av |
| pH | : N/Av | Specific gravity | : 1.17 – 1.20 |
| Boiling point | : 212°F (100°C) | Coefficient of water/oil distribution | : N/Av |
| Melting/Freezing point | : N/Av | Solubility in water | : Miscible |
| Vapor pressure (mm Hg @ 20°C / 68°F) | : N/Av | Evaporation rate (n-Butyl acetate = 1) | : N/Av |
| Vapor density (Air = 1) | : N/Av | Volatiles (% by wt, including water) | : 35 - 40 |
| Volatile organic compounds (VOCs) | : 5.5 g/L (A + B) ASTM D2369 | | |
| Particle size | : N/Av | Flammability classification | : Not flammable |
| Flash point | : >212°F (100°C) | Lower flammable limit (% by vol) | : Not available |
| Flash point method | : Setflash closed | Upper flammable limit (% by vol) | : Not available |
| Auto-ignition temperature | : N/Av | Decomposition temperature | : Not available |
| Viscosity | : Not available | Oxidizing properties | : Not available |
- Explosion data: Sensitivity to mechanical impact / static discharge**
: Not expected to be sensitive to mechanical impact or static discharge.

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

- Reactivity** : Reacts with ammonia and amines. Reaction releases heat.
- Stability** : Stable under the recommended storage and handling conditions prescribed.
- Hazardous reactions** : Hazardous polymerization does not occur.
- Conditions to avoid** : High temperatures.
- Materials to avoid and incompatibility**
: Strong oxidizing agents.
- Hazardous decomposition products**
: None known, refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of exposure : *Inhalation*: YES *Skin Absorption*: NO *Skin and Eyes*: Yes *Ingestion*: YES

Symptoms of exposure : See Section 4.

Calculated Acute Toxicity Estimates for the Product

Inhalation : N/Av
Oral : > 5000 mg/kg
Dermal : > 6000 mg/kg

Toxicological data : See below for individual ingredient acute toxicity data.

Ingredients	LC50 (4 hr) Inhalation, rat	LD50	
		Oral, rat	Dermal, rabbit
Limestone	N/Av	6 450 mg/kg	N/Av
2,2-bis(4-hydroxyphenyl)propane, polymer with (chloromethyl)oxirane	N/Av	11 400 mg/kg	> 6 000 mg/kg
Aliphatic glycidyl ether	N/Av	7 800 mg/kg	> 2 000
Phenol, polymer with formaldehyde, glycidyl ether	N/Av	> 5 000 mg/kg	4 000 mg/kg
Crystalline silica	N/Av	> 22500 mg/kg	N/Av

Skin corrosion or irritation : Causes irritation to skin.

Serious eye damage / eye irritation : Causes irritation to eyes.

Respiratory or skin sensitization : Contains epoxy resin, which is known to cause skin sensitization reactions.

Germ cell mutagenicity : None known.

Carcinogenic status : This product contains Crystalline silica. Crystalline silica (respirable size) is classified as carcinogenic by inhalation by IARC (Group 1), ACGIH (Group A2), NTP (Group 1) and OSHA (OSHA Select carcinogen). During normal usage of the product as recommended, airborne dusts will not be present. See Section 7 for more information. No other components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive toxicity : None known.

Specific Target Organ Toxicity, Single Exposure

: May cause respiratory irritation.

Specific Target Organ Toxicity, Repeated Exposure

: None known.

Aspiration hazard : None known.

Additional information : N/Av

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

Ecotoxicological : No data is available on the product itself. Information on components is listed below.

Ecotoxicity : No data available.

Biodegradability : No data available.

Bioaccumulative potential : No data available.

Mobility in soil : No data available.

PBT and vPvB assessment : No data available.

Other adverse effects : No data available.

SECTION 13 – DISPOSAL CONSIDERATION

Handling for disposal : Handle waste according to recommendations in Section 7.

Methods of disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

Packaging : Handle contaminated packaging in the same manner as the product.
RCRA : For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None				
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None				

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:

Skin sensitizer, Category 1.

Eye irritant, Category 2B.

Skin irritant, Category 2.

Specific Target Organ Toxicity (Single Exposure) Category 3, Respiratory

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right To Know Laws

California Proposition 65: See product label for information regarding Proposition 65.

Other State Right to Know Laws:

Ingredients and State Right-to-Know Law status	N° CAS	CA	MA	MN	NJ	NY	PA	RI
Limestone	1317-65-3	No	Yes	No	Yes	No	Yes	Yes
Crystalline silica, quartz	14808-60-7	No	Yes	Yes	Yes	No	Yes	Yes

SECTION 16 – OTHER INFORMATION

HMIS Rating : * - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe
*Health: *2 Flammability 1 Physical Hazard 0 PPE: Gloves, safety glasses*

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substances List
EPA: Environmental Protection Agency
GHS: Globally Harmonized System
HPR: Hazardous Products Regulations
IARC: International Agency for Research on Cancer
Inh: Inhalation
N/Av: Not Available
N/Ap: Not Applicable
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:

ARDEX L.P.
400 Ardex Park Drive
Aliquippa, PA, U.S.A.
15001

(724) 203-5000

Visit our Website: <http://www.ardexamericas.com>

Revision date:

: 16-Dec-2020

End of Document