

# ARDEX PANDOMO® K2

## Loft Design Micro-Topping Compound

Self-drying topping for fast-track resurfacing of indoor concrete to produce a high-end, creatively designed ARDEX PANDOMO® Loft wear surface.

### Key Features

- Trowelable
- Portland cement-based
- Use over new or existing interior concrete
- Highly durable surface
- Color with  
ARDEX PANDOMO® CC Color Concentrates

### Installation

- **General priming recommendations:**
  - ARDEX EP 2000™ Substrate Preparation Epoxy Primer
- **Packaging:** 55 lbs. (25 kg)
- **Coverage:** 100 to 120 ft<sup>2</sup> (9.3 to 11.1 m<sup>2</sup>) per bag in 2 coats
- **Thickness:**
  - Install from 1/16" up to 3/16" (1.5 to 4.5 mm)
- **Working Time:** 10 minutes
- **Walkable:** 3 hours after second coat
- **Begin Processing:** 6 to 12 hours
- **Seal with ARDEX PANDOMO® ES/PS Protective Wear Layer System**

### Performance

- **ASTM C191 Initial Set:** Approx. 10 minutes
- **ASTM C191 Final Set:** Approx. 45 minutes
- **ASTM C109 mod (air cure only) Compressive Strength:** 4600 psi (323 kg/cm<sup>2</sup>) at 28 days
- **ASTM C348 Flexural Strength:** 1400 psi (98 kg/cm<sup>2</sup>) at 28 days



For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google play.



Refer to the technical data sheet at [www.ardexamericas.com](http://www.ardexamericas.com) or call 888-512-7339 prior to installation. For free ARDEX product training, click on ARDEX Academy.

© 2014 ARDEX Engineered Cements, L.P. All rights reserved.

AF397 06/15

ARDEX®  
PANDOMO



AMERICAS

888-512-7339

+1-724-203-5000

[www.ardexamericas.com](http://www.ardexamericas.com)