

ARDEX PANDOMO® ES/PS

Clear Waterborne Epoxy Floor Primer

Clear Waterborne Two-Part Urethane Protective Wear Layer

ARDEX PANDOMO® ES

Waterborne, two-part epoxy base coat primer. Use as a system with ARDEX PANDOMO® PS Urethane Protective Wear Layer to seal and protect.

Key Features

- Designed for ARDEX PANDOMO® CF1, CF3, and K2
- Interior use

Installation

- **Packaging:** 1 gallon (Part A: 0.80 gal; Part B: 0.20 gal) (Part A: 3 L Part B .75L)
- **Coverage:** 250 to 300 ft² (23 to 28 m²) per unit
- **Installation:**
 - 5 to 7 mils wet, which yields 2 to 3.5 mils dry (127 to 178 / 50 to 90 microns)
- **Pot Life:** 2 hours
- **Dry Time:** 2 to 4 hours to touch
- **Apply ARDEX PANDOMO® PS:** 4 to 6 hours

Performance

- **Solids content:** 43% (+/- 2%) by weight
- **Adhesion:** > 425 psi (concrete failure, no delamination)
- **VOC:** 145 g/L

ARDEX PANDOMO® PS

A two-part urethane protective wear layer designed to be used as a top coat over ARDEX ES Epoxy Floor Primer.

Key Features

- Designed for ARDEX PANDOMO® CF1, CF3, and K2
- Satin finish, non-darkening
- Stain resistant
- UV-stable
- Interior use only

Installation

- **Packaging:** One 5L (16.9 fl. oz.) bottle of Part A (Base)
Two 500mL (16.9 fl. oz.) bottles of Part B (Cross Linker)
- **Coverage:** 1000 to 1050 ft² (93 to 97.5 m²) per kit
- **Pot Life:** 1 hour
- **Time to Re-coat:** 2 hours
- **Light Foot Traffic:** 24 hours
- **Full Cure:** 7 days

Performance

- **VOC:** < 110 g/L
- **Gloss Level:** Approx. 28

PANDOMO®

For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google play.



Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training, click on ARDEX Academy.

© 2016 ARDEX Engineered Cements, L.P. All rights reserved.

AF414 04/16



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com