INVINCIBLE!

FLEXBONE[®] - The Most **Advanced Single Source Uncoupling Solutions!**

ARDEX UI 720[™] FLEXBONE[®]

Floating Uncoupling Membrane



tile&stone Installation Systems

Uncoupling for Tile and Stone Installations


Substrates provide a variety of challenges for tile and stone installations. Wooden and concrete subfloors go through various cycles of expansion, contraction and deflection during the life of a floor covering due to changes in weather, moisture conditions, inherent subfloor properties, etc. Uncoupling membranes are designed to protect tile and stone installations from subfloor movement, moisture vapor transmission, and provide load distribution preventing tile and joint cracking, buckling and disbonding. ARDEX offers two unique high performance single source uncoupling system solutions that are easy to install and provide an enhanced level of safety and convenience for tile and stone installations.

FLEXBONE® An Enhanced Level of Protection

The unique FLEXBONE[®] design is the high-performance backbone for tile and stone installations delivering true 100% uncoupling, moisture vapor equalization and maximum installation protection. FLEXBONE[®] Uncoupling Systems are recommended with ARDEX high-performance polymer modified mortars for enhanced installation safety.

ARDEX UI 720[™] FLEXBONE[®] Floating Uncoupling System

- Revolutionary unbonded, floating system
- True 100% uncoupling
- Perfect for use over difficult substrates
- Ideal for frequently changed floor coverings
- Up to 50% time savings and significant cost reduction
- Prevents grout joint and tile damage
- Use with porcelain, ceramic, quarry and natural stone tiles for interior applications



True 100% Uncoupling

ARDEX UI 720[™] FLEXBONE[®] Floating Uncoupling Membrane is a revolutionary loose laid floating system providing 100% uncoupling. Since the membrane is not bonded to the substrate, the result is significant time and cost savings. ARDEX UI 720[™] FLEXBONE[®] has a unique bone shaped pattern with GripLock Technology for the highest level of bond strength. The membrane is constructed of a highly durable, flexible plastic with a glass fiber mesh laminated on the top side with self-sticking overlaps for easy seam connection. The membrane also contains more than 1,000 perforations per square foot for improved vapor pressure equalization.

Difficult Substrate? NO PROBLEM!


ARDEX UI 720[™] FLEXBONE[®] is ideal for installation over difficult indoor substrates like:

- Fresh laid, slightly damp concrete
- Linoleum and vinyl floorcoverings
- Oil contaminated floors
- Existing and cracked tile
- Painted floors
- Modified OSB
- Cutback adhesive
- Mixed substrates
- Epoxy and polished concrete floors

Change the floor... ...and be quick about it!

ARDEX UI 720TM FLEXBONE®</sup> is the perfect solution for frequently changing floors.

- Boutique retail stores
- Showrooms
- Multi-unit housing
- Tradeshow exhibits
- Subfloors with encased in-floor heating











Adhesive residue



ARDEX UI 720[™] FLEXBONE[®] ideal for:

- Residential applications
- Offices
- Hotel rooms
- Medical offices
- Boutique retail shops
- Car dealer showrooms
 Robinson Test Rating Light Commercial



ARDEX Polymer Modified Mortar

Self-adhesive mesh seam overlap

Vinyl ARDEX UI 720[™] Floor FLEXBONE[®] Floating Uncoupling Membrane with Mesh Weave

Tile

Extremely Easy Installation

- Roll out the mat
- Adhere the seams
- Flat trowel mortar into the mesh
- Comb out the mortar
- Install tile and grout



When ARDEX FLEXBONE[®] Uncoupling Membranes are used with approved ARDEX high-performance mortars and grouts, the installation is eligible for the industry best ARDEX SystemOne[™] 10 Year Warranty.









When a bonded application is desired and for wet or high traffic area applications, ask about ARDEX UI 740[™] FLEXBONE[®] Uncoupling Membrane.

www.ardexamericas.com 888-512-7339

