

## SAFETY DATA SHEET

### SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : **Henry® 1171N SureLock™ Acrylic Urethane Wood Flooring Adhesive**  
Product ID No. : 70012482  
Trade Name/Synonyms : Henry 1171N  
Material Use : Acrylic Urethane Wood Flooring Adhesive.  
Uses Advised Against : Use only as recommended in the product's Technical Data Sheet.  
**Manufacturer's name and address:**



ARDEX L.P.  
400 Ardex Park Drive  
Aliquippa, PA 15001 USA

Information Telephone No. : (724) 203-8000  
Website Address : <http://www.ardexamericas.com> or <http://www.wwhenry.com>  
24 Hr Emergency Telephone # : **CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)**

### SECTION 2 – HAZARDS IDENTIFICATION

#### GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Specific Target Organ Toxicity, Single Exposure, Category 3, Narcotic effect  
Skin Corrosion/Irritation, Category 2  
Serious Eye Damage/Eye Irritation, Category 2B.

#### GHS Pictograms



#### Signal Word

Warning.

#### Hazard Statements

May cause drowsiness or dizziness.  
Causes skin and eye irritation.

#### Precautionary Statements

Avoid breathing dust/vapors. Use only in a well-ventilated area. Wear protective gloves/protective clothing/eye protection. Wash hands and exposed skin thoroughly after handling. Take off contaminated clothing and wash before reuse. Do not subject to grinding. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents / container in accordance with federal, state, and local laws. Do not allow product to enter drains.

During normal usage of the product as recommended, airborne dusts and mists will not be present. See Sections 7 and 11 for further details.

#### Hazards Not Otherwise Classified

None

**% With Unknown Acute Toxicity** : Up to 40% by weight of this product is comprised of ingredients with unknown acute toxicity.

### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS #	% (by weight)
Limestone	1317-65-3	30 - 60
Solvent naphtha (petroleum) light aliphatic	64742-89-8	1 – 5
Crystalline silica, quartz**	14808-60-7	0.1 - 1.0

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

\*\*Note: Crystalline Silica (Quartz) is not intentionally added to this product, but is a naturally occurring component in Limestone.

### SECTION 4 – FIRST AID MEASURES

- General** : Call a Poison Center or doctor if you feel unwell.
- Inhalation** : If breathing is difficult, remove person to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: call a doctor/physician.
- Skin contact** : Remove immediately all contaminated clothing. Flush affected skin with gently flowing lukewarm water for at least 20 minutes. Seek immediate medical attention/advice.
- Eye contact** : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- Ingestion** : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.
- Notes for Physician** : Treat symptomatically.

#### Signs and symptoms of short-term (acute) exposure

- Inhalation* : May cause minor, temporary irritation to respiratory tract. Symptoms may include coughing and shortness of breath.
- Skin* : May cause skin irritation. Symptoms may include redness and itching.
- Eyes* : Causes irritation to eyes. Symptoms may include redness, itching, blurred vision or pain.
- Ingestion* : Symptoms such as gastric pain, nausea, vomiting, and diarrhea may occur.

#### Effects of long-term (chronic) exposure

- : None known.

#### Indication of need for immediate medical attention or special treatment

- : Difficulty breathing persists after removing the person to fresh air.  
Any exposure to the eye which causes irritation.  
Ingestion.

### SECTION 5 – FIRE FIGHTING MEASURES

- Suitable extinguishing media** : Carbon dioxide, dry chemical powder, foam, or water fog or spray.
- Unsuitable extinguishing media** : None known.
- Hazardous combustion products** : Carbon monoxide, carbon dioxide, nitrogen oxides, and other toxic vapors and gases that are common to thermal degradation of organic compounds.
- Special fire-fighting procedures/equipment** : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all equipment and surfaces exposed to fumes.
- Environmental precautions** : Do not allow material to enter drains or contaminate ground water system.
- Fire hazards/conditions of flammability**

: Not flammable under normal conditions of use. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

**Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)**

: Not flammable

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : Restrict access to area until completion of clean-up. All persons dealing with clean-up should wear the appropriate chemically protective equipment.
- Protective equipment** : Refer to Section 8 for additional information on personal protective equipment.
- Emergency Procedures** : This product does not contain chemicals requiring EPA notification for spills. In case of a chemical spill, call the emergency telephone number listed in Section 1. US CERCLA Reportable quantity (RQ): None reported.
- Methods and materials for containment and cleaning up** : Ventilate area of release. Stop spill or leak at source if safely possible. Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with warm soapy water. Notify the appropriate authorities as required.
- Prohibited materials** : Avoid strong oxidizing agents
- Environmental precautions** : Do not allow product to enter drains or waterways. Do not allow material to contaminate ground water system.
- Reference to other sections** : See Section 13 for disposal information.

**SECTION 7 – HANDLING AND STORAGE**

- Safe handling procedures** : Observe good hygiene standards. Use only with adequate ventilation. Wash thoroughly after handling. Avoid breathing dust or vapors of this product. Sanding and grinding dusts may be harmful if inhaled. When removing this product from existing flooring (i.e. during a renovation), wear safety goggles and respiratory protection from dust due to grinding, chipping, or shot blasting. Wear protective clothing to prevent skin contact. Promptly remove any clothing that becomes contaminated. Clean contaminated clothing before reuse. Keep container tightly closed.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Avoid storing in direct sunlight. Store in original container. Keep tightly closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning.
- Incompatible materials** : See Section 10.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

**SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Permissible Exposure Limits** : No exposure limits have been established for the product itself. Below are exposure limits for the components in the product.

Ingredients	CAS #	ACGIH TLV		OSHA PEL	
		TWA	STEL	PEL	STEL
Limestone	1317-65-3	TLV Withdrawn In 2007	N/Av	15 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (respirable)	N/Av
Solvent naphtha (petroleum) light aliphatic	64742-89-8	300 ppm	N/Av	500 ppm	N/Av
Crystalline silica, quartz	14808-60-7	0.025 mg/m <sup>3</sup> (respirable fraction)	N/Av	0.05 mg/m <sup>3</sup> (respirable) (Final rule limit)	N/Av

**Engineering Controls** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any vapor generated from the handling of this product.

**Personal Protection Equipment**

- Eye / face protection** : Wear safety glasses or safety goggles when using this product
- Skin protection** : Wear chemical resistant protective clothing and impervious gloves. Materials such as nitrile rubber or Viton (fluorocarbon rubber) are recommended.
- Body protection** : Where extensive exposure to product is possible, wear resistant coveralls, apron and boots to prevent contact.
- Respiratory protection** : If work process generates excessive quantities of vapor, or if exposures exceed any PEL, wear an appropriate organic vapor respirator. Wear a NIOSH-approved dust mask, rated N-95 or better, when airborne dusts are present.
- Site safety equipment** : An eyewash station and safety shower should be made available in the immediate working area.
- General hygiene considerations** : Avoid breathing vapors/dust. Clean all equipment and clothing at end of each work shift.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

- |   |                           |   |                            |
|---|---------------------------|---|----------------------------|
| <b>Physical state</b>                       | : Paste                   | <b>Appearance</b>                             | : Yellowish-beige paste    |
| <b>Odor</b>                                 | : mild solvent odor       | <b>Odor threshold</b>                         | : N/Av                     |
| <b>pH</b>                                   | : 8.0 – 8.5               | <b>Specific gravity</b>                       | : 1.40 – 1.50              |
| <b>Boiling point</b>                        | : > 212°F (> 100°C)       | <b>Coefficient of water/oil distribution</b>  | : N/Av                     |
| <b>Melting/Freezing point</b>               | : N/Av                    | <b>Solubility in water</b>                    | : Dispersible              |
| <b>Vapor pressure (mm Hg @ 20°C / 68°F)</b> | : N/Av                    | <b>Evaporation rate (n-Butyl acetate = 1)</b> | : N/Av                     |
| <b>Vapor density (Air = 1)</b>              | : N/Av                    | <b>Volatiles (% by weight)</b>                | : 12 – 14 (includes water) |
| <b>Volatile Organic Compounds (VOCs)</b>    | : 16 g/L SCAQMD Rule 1168 |   |                            |
| <b>Particle size</b>                        | : N/Av                    | <b>Flammability classification</b>            | : Not flammable            |
| <b>Flash point</b>                          | : >200°F (93.3°C)         | <b>Lower flammable limit (% by vol)</b>       | : Not available            |
| <b>Flash point method</b>                   | : Setaflash closed        | <b>Upper flammable limit (% by vol)</b>       | : Not available            |
| <b>Auto-ignition temperature</b>            | : N/Av                    | <b>Decomposition temperature</b>              | : Not available            |
| <b>Viscosity</b>                            | : Not available           | <b>Oxidizing properties</b>                   | : Not available            |
- Explosion data: Sensitivity to mechanical impact / static discharge**  
: Not expected to be sensitive to mechanical impact or static discharge.

**SECTION 10 – REACTIVITY AND STABILITY INFORMATION**

- Reactivity** : Does not react.
- Stability** : Stable under the recommended storage and handling conditions prescribed.
- Hazardous reactions** : Hazardous polymerization does not occur.
- Conditions to avoid** : High temperatures.
- Materials to avoid and incompatibility** : Oxidizing agents.
- Hazardous decomposition products** : None known, refer to hazardous combustion products in Section 5.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

- Routes of exposure** : *Inhalation*: YES    *Skin Absorption*: NO    *Skin and Eyes*: YES    *Ingestion*: YES
- Symptoms of exposure** : See Section 4.
- Calculated Acute Toxicity Estimates for the Product**
- Inhalation* : > 80 mg/L
- Oral* : > 7,000 mg/kg
- Dermal* : > 10,000 mg/kg
- Toxicological data** : See below for individual ingredient acute toxicity data.

Ingredients	LC50 (4 hr)	LD50	
	Inhalation, rat, mg/L	Oral, rat, mg/kg	Dermal, rabbit, mg/kg
Limestone	N/Av	6450	N/Av
Solvent naphtha (petroleum) light aliphatic	13	> 8000	3000
Crystalline silica	N/Av	N/Av	N/Av

- Skin corrosion or irritation** : May cause irritation to skin.
- Serious eye damage / eye irritation** : May cause irritation to eyes.
- Respiratory or skin sensitization** : None known.
- Germ cell mutagenicity** : None known.
- Carcinogenic status** : Not considered to be a hazard. During normal usage of the product as recommended, airborne dusts will not be present. Do not sand off excess material, following initial application. When removing adhesive from existing flooring (i.e. during a renovation), do not mechanically remove under dry conditions (e.g. blasting, chipping, mechanically pulverizing).
- Reproductive toxicity** : None known.
- Specific Target Organ Toxicity, Single Exposure** : Contains low levels of petroleum distillates. May cause Central Nervous System effects.
- Specific Target Organ Toxicity, Repeated Exposure** : Not considered to be a hazard during normal usage of the product as recommended.
- Aspiration hazard** : None known.
- Additional information** : N/Av

## SECTION 12 – ECOLOGICAL INFORMATION

- Environmental effects** : The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
- Ecotoxicity** : No data available.
- Biodegradability** : No data available.
- Bioaccumulative potential** : No data available.
- Mobility in soil** : No data available.
- PBT and vPvB assessment** : No data available.
- Other adverse effects** : No data available.

## SECTION 13 – DISPOSAL CONSIDERATION

- Handling for disposal** : Handle waste according to recommendations in Section 7.
- Methods of disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
- Packaging** : Handle contaminated packaging in the same manner as the product.
- RCRA** : For disposal of unused or waste material, check with local, state and federal environmental agencies.

## SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
<b>TDG</b>	<b>None</b>	This product is not regulated according to Canadian TDG regulations.	<b>None</b>	<b>None</b>	<b>None</b>
<b>TDG Additional Information</b>	<b>None</b>				
<b>49 CFR/DOT</b>	<b>None</b>	This product is not regulated according to US DOT regulations.	<b>None</b>	<b>None</b>	<b>None</b>

49 CFR/DOT Additional Information	None
-----------------------------------	------

**IATA** : Not regulated for Air Transport  
**IMDG** : Not regulated for Ocean Transport  
**Marine Pollutant** : Not classified as a Marine Pollutant

## SECTION 15 – REGULATORY INFORMATION

### Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.  
Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

### US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:  
Specific Target Organ Toxicity, Single Exposure, Category 3, Narcotic effect  
Skin Corrosion/Irritation, Category 2  
Serious Eye Damage/Eye Irritation, Category 2B.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The threshold for this product is 10,000 pounds.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above de minimus concentrations.

U.S. State Right to Know Laws

California Proposition 65: See the product label for information about California Proposition 65.

Other State Right to Know Laws: Limestone [CAS# 1317-65-3] (MA, NJ, PA, RI); Crystalline silica [CAS# 14808-60-7] (MA, MN, NJ, PA, RI).

## SECTION 16 – OTHER INFORMATION

**HMIS Rating** : \* - Chronic Hazard 0 - Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe  
*Health: 1 Flammability 1 Physical Hazard 0*  
Recommended PPE: Gloves, safety glasses

**Legend** : ACGIH: American Conference of Governmental Industrial Hygienists  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
DOT: Department of Transportation  
DSL: Domestic Substances List  
EPA: Environmental Protection Agency  
GHS: Globally Harmonized System  
HPR: Hazardous Products Regulations  
IARC: International Agency for Research on Cancer  
Inh: Inhalation  
N/Av: Not Available  
N/Ap: Not Applicable

NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration  
PEL: Permissible exposure limit  
RCRA: Resource Conservation and Recovery Act  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

#### **Disclaimer of Liability**

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product. No warranty of any kind is given or implied. ARDEX L.P. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

**Prepared By:**  
ARDEX L.P.  
400 Ardex Park Drive  
Aliquippa, PA, U.S.A.  
15001

(724) 203-8000  
Visit our Website

: <http://www.ardexamericas.com> or <http://www.wwhenry.com>

**Revision date:** : 11-Nov-2021

**End of Document**