

HENRY®

The Professional's Formula For Success™



HENRY® 1171N SureLock™ Acrylic Urethane Wood Flooring Adhesive



A premium high-solids, acrylic-urethane adhesive used for almost all types of interior wood flooring that are recommended for glue-down installations.

Use for: Solid wood up to 3/4" thick and 5" wide, parquet up to 5/16" thick, engineered wood plank up to 3/4" thick and 5" wide, and cork sheet underlayment. Note: Use only for flooring structures that are recommended for glue-down installation.

Key Features & Benefits:

- Best of both worlds - Ease & high performance of acrylic systems, plus the toughness of urethanes
- Excellent Initial Grab - Holds flooring securely during installation
- Superior Bond and Rebond - Assures long term integrity and reduces hollow spots
- Contributes towards LEED® points

Bonds To:

On all grade levels: concrete, well-bonded cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), cork sheet underlayments, existing well bonded, non-cushioned vinyl tile and sheet flooring.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)



Coverage:

**Solid Wood more than 7/16" thick;
Engineered Wood Plank: V-Notch**
1/4"D x 3/16"W x 5/16"A
45-55 sq.ft. / gal.

Cork Sheet Underlayment: Sq. Notch
1/16"D x 1/16"W x 1/16"A
115-125 sq.ft. / gal.

**Thin-gauged Solid Wood 7/16" thick or less:
V-Notch**
1/4"D x 3/16"W x 1/2"A
75-85 sq.ft. / gal.

Parquet: Sq. Notch
3/32"D x 3/32"W x 3/32"A
70-80 sq.ft. / gal.

Parquet: U-Notch
3/32"D x 1/8"W x 1/8"A
70-80 sq.ft. / gal.

SystemOne™

GREENLINE
ENVIRONMENTAL TECHNOLOGY

© 2016 The W.W. HENRY Company, L.P. All rights reserved.
The W.W. Henry Company • 400 Ardex Park Drive • Aliquippa, PA 15001 USA
(800) 232-4832 (Phone) • (724) 203-8000 (Phone) • (724) 203-5001 (Fax)

HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com