



HENRY[®] 263

WeatherPro[™]

Outdoor Carpet Adhesive

Our best outdoor carpet adhesive

Waterproof after 2 hours

For all weather use

Ample working time

Excellent initial grab reduces edge curl

No open time required - install immediately

Excellent long-term bond integrity

Great for patios, boats and decks

Outdoor use only

Excellent trowelability

Trowels & Coverage

Recommended trowel sizes are guidelines only and are minimum requirements.



U-Notch
Smooth-Back Carpet
108-126 sq. ft. / gal.
10-12 sq. m / L



V-Notch
Rough-Back Carpet and All Installations on Rough Asphalt and
on Extremely Porous or Rough Concrete
70-80 sq. ft. / gal.
6-7 sq. m / L

ARDEX Americas
400 Ardex Park Drive
Aliquippa, PA 15001 USA
724-203-5000
888-512-7339
www.wwhenry.com

HENRY® 263 WeatherPro™

Outdoor Carpet Adhesive

Description

The Professional's Formula for Success™ when installing carpet outdoors. HENRY® 263 is waterproof within two hours after installation and can be used in wide temperature ranges.

Use For

Outdoor carpet and artificial turf. Not for use with vinyl-backed or urethane-backed carpet.

Bonds To

Concrete, asphalt paving and other clean, sound, solid paving surfaces and cementitious underlayments. Untreated, exterior or marine-grade plywood decking; please note that we cannot be responsible for failures resulting from deterioration of the plywood itself. Do not install over plank decking. Substrates that have been painted, stained, or otherwise coated must be tested to ensure compatibility with adhesive. Do not install over rubber or asphalt roofing.

Refer to the flooring manufacturer's specific recommendations for suitable substrates. Please note that all substrates must be sound, solid and well bonded.

Preparation

This adhesive is for outdoor use only.

Refer to the flooring manufacturer's specific recommendations.

Acceptable installation temperatures range from 40°F (4°C) to 100°F (38°C).

Substrate must be clean and dry. Mechanically remove dirt, wax, grease, paints, oils, sealers, curing compounds and all foreign matter that would interfere with proper adhesion.

Installation

Full spread the adhesive using the proper trowel. Recommended trowel sizes are guidelines only, and are minimum requirements. Rough, porous concrete or asphalt paving and heavily textured carpet backings may require deeper notches. A 100% transfer of adhesive into the carpet backing, while maintaining full coverage of the substrate, must be obtained.

Install carpet immediately into wet adhesive. Do not allow a heavy film to form on surface of the adhesive. If the adhesive dries or skins over, it must be scraped up, and fresh adhesive needs to be applied. Cut, fit and reposition within 30 minutes. Working time will vary based on jobsite conditions, such as substrate temperature and humidity. Lift a newly laid area occasionally to make sure adhesive is transferring fully to the back.

Carpeting and turf with smooth, solid backings require the use of a light roller. Apply firm pressure using a 2-foot length of carpet tube or similar. Avoid squeezing adhesive up at the seams. For all other backing types, roll the flooring with a 75 to 100 lb. roller across width and length, as recommended by the flooring manufacturer.

Cut and seal all seams as recommended by the carpet manufacturer. Seams in rubber-backed goods may peak slightly after fitting, and small bubbles may appear in the field. These come from temporary swelling of the rubber back and will stay down when the adhesive starts to set.

Clean Up

Remove wet adhesive residue with a clean, white cloth dampened with soapy water. Use mineral spirits for dried adhesive residue. When using mineral spirits, carefully follow the recommendations of the manufacturer, and test a small area before proceeding to make sure it does not damage the surface being cleaned.

Warranty

10-Year Limited HENRY'S Best Warranty. Failure to follow written directions will void the warranty. For complete warranty details, please visit www.wwhenry.com.

Note

FOR PROFESSIONAL USE ONLY.

Freeze/Thaw Stable to 10°F (-12°C). Avoid lower temperatures or multiple freeze/thaw cycles.

Shelf life is 1 year, if unopened.

VOC: 325 g/L, calculated and reported, SCAQMD 1168

Do not reuse container. Dispose of container and adhesive residue in accordance with federal, state and local waste disposal regulations. Do not flush adhesive down drains.

Precaution

Carefully read and follow all precautions and warnings on the product label. For complete safety information, please refer to the Safety Data Sheet (SDS) available at www.wwhenry.com.

IMPORTANT TECHNICAL UPDATES

Technical update effective 10-16-18:
ARDEX / HENRY Adhesives and Gypsum Substrates

Made in the USA.
© 2020 ARDEX, L.P. All rights reserved.
Content updated 09-17-2020. Published 5-12-2023. Supersedes all previous versions. Check www.ardexamericas.com for most recent version and for technical updates, which may supersede the information herein.

09/2020

Visit www.youtube.com/ARDEX101 to watch ARDEX Americas product videos.

For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.



ARDEX Americas
400 Ardex Park Drive
Aliquippa, PA 15001 USA
Tel: 724-203-5000
www.ardexamericas.com