

HENRY®

The Professional's Formula For Success™



HENRY® 420

Clear VCT (Vinyl Composition Tile) Floor Adhesive



Designed to install vinyl composition tile (VCT) in residential and commercial installations. Dries clear and has strong initial grab and ultimate bond strength.

Use for: Vinyl composition tile (VCT). Not for use with solid vinyl tiles and planks or other vinyl-backed floor structures.

Key Features & Benefits:

- Up to 18-hour working time – ideal for large commercial installations
- Moisture and alkali resistant – up 90% RH and pH of 11
- Can be used over cutback adhesive residue – reduces subfloor preparation

Bonds To:

Porous: Concrete, cementitious underlayments, APA grade underlayment plywood (untreated) and radiant heated subfloors where temperatures do not exceed 85°F (29.4°C) on all grade levels. Can also be used over properly primed gypsum underlayments (above-grade only).

Non-porous: Existing, well-bonded, non-cushion-backed vinyl tile and sheet flooring and existing “cutback” adhesive.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)



Coverage:

Extended Coverage: U-Notch
1/32”D x 1/16”W x 5/64”A
250 - 300 sq. ft. / gal.

Long Working time: U-Notch
1/16”D x 1/16”W x 3/32”A
150 - 250 sq. ft. / gal.

HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com