

HENRY®

The Professional's Formula For Success™

HENRY® 622 VinylBond™

Premium High Strength Vinyl Flooring Adhesive



A premium, high strength, professional grade wet-set pressure sensitive adhesive

Use for

Commercial and residential permanent installation of luxury vinyl tile, plank and vinyl-backed sheet flooring. Can be used over well-bonded, properly primed gypsum underlayments (above-grade only).

Key Features and Benefits:

- Outstanding initial grab and bond strength
- Moisture and alkali resistant up to 90% RH and pH 11
- Meets the emissions requirement of CHPS 1350
- Contributes towards LEED® points

Bonds To

Concrete, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), terrazzo, ceramic tile, metal, certain epoxy coatings and existing, fully adhered, non-cushion backed resilient on all grade levels.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

Coverage:

Sq. Notch
1/16"D x 1/16"W x 1/16"A
Up to 250 ft² / gal.



SystemOne

GREENLINE
ENVIRONMENTAL TECHNOLOGY



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com