

# HENRY®

The Professional's Formula For Success™



## HENRY® 630 PeachPro™ Pressure Sensitive Flooring Adhesive



Premium, pressure-sensitive adhesive with releasable bonding properties for carpet tile and carpet cushion-to-substrate installations. HENRY 630 can be used as a pressure-sensitive or a wet-set adhesive.

**Use For:** Vinyl-backed carpet tile (compatible backings only) and approved carpet cushions to a variety of substrates in double glue-down installations.

### Key Features & Benefits:

- Easy Application - Trowel, brush or roll on
- Highly Versatile - Releasable or permanent installations
- Plasticizer migration resistant – great for installing vinyl back carpet tile
- Excellent grab – helps reduce product movement during installation

### Bonds To:

**Porous:** Concrete, cementitious underlayments, APA grade underlayment plywood (untreated) and radiant heated subfloors where temperatures do not exceed 85°F (29.4°C) on all grade levels. Can also be used over properly primed gypsum underlayments (above-grade only).

**Non-porous:** Terrazzo and existing fully adhered, non-cushion backed resilient on all grade levels.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

### Coverage:

**Vinyl-Backed Carpet Tile (releasable and permanent), Non-Vinyl-Backed Carpet Tile (permanent), and Cushion-To-Substrate (permanent):** Sq. Notch  
1/16"D x 1/16"W x 1/16"A  
125-175 sq. ft. / gal.

**Releasable Vinyl-Backed Carpet Tile, Releasable Non-Vinyl-Backed Carpet Tile and Releasable Cushion-To-Substrate**  
Roller 3/16"-3/8"  
300-450 sq. ft. / gal.

**SystemOne™**

**GREENLINE**  
ENVIRONMENTAL TECHNOLOGY

# HENRY®

The W.W. Henry Company  
(888) 512-7339  
[www.wwhenry.com](http://www.wwhenry.com)