

HENRY®

The Professional's Formula For Success™



HENRY® 640 VinylLock™ Pressure Sensitive Vinyl Flooring Adhesive



Premium, high performance flooring adhesive for the installation of vinyl-backed flooring, including solid vinyl tile, plank and vinyl-backed sheet.

Use for: Commercial and residential installations of luxury vinyl tile (LVT), solid vinyl tile, plank and vinyl-backed sheet flooring.

Key Features & Benefits:

- Versatile - use as a pressure sensitive or wet-set adhesive
- Moisture and alkali resistant - up to 90% RH and pH 11
- Long working time – 2 hours
- Outstanding initial grab and bond strength

Bonds To:

On all grade levels: concrete, well-bonded cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), terrazzo, ceramic tile, metal, certain epoxy coatings and existing, fully adhered, non-cushion backed resilient on all grade levels.

Coverage:

Porous substrates: Sq. Notch
1/16"D x 1/16"W x 1/16"A
125 - 150 sq. ft. / gal.

Alternate Trowel for Extremely Flat Substrates (Minor surface imperfections, such as trowel marks or pitting, must not exceed the 1/32" height of the adhesive trowel ridge):

U-Notch
1/32"D x 1/16"W x 5/54"A
225-275 sq. ft. / gal.

Non-porous substrates: U-Notch
1/32"D x 1/16"W x 1/32"A
150 - 200 sq. ft. / gal.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com