

HENRY®

The Professional's Formula For Success™



HENRY® 663 Outdoor Carpet Adhesive



Our best latex adhesive for exterior installations of indoor/outdoor carpet.

Use For:

Indoor/outdoor carpet exterior installations only on concrete, asphalt paving, exterior and marine grade plywood decking, fiberglass, and aluminum boat decks. Not for use with vinyl-backed or urethane-backed carpet. Not for use with asphalt roofing, plank decking or treated wood.

Key Features & Benefits:

- Water resistant - after 5 days
- Strong initial grab - helps reduce edge curl
- No open time required - install immediately
- Long working time - for large installations

Bonds To:

Porous: Concrete, asphalt paving and other clean, sound, solid paving surfaces and cementitious underlayments. Untreated, exterior or marine-grade plywood decking.

Non-porous: Abraded fiberglass substrates, roughened aluminum boat decks. Substrates that have been painted, stained, or otherwise coated must be tested to ensure compatibility with adhesive. Do not install over rubber or asphalt roofing.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

Coverage:

Smooth-Back Carpet: U-Notch
3/32"D x 1/8"W x 1/8"A
108-126 sq. ft. / gal.

Rough-Back Carpet and All Installations on Rough Asphalt and on Extremely Porous or Rough Concrete: V-Notch
1/8"D x 1/8"W x 1/16"A
54-72 sq. ft. / gal.



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com