

HENRY®

The Professional's Formula For Success™



HENRY® 971 PlankPro™ Moisture-Cured Urethane Wood Adhesive



A one-part, urethane wood adhesive for all manufacturers' solid wood plank and strip (up to 1/2" thick), wood parquet and engineered wood plank in commercial and residential applications. Use for bamboo wood flooring that is coated on both sides.

Use For: All manufacturers' solid wood plank and strip (up to 1/2"), wood parquet and engineered wood plank in commercial and residential applications.

Key Features & Benefits:

- Non-slump formula - to reduce hollow spots
- Extremely versatile - Use for all installation of all manufacturers' wood flooring
- Contains no water - 95% solids
- Long working time - Allows for product repositioning

Bonds To:

On all grade levels: concrete, cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), cementitious terrazzo and existing resilient flooring. Not for use over perimeter-bonded or cushion-backed flooring. **Above grade:** can be used over properly primed gypsum underlayments.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

Coverage:

Engineered Plank and Strip, Solid Wood and Plank Strip (Up to 1/2" Thick): V-Notch
1/4"D x 3/16"W x 5/16"A
45 - 55 sq. ft. /gal.

Wood Parquet: Sq.-Notch
3/32"D x 3/32"W x 3/32"A
50 - 60 sq. ft. /gal.

SystemOne™

GREENLINE
ENVIRONMENTAL TECHNOLOGY

HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com