

Declare.

Calla® Ceiling Panels Armstrong World Industries, Inc.

Final Assembly: Pensacola, Florida, USA; Marietta, Pennsylvania, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 3.05E-01 kg CO2 eq. 

Declared Unit: 1 square foot of product

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program)

Ingredients:

Mineral Wool; Perlite; Clay; Corn Starch; Calcium Carbonate; Cellulose; Limestone; Polyvinyl acetate; Aluminum hydroxide; Acrylic Acid; Titanium dioxide; Aluminum Trihydrate; Propanol; Calcium carbonate; Kaolin; Starch; White Tint; Mica; Silica; Quartz; Diatomaceous Earth; Amorphous Silica; Sodium Salt; Polyvinyl alcohol; Proprietary Ingredient (< 1%)¹; Silicic Salt; Hydroxyethylcellulose; Black Tint; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Attapulgitic Clay; Starch derivative; Water; Red Tint; Polyethylene; Butanamide, N-(4-chloro-2,5-dimethoxyphenyl) -2-[[2,5-dimethoxy-4-[(phenylamino)sulfonyl]phenyl]azo]-3-oxo-

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0001

EXP. 01 FEB 2024

Original Issue Date: 2016