

# Declare.

## Calla® Ceiling Panels Armstrong World Industries

**Final Assembly:** Pensacola, Florida, USA

**Life Expectancy:** 30 Year(s)

**Embodied Carbon:** 0.305kg CO<sub>2</sub>eq 

**Declared Unit:** 1 square ft.

**End of Life Options:** Take Back Program (Armstrong Ceiling Recycling Program)

### Ingredients:

Mineral Wool; Perlite ore; Corn Starch; Clay; Cellulose; Calcium Carbonate; Limestone; Aluminum hydroxide; Aluminum Trihydrate; Polyvinyl acetate; Titanium dioxide; Acrylic Acid; Calcium carbonate; Barium sulfate; Propanol; Starch; Polyvinyl alcohol; Kaolin; Silica; Diatomaceous Earth; Quartz; Mica; Amorphous Silica; Sodium Salt; Hydroxyethylcellulose; Polyethylene Wax; Black Tint; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Silicic Salt; Attapulgite Clay; Iron Oxide; Water; Methylpropanoate; Polyethylene; Butanamide, N-(4-chloro-2,5-dimethoxyphenyl)-2-[[2,5-dimethoxy-4-[(phenylamino)sulfonyl]phenyl]azo]-3-oxo-

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- |   |                             |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved        | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared                     |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.1-2010

**I-14 Responsible Sourcing:** Not Applicable