

CALLA®
Square Lay-in
smooth texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)




SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



DESIGNFlex®
A New World of Choice
for Ceiling Systems

NEW A ceiling that
saves energy!
Learn more



Calla® Square Lay-in panels with Prelude® XL® 15/16" suspension system

Smooth, drywall-like finish with both Sustain® and Total Acoustics® panel performance for flexible space;
Offers excellent noise reduction and sound blocking in one product.

KEY SELECTION ATTRIBUTES

- DesignFlex® options include made-to-order sizes and colors available to ship in 3 weeks
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Calla® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Excellent combination of acoustical performance; NRC up to 0.90, and CAC 35
- USDA-Certified Biobased Product – 91%
- Washable, Scratch-resistant, Soil-resistant
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Compatible with the TechZone® Ceiling Systems
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant
- 10-Year replacement panel available for items 2820, 2821



COLORS Due to printing limitations, shade may vary from actual product.



White
(WH)



Black
(BK)



Light Grey
(MLG)



Grey Stone
(MGS)



Stone
(SE)



Mist
(MMT)



Custom Colors
Available



Sandstone
(MSS)



Fossil
(MFL)



Feldspar
(MFS)



Boxwood
(MBW)



Lilac
(MLC)




Rainstorm
(MRS)



Oat
(MOT)

Standard colors are pre-qualified to meet Sustain® portfolio requirements. Custom colors may need to be evaluated if sustainability criteria is required.

DETAILS



Calla® Square Lay-in

TechLine 877 276-7876
armstrongceilings.com/calla



*Calla Templok
Energy Saving
Ceilings*

Armstrong®
World Industries

CALLA®
Square Lay-in
smooth texture



SUSTAIN®
High Performance
Sustainable Ceiling Systems

Declare®

LEED®
WELL® LBC

UP TO 76% RECYCLED CONTENT

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes



LOCATION DEPENDENT

VISUAL SELECTION

| armstrongceilings.com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) |
|--------------------------------|------------|----------|---------------------|
| CALLA® | 1 | 2820 | 24 × 24 × 1" □ |
| 15/16" Square Lay-in | | 2820BK | 24 × 24 × 1" □ |
| | | 2821 | 24 × 48 × 1" □ |
| | | 2821BK | 24 × 48 × 1" □ |
| | | 2854 | 30 × 30 × 1" □ |
| | | 2857 | 24 × 60 × 1" □ |
| | | 2864 | 24 × 72 × 1" □ |
| | | 2878 | 30 × 60 × 1" □ |

1" Thick - 15/16" Square Lay-in

Made-to-Order Sizes

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

| Width | Length |
|----------|----------|
| 4" - 30" | 9" - 72" |

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

| UL Classified Acoustics | | Total Acoustics ¹ | Articulation Class | Fire Performance | Light Reflect* | Bio-Block | Humi-Guard+ | Certified Low VOC Emissions | CleanAssure™ | DURABILITY | | | | | Recycle Program | 30-Yr Warranty |
|-------------------------|-----|------------------------------|--------------------|------------------|----------------|-----------|-------------|-----------------------------|----------------------|------------|-------|--------|----------|------|-----------------|----------------|
| NRC | CAC | | | | | | | | Disinfectable Panels | Fog | Wash* | Impact | Scratch* | Soil | | |
| 0.85 | 35 | BEST | 170 | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | N/A | * | * | * | | | - | * | - | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | N/A | * | * | * | | | - | * | - | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |
| 0.85 | 35 | BEST | 170 | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |
| N/A | N/A | N/A | N/A | Class A | 0.85 | * | * | * | | | * | * | * | * | * | * |



MINERAL FIBER - Standard

SUSPENSION SYSTEMS

15/16"



Prelude® XL®

PHYSICAL DATA

Material

Wet-formed mineral fiber with acoustically transparent membrane

Surface Finish

Acoustically transparent membrane with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification

Type A, Form A2.2, Pattern G; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Design Considerations

Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Product is dye-lotted. Order sufficient initial quantities and attic stock to minimize possible color variation.

Acoustical Performance

CAC testing conducted using Prelude® XL® suspension system. NRC test conducted using white panels. Painted panels may experience a slight reduction in NRC due to the color painting process.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor - 2.9 (BTU units)
R Factor - 0.445 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton

2820, 2820BK - 1.0 LBS/SF; 40 SF/CTN
2821, 2821BK - 1.0 LBS/SF; 48 SF/CTN
2854 - 1.0 LBS/SF; 50 SF/CTN
2857 - 1.0 LBS/SF; 80 SF/CTN
2864 - 1.0 LBS/SF; 72 SF/CTN
2878 - 1.0 LBS/SF; 75 SF/CTN

Minimum Order Quantity

1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/calla
BPCS-5867-1024

LEED® is a trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL® and WELL Building Standard are trademarks of the International WELL Building Institute; UL® is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2024 AWI Licensing LLC

Armstrong®
World Industries