

Declare.

Cortega® Fire Guard™ Ceiling Panels Armstrong World Industries

Final Assembly: Marietta, PA; Pensacola, FL

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.216 kg CO₂e/ft² 

Declared Unit: square foot

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Calcium Carbonate; Clay; Perlite ore; Perlite; Quartz; Cellulose; Corn Starch; Titanium dioxide; Kaolin; Acrylic Acid; Silica; Diatomaceous Earth; Silicic Salt; Polyethylene Wax; Starch; Hydroxy starch; Water; Sodium Salt; Amorphous Silica; Aluminum hydroxide; Fatty Acids; Chlorite-group minerals; Talc; Sodium dimethyldithiocarbamate

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0082

EXP. 01 JUN 2026

Original Issue Date: 2022