

CORTEGA® Second Look®

Tegular
medium texture



▲ Cortega® Second Look® II panels with Suprafine® XL® 9/16" suspension system

Medium-texture panels; Economical solution with standard acoustical absorption.

KEY SELECTION ATTRIBUTES


- Cortega® Second Look® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Economical
- Geometric Scored Visuals

COLOR




White
(WH)

FACE VIEWS




Cortega® Second Look® I panels –
Scoring creates nominal 12" x 12" squares



Cortega® Second Look® II panels –
Scoring creates nominal 24" x 24" squares

DETAIL



Cortega® Second Look®

CORTEGA® Second Look®

Tegular
medium texture



Declare®

GREENGUARD
Gold Certified
(details below)

LEED®
WELL™ LBC

UP TO 55% RECYCLED CONTENT

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/excised producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

LOCATION DEPENDENT

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

VISUAL SELECTION

PERFORMANCE SELECTION

\$\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
CORTEGA® Second Look® I 15/16" Angled Tegular	11	2765	24 x 48 x 3/4"	

CORTEGA® Second Look® II 15/16" Angled Tegular	11	2758	24 x 48 x 3/4"	
--	----	------	----------------	--

2767	24 x 48 x 3/4"	
------	----------------	--

9/16" Angled Tegular	27	2776	24 x 48 x 3/4"	
----------------------	----	------	----------------	--

UL Classified Acoustics	Total Acoustics¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
0.55 35 •	N/A	Class A	0.81	N/A	Std	•	Std	Std	•	1-Yr
0.55 40 •	N/A	Fire Guard	0.81	N/A	Std	•	Std	•	•	1-Yr
0.55 35 •	N/A	Class A	0.81	N/A	Std	•	Std	•	•	1-Yr
0.55 30	N/A	Class A	0.81	N/A	Std	•	Std	•	•	1-Yr

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Cortega®/Cortega® Second Look®: wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

Fire Guard: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type III, Form 2, Pattern C D K

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions (PB suffix items only)
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED® WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy
See all LCA information on our EPDs.

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818



High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
2765, 2758, 2767, 2776 – R Factor – 1.5 (BTU units);
R Factor – 0.28 (Watts units)

Weight; Square Feet/Carton
2765, 2767 – 0.73 lbs/SF; 80 SF/ctn
2758 – 1.26 lbs/SF; 64 SF/ctn
2776 – 0.70 lbs/SF; 80 SF/ctn

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/cortega
BPCS-3022-123

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2023 AWI Licensing LLC

Armstrong®
CEILING & WALL SOLUTIONS

MINERAL FIBER – Standard

