

CORTEGA® Second Look®

Tegular
medium texture



Cortega Second Look II panels with Suprafine XL 9/16\"/>

Medium-texture panels; economical solution with standard acoustical absorption.

KEY SELECTION ATTRIBUTES


- Cortega® Second Look® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Made in the U.S.A. of domestic and global content
- Economical
- Build America, Buy America (BABA) Act compliant
- Geometric Scored Visuals

COLOR




White
(WH)

FACE VIEWS




Cortega® Second Look® I panels –
Scoring creates nominal 12\"/>



Cortega® Second Look® II panels –
Scoring creates nominal 24\"/>

DETAIL



Cortega® Second Look®

CORTEGA® Second Look®

Tegular
medium texture



LEED® WELL™ LBC

UP TO 55% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting materials

lighting quality

acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
CORTEGA® Second Look® I 15/16" Angled Tegular	11	2765	24 × 48 × 3/4"	

CORTEGA® Second Look® II 15/16" Angled Tegular	11	2758	24 × 48 × 3/4"	
---	----	------	----------------	--

2767	24 × 48 × 3/4"	
------	----------------	--

9/16" Angled Tegular	27	2776	24 × 48 × 3/4"	
----------------------	----	------	----------------	--

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC + CAC =										
0.55 35 *	N/A	Class A	0.81	N/A	Std	*	Std	Std	*	1-Yr
0.55 40 *	N/A	Fire Guard™	0.81	N/A	Std	*	Std	*	*	1-Yr
0.55 35 *	N/A	Class A	0.81	N/A	Std	*	Std	*	*	1-Yr
0.55 30	N/A	Class A	0.81	N/A	Std	*	Std	*	*	1-Yr

Red Numbers are Fire Guard items.

¹ Total Acoustics¹ ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Surface Finish
Cortega®/Cortega® Second Look®: Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

Fire Guard: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type A, Form A1.2, Pattern E; Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
2765, 2758, 2767, 2776 – R Factor – 1.5 (BTU units);
R Factor – 0.28 (Watts units)

Weight; Square Feet/Carton
2765, 2767 – 0.73 LBS/SF; 80 SF/CTN
2758 – 1.26 LBS/SF; 64 SF/CTN
2776 – 0.70 LBS/SF; 80 SF/CTN

Minimum Order Quantity
1 carton