

## Dune Ceiling Panels Armstrong World Industries

Final Assembly: Marietta, Pennsylvania, USA; Macon, Georgia,

USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.224 kg CO<sub>2</sub> ▼

**Declared Unit: 1 ft2** 

End of Life Options: Take Back Program (Armstrong Ceilings

Recycling Program)

## Ingredients:

Perlite; Glass, oxide, chemicals; Cellulose; Mineral Wool; Corn Starch; Calcium Carbonate; Clay; Silica; Diatomaceous Earth; Fatty acids, C14-18 and C16-18-unsatd., calcium salts; Proprietary Ingredient (< 1%)<sup>1</sup>; Glucose; Water; Lubricating oil; Polyvinyl acetate; Hydroxy starch; Starch; Fatty Acids; Lubricating Oil; Quartz; Starch, 2-hydroxyethyl ether; Titanium dioxide; Calcium carbonate

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

## Living Building Challenge Criteria: Compliant

## I-13 Red List:

☐ LBC Red List Free

LBC Red List Approved

% Disclosed: 99% at 100ppm VOC Content: Not Applicable

Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0035 EXP. 01 MAR 2024

Original Issue Date: 2018