

FINE FISSURED™ FINE FISSURED™ High NRC

Tegular
medium texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)



SUSTAIN®
High Performance
Sustainable
Ceiling Systems

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Fine Fissured Tegular panels with Prelude XL suspension system



See more photos at:
armstrongceilings.com/photogallery

Economical panels; non-directional with standard or Total Acoustics® panel performance.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Fine Fissured panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Four new colors
- Mold- and mildew-resistant surface
- Options provide excellent combination of acoustical performance NRC up to 0.75, CAC up to 35, and Articulation Class 170
- Fine Fissured™ School Zone® items help comply with ANSI S12.60 Classroom Guidelines
- Non-directional visual reduces scrap and installation time
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- 10-Year replacement panel available for items 1732, 1734
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant




COLORS Due to printing limitations, shade may vary from actual product.



Item 1732 is available in colors.
All other items are available in White only.
Colored ceilings are dye-lotted and should be segregated by dye lot. Do not mix.

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Fine Fissured™ Beveled Tegular
2. Fine Fissured™ Angled Tegular
3. Fine Fissured™ Tegular with Suprafine® 9/16" suspension system

FINE FISSURED™ FINE FISSURED™ High NRC

Tegular
medium texture



Declare.

RECYCLED
CONTENT

UP TO
73%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No. ♦	Dimensions (Inches)
FINE FISSURED™ High NRC	13	1756	24 × 24 × 7/8" □
15/16" Angled Tegular		1757	24 × 48 × 7/8" □
9/16" Beveled Tegular	29, 44, 48, 52, 56	1758	24 × 24 × 7/8" □
		1759	24 × 48 × 7/8" □
FINE FISSURED™ 15/16" Angled Tegular	12	1732__	24 × 24 × 5/8" □
		1833	24 × 24 × 5/8" □
		1733	24 × 48 × 5/8" □

PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.75 *	35 *	BETTER ()))	170 *	Class A	0.85 *	*	*	*	*	Std	*	*	*
0.75 *	35 *	BETTER ()))	170 *	Class A	0.85 *	*	*	*	*	Std	*	*	*
0.75 *	35 *	BETTER ()))	170 *	Class A	0.85 *	*	*	*	*	Std	*	*	*
0.55 *	35 *	N/A	N/A	Class A	0.82* *	*	*	*	*	Std	*	*	*
0.55 *	35 *	N/A	N/A	Fire Guard™	0.82 *	*	*	*	*	Std	Std	*	*
0.55 *	35 *	N/A	N/A	Class A	0.82 *	*	*	*	*	Std	Std	*	*

MORE ITEMS ►


Red Numbers are Fire Guard items.

¹ Total Acoustics* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

♦ Add 2-letter color suffix to item number when specifying or ordering (e.g., 1732 | V)

* Light reflectance value for white panels only

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies. (Class A).

ASTM E1264 Classification

Type A, Form A1.2, Pattern D; Fire Class A

Humidity/Sag Resistance

HumiGuard™ Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications (excludes items 1757 and 1759).

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 1.5 (BTU units); R Factor – 0.26 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton

1732 – 0.70 LBS/SF; 64 SF/CTN
1733 – 0.70 LBS/SF; 80 SF/CTN
1833 – 1.05 LBS/SF; 48 SF/CTN
1756, 1758 – 1.08 LBS/SF; 40 SF/CTN
1757, 1759 – 1.08 LBS/SF; 48 SF/CTN

Minimum Order Quantity

1 carton

Metric Items Available

1732M, 1733M, 1756M, 1757M, 1758M, 1759M – Metric items subject to extended lead times and minimum quantities.

TechLine 877 276-7876

armstrongceilings.com/finefissured

Armstrong®
World Industries

MINERAL FIBER – Standard

FINE FISSURED™ FINE FISSURED™ High NRC

Tegular
medium texture



Declare.

RECYCLED
CONTENT

UP TO
73%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

PERFORMANCE SELECTION

\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
FINE FISSURED™ 15/16" Angled Tegular	1	1834	24 × 48 × 5/8"

9/16" Beveled Tegular	29, 44, 48, 52, 56	1734	24 × 24 × 5/8"
-----------------------	--------------------	------	----------------

1835	24 × 24 × 5/8"
------	----------------

Made-to-Order Sizes	Width	Length
FINE FISSURED™	12" - 30"	18" - 72"

School Zone® FINE FISSURED™ 15/16" Angled Tegular	13	1717	24 × 24 × 3/4"
---	----	------	----------------

1820	24 × 24 × 3/4"
------	----------------

1824	24 × 48 × 3/4"
------	----------------

UL Classified Acoustics	Total Acoustics¹	Articulation Class	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Fog	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.55	35	N/A	N/A	Fire Guard™	0.82	*	*	*	*	Std	*	*	*
0.55	35	N/A	N/A	Class A	0.82	*	*	*	*	Std	Std	*	*
0.55	35	N/A	N/A	Fire Guard	0.82	*	*	*	*	Std	Std	*	*
0.70	40	BETTER	N/A	Class A	0.82	*	*	*	*	Std	*	*	*
0.70	35	BETTER	N/A	Fire Guard	0.82	*	*	*	*	Std	*	*	*
0.70	35	BETTER	N/A	Fire Guard	0.82	*	*	*	*	Std	*	*	*

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

MINERAL FIBER – Standard

FINE FISSURED™ FINE FISSURED™ High NRC

Tegular
medium texture



Declare.

RECYCLED
CONTENT

UP TO
73%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
School Zone® FINE FISSURED™ 9/16" Beveled Tegular	29, 44, 48, 52, 56	1719	24 × 24 × 3/4" □
		1821	24 × 24 × 3/4" □

Made-to-Order
Sizes
School Zone®
FINE FISSURED™

4-6
WEEKS
order to ship

3/4" Thick – 15/16" Angled Tegular, 9/16" Beveled Tegular

Width	Length
12" - 30"	18" - 72"

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Bio-Block	Humid-Guard+	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	Durability	Recycled Content	Recycle Program	30-Yr Warranty
0.70	40	BETTER	N/A	Class A	0.82	*	*	*	Std	*	*	*
0.70	35	BETTER	N/A	Fire Guard™	0.82	*	*	*	Std	*	*	*
N/A	N/A	N/A	N/A	Class A	0.82	*	*	*	Std	Std	*	*

Red Numbers are Fire Guard items.

¹ Total Acoustics* ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

15/16"	9/16"
Prelude® XL* Prelude® XL* Fire Guard™	Silhouette® 1/4" Reveal
	Silhouette® 1/8" Reveal
	Suprafine® Suprafine® XL* Fire Guard™
	Interlude®

PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification
Type A, Form A1.2, Pattern D; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 1.5 (BTU units); R Factor – 0.26 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1820, 1821 – 1.31 LBS/SF; 48 SF/CTN
1717, 1719 – 1.25 LBS/SF; 48 SF/CTN
1834 – 1.05 LBS/SF; 64 SF/CTN
1734 – 0.70 LBS/SF; 64 SF/CTN
1835 – 1.05 LBS/SF; 48 SF/CTN
1824 – 1.20 LBS/SF; 64 SF/CTN

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
1820M, 1821M, 1717M, 1719M, 1834M, 1734M, 1824M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/finefissured
BPCS-3026-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong®
World Industries

MINERAL FIBER – Standard