

# FISSURED™

Square Lay-in & Tegal  
medium texture

Declare.  
GREENGUARD  
Gold Certified  
(details below)

LEED® WELL™ LBC

UP TO 41% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/extended producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting materials

lighting quality

acoustics

Calculate sustainability with Green Genie™  
armstrongceilings.com/greengenie

LOCATION DEPENDENT



▲ Fissured™ Angled Tegal panels with Prelude® XL® 15/16" suspension system

Economical panels; Directional with standard acoustical performance.

## KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image





















## COLOR



## VISUAL SELECTION

## PERFORMANCE SELECTION

Dots represent high level of performance.

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	 UL Classified Acoustics	 NRC + CAC =	 Total Acoustics <sup>1</sup>	 Fire Performance	 Light Reflect	 Anti-Mold/ Mildew	 Sag Resistant	 Certified Low VOC Emissions	 Durability	 Recycled Content	 Recycle Program	 Warranty
FISSURED™ Square Lay-in 15/16" Square Lay-in 	1	756	24 x 24 x 5/8" 	0.55	30	N/A	Class A	0.79	N/A	Std	•	Std	Std	•	1-Yr
		896	24 x 24 x 5/8" 	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	•	Std	Std	•	1-Yr
		755	24 x 48 x 5/8" 	0.55	30	N/A	Class A	0.79	N/A	Std	•	Std	Std	•	1-Yr
		895	24 x 48 x 5/8" 	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	•	Std	Std	•	1-Yr
FISSURED™ Tegal 15/16" Angled Tegal 	12	705	24 x 24 x 5/8" 	0.55	30	N/A	Class A	0.79	N/A	Std	•	Std	Std	•	1-Yr
		815	24 x 24 x 5/8" 	0.55	35	N/A	Fire Guard™	0.79	N/A	Std	•	Std	Std	•	1-Yr
5/8" Thick – 15/16" Square Lay-in & Tegal															
Made-to-Order Sizes		Width	Length	N/A	N/A	N/A	Class A	0.79	N/A	Std	•	Std	Std	•	1-Yr
		12" - 30"	18" - 72"												

4-6


WEEKS

order to ship

Red Numbers are Fire Guard items.

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

## SUSPENSION SYSTEMS



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

### ASTM E1264 Classification

Type III, Form 2, Pattern C D

Fire Class A

### Humidity/Sag Resistance

Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

### VOC Emissions

GREENGUARD Gold Certified  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

### Insulation Value

755, 756, 895, 896 – R Factor – 1.5 (BTU units)

R Factor – 0.26 (Watts units)

705, 815 – R Factor – 1.6 (BTU units)

R Factor – 0.28 (Watts units)

PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS  
UL.COM/GG  
UL 2818



### 1-Year Limited Warranty

Details at armstrongceilings.com/warranty

### Weight; Square Feet/Carton

705 – 0.69 lbs/SF; 64 SF/ctn 815 – 1.08 lbs/SF; 48 SF/ctn

755 – 0.66 lbs/SF; 96 SF/ctn 895, 896 – 1.09 lbs/SF;

756 – 0.67 lbs/SF; 64 SF/ctn 64 SF/ctn

### Minimum Order Quantity

1 carton, excludes made-to-order panels

### Metric Items Available

756M, 896M, 755M, 895M, 705M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.