

FISSURED™

Square Lay-in & Tegular
medium texture

Declare.

LEED® WELL | LBC

UP TO 41% RECYCLED CONTENT

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/ biobased producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting/ materials
lighting quality
acoustics

Calculate sustainability with Ecomedes
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

\$\$\$\$



Fissured Angled Tegular panels with Prelude® XL® 15/16" suspension system

Economical panels; Directional with standard acoustical performance.

KEY SELECTION ATTRIBUTES

- Economical
- Directional fissured image
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR



VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance.

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	NRC + CAC =				Fire Performance				UL Classified Acoustics			
FISSURED™ Square Lay-in	1	756	24 × 24 × 5/8" □	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
15/16" Square Lay-in 		896	24 × 24 × 5/8" □	0.55	35*	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
		755	24 × 48 × 5/8" □	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
		895	24 × 48 × 5/8" □	0.55	35*	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
FISSURED™ Tegular	12	705	24 × 24 × 5/8" □	0.55	30	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
15/16" Angled Tegular 		815	24 × 24 × 5/8" □	0.55	35*	N/A	Fire Guard™	0.79	N/A	Std	*	Std	Std	*	1-Yr
5/8" Thick – 15/16" Square Lay-in & Tegular															
Made-to-Order Sizes		Width	Length	N/A	N/A	N/A	Class A	0.79	N/A	Std	*	Std	Std	*	1-Yr
		12" - 30"	18" - 72"												

4-6


WEEKS

order to ship

Red Numbers are Fire Guard items.

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).
Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type A, Form A1.2, Pattern D; Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value
755, 756, 895, 896 – R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)
705, 815 – R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

1-Year Limited Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
705 – 0.69 LBS/SF; 64 SF/CTN 815 – 1.08 LBS/SF; 48 SF/CTN
755 – 0.66 LBS/SF; 96 SF/CTN 895, 896 – 1.09 LBS/SF;
756 – 0.67 LBS/SF; 64 SF/CTN 64 SF/CTN

Minimum Order Quantity
1 carton, excludes made-to-order panels

Metric Items Available
756M, 896M, 755M, 895M, 705M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.