

# GEORGIAN™ GEORGIAN™ HIGH WASHABILITY

Square Lay-in & Tegular  
medium texture



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)

Georgian Beveled Tegular panels with Prelude® XL® 15/16" suspension system

Medium-texture panels with a unique splatter-painted visual and options for high washability; offer standard or Total Acoustics® panel performance.

## KEY SELECTION ATTRIBUTES

- Georgian™ is part of the Sustain® portfolio, and meets the most stringent industry sustainability compliance standards today
- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance (items 795 and 796 only)
- Unique splatter-painted visual
- Mold- and mildew-resistant surface
- High Washability items available
  - Meets USDA/FSIS guidelines for use in food processing establishments
- Durable –
  - Washable
  - Scrubable
  - Impact-resistant
  - Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

## TYPICAL APPLICATIONS


- Schools/classrooms (Items 795, 796)
- Corridors/conference rooms
- Kitchen/food preparation areas (Items 793, 794)

## COLOR



White  
(WH)

## DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Georgian™ Beveled Tegular
2. Georgian™ Beveled Tegular with Prelude® 15/16" suspension system
3. Georgian™ Beveled Tegular with Silhouette® 9/16" suspension system 1/4" Reveal

# GEORGIAN™ GEORGIAN™ HIGH WASHABILITY

Square Lay-in & Tegular  
medium texture



Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes



LOCATION DEPENDENT

## VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	
GEORGIAN™	1	764	24 × 24 × 5/8"	
15/16" Square Lay-in		763	24 × 48 × 5/8"	
15/16" Beveled Tegular	15	1752	24 × 24 × 5/8"	
9/16" Beveled Tegular	29, 44, 48, 52, 56	1753	24 × 24 × 5/8"	
GEORGIAN™ High Washability Panels, Unperforated	1	794	24 × 24 × 5/8"	
15/16" Square Lay-in		793	24 × 48 × 5/8"	
SCHOOL ZONE® GEORGIAN	1	796	24 × 24 × 3/4"	
15/16" Square Lay-in		795	24 × 48 × 3/4"	

## PERFORMANCE SELECTION


Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	Total Acoustics¹	Fire Performance	Light Reflect	Bio-Block/Mildew	Humi-Guard Sag Resist	Certified Low VOC Emissions	DURABILITY	Recycle Program	30-Yr Warranty
NRC + CAC	NRC CAC						Wash Scrub Impact Scratch		
0.55 33	N/A	Class A	0.86 *	*	*	*	N/A N/A * *	*	*
0.55 33	N/A	Class A	0.86 *	*	*	*	N/A N/A * *	*	*
0.55 35 *	N/A	Class A	0.86 *	*	*	*	N/A N/A * *	*	*
0.55 35 *	N/A	Class A	0.86 *	*	*	*	N/A N/A * *	*	*
N/A 33	N/A	Class A	0.88 *	*	*	*	* * * *	*	*
N/A 33	N/A	Class A	0.88 *	*	*	*	* * * *	*	*
0.65 35 *	GOOD	Class A	0.86 *	*	*	*	N/A N/A * *	*	*
0.65 35 *	GOOD	Class A	0.86 *	*	*	*	N/A N/A * *	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS



## PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL\* labeled).

**ASTM E1264 Classification**  
Type A, Form A1.2, Pattern G; Fire Class A

**Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor - 1.6 (BTU units)  
R Factor - 0.28 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System.  
Details at armstrongceilings.com/warranty

**Weight; Square Feet/Carton**  
763, 793 - 0.67 LBS/SF; 96 SF/CTN  
764, 794, 1752, 1753 - 0.72 LBS/SF; 64 SF/CTN  
796 - 1 LBS/SF; 48 SF/CTN  
795 - 1 LBS/SF; 64 SF/CTN

**Minimum Order Quantity**  
1 carton, excludes made-to-order panels

**Metric Items Available**  
1753M, 764M, 763M, 1752M, 796M, 795M, 794M, 793M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.