



INVISACOUSTICS™ Acoustical Ceiling & Wall Panels

Armstrong World Industries

Final Assembly: Pensacola, Florida, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.382 kg CO₂eq

Declared Unit: 1 sq. ft

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Mineral Wool; Perlite; Corn Starch; Cellulose; Calcium Carbonate; Clay; Aluminum hydroxide; Acrylic Acid; Polyvinyl acetate; Silica; Diatomaceous Earth; Polyvinyl alcohol; Titanium dioxide; Propanol; Calcium carbonate; Kaolin; Sodium Salt; Tetra Hydro Ester

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0058

EXP. 01 APR 2025

Original Issue Date: 2020

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare