

# Declare.



## INVISACOUSTICS™ Acoustical Ceiling & Wall Panels Armstrong World Industries

**Final Assembly:** Pensacola, Florida, USA

**Life Expectancy:** 30 Year(s)

**Embodied Carbon:** 0.382kg CO<sub>2</sub>eq 

**Declared Unit:** 1 square ft

**End of Life Options:** Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

### Ingredients:

Mineral Wool; Perlite ore; Corn Starch; Cellulose; Calcium Carbonate; Clay; Aluminum hydroxide; Acrylic Acid; Polyvinyl acetate; Silica; Diatomaceous Earth; Polyvinyl alcohol; Titanium dioxide; Propanol; Calcium carbonate; Kaolin; Sodium Salt; Tetra Hydro Ester

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- |   |                             |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved        | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared                     |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable