

KITCHEN ZONE™

Square Lay-in
smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Kitchen Zone 24" x 24" panels with Prelude XL 15/16" suspension system

Panels meet USDA/FSIS guidelines. A better option than vinyl-covered gypsum; panels offers a lower cost, lighter weight option, with more pieces per carton.

KEY SELECTION ATTRIBUTES

-  Kitchen Zone™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Easier to cut with less dust
- Recyclable through Armstrong Recycling Program
- Brighter visual with 20% more light reflectance than vinyl-covered gypsum
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Durable – Water-repellent, Washable, Scratch-resistant, Soil-resistant
- Smooth surface meets USDA/FSIS guidelines for use in food processing areas
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

TYPICAL APPLICATIONS

- Kitchen/food preparation areas
- Laboratories
- Cafeterias
- Lavatories/restrooms

COLOR



White
(WH)

DETAILS



- Kitchen Zone™ Lay-in
- Kitchen Zone™ Lay-in with Prelude® 15/16" suspension system

KITCHEN ZONE™

Square Lay-in
smooth texture



Declare.

RECYCLED
CONTENT

UP TO
36%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
--------------------------------	------------	----------	---------------------

KITCHEN ZONE™ 1 **673** 24 × 24 × 5/8" ☐

15/16" Square Lay-in



672 24 × 48 × 5/8" ☐

PERFORMANCE SELECTION

Dots represent high level of performance.


\$\$\$

NRC + CAC =		Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels	DURABILITY					Recycle Program	30-Yr Warranty
									Fog/Spray	Wipe	Water Repel	Wash	Scratch	Soil	
N/A	33	N/A	Class A	0.89	*	*	*	*	*	*	*	*	*	*	*
N/A	33	N/A	Class A	0.89	*	*	*	*	*	*	*	*	*	*	*

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

SUSPENSION SYSTEM

15/16"



Prelude®

PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: ASTM E84 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less.

ASTM E1264 Classification

Type A, Form A3.2, Pattern G; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

Application Consideration

Not designed for use in close proximity to commercial grease ducts.

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/ Carton

672 – 0.67 LBS/SF; 96 SF/CTN
673 – 0.82 LBS/SF; 64 SF/CTN

Minimum Order Quantity

1 carton