

LYRA® Concealed  
 Concealed Suspension  
 smooth texture




Lyra Concealed panels with Prelude® XL® 15/16" suspension system

CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)



**DESIGNFlex®**  
 A New World of Choice  
 for Ceiling Systems

plus capabilities  
 to do more



[armstrongceilings.com/capabilities](http://armstrongceilings.com/capabilities)  
 See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)

Smooth, drywall-like visual with fully-concealed suspension and downward accessibility;  
 ideal for projects where plenum space is limited. Offers high sound absorption.

**KEY SELECTION ATTRIBUTES**

- DesignFlex® options include made-to-order sizes and colors available to ship in 3 weeks
- Large format acoustical panels
- Downward accessible for minimal plenum height
- Outstanding acoustical performance for open plan areas, both Noise Reduction and Articulation Class NRC 0.90, AC up to 190
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Smooth, clean, durable finish – Washable, Scratch-resistant, Soil-resistant
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Available with factory-cut holes for USA!® trimless downlight fixture integration

**COLORS** Due to printing limitations, shade may vary from actual product.



**DETAILS**



1. Lyra® Concealed
2. Lyra® Concealed with Prelude® XL® HD 15/16" suspension system

# LYRA® Concealed

## Concealed Suspension

### smooth texture

**LEED® WELL™ LBC**

UP TO **71% RECYCLED CONTENT**

Calculate sustainability with Green Genie® [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/repurposed producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting/low materials
- lighting quality
- acoustics

LOCATION DEPENDENT

### VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
LYRA® Concealed	1	8430	30 × 30 × 7/8"
Quick Kerf Edge		8433	24 × 48 × 7/8"
		8431	24 × 72 × 7/8"
Non-support Edge		8432	24 × 96 × 7/8"
		8434	48 × 48 × 7/8"

Made-to-Order Sizes	1 Ctn Min FASTSAFE 3 WEEKS order to ship	Width (short side)	Length (long side)
Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email <a href="mailto:TechLine@armstrongceilings.com">TechLine@armstrongceilings.com</a>		24" - 96"	24" - 30"
		30-1/16" - 48"	24" - 48"

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

\* Advertised values for light reflectance, wash and scratch resistance are applicable to white tiles only

### PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$


UL Classified Acoustics	Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect*	Anti-Mold/Mildew	Sag Resistant	Fog	Wash*	Scratch*	Soil	30-Yr Warranty
0.90	N/A	N/A	190	Class 0.88* A	.	.	.	.	.	.	.
0.90	N/A	N/A	190	Class 0.88* A	.	.	.	.	.	.	.
0.90	N/A	N/A	190	Class 0.88* A	.	.	.	.	.	.	.
0.90	N/A	N/A	190	Class 0.88* A	.	.	.	.	.	.	.
0.90	N/A	N/A	190	Class 0.88* A	.	.	.	.	.	.	.
N/A	N/A	N/A	N/A	Class 0.88* A	.	.	.	.	.	.	.

### FIXTURE TRIM

Item No.	Color	Length	Pcs/Ctn
CTK4ZW	Blizzard White	4" Concealed Fixture Kit	24
CTK6ZW	Blizzard White	6" Concealed Fixture Kit	24
CTK24ZW	Blizzard White	24" Concealed Fixture Kit	24
CTK48ZW	Blizzard White	48" Concealed Fixture Kit	24
CTK72ZW	Blizzard White	72" Concealed Fixture Kit	24
CTK96ZW	Blizzard White	96" Concealed Fixture Kit	24
Other Size Fixture Trims	Blizzard White (custom colors available)	4" to 96" Trim Pieces	-

Fixture trim kits include 24 straight trim pieces and required Speed Clips. Example: For a space with 24" × 48" fixtures, order (1) 24" kit CTK24ZW and (1) 48" kit CTK48ZW. This will frame (12) 24" × 48" fixtures.


### SUSPENSION SYSTEMS



### ACCESSORIES (must be ordered separately)

Item No.	Description
441	Border Clip for Vector® panels (required for installations with the suspension system resting on the wall molding). Primarily used for corners and special cutouts.
442A	Hold-down Clip for Vector® panels (for all installations)
7425 (24"), 7431 (30"), 7445 (48"), 7461 (60")	Stabilizer Bars
522	Midpoint Clip (Needed for panels over 30" wide)
7870	Spring Border Clip (For installations with the panel resting on the wall molding)

### AXIOM® TRIM DETAIL



### PHYSICAL DATA

**Material**  
Fiberglass with acoustically transparent membrane.

**Surface Finish**  
Acoustically transparent membrane with factory-applied latex paint.

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled)

**ASTM E1264 Classification**  
Type XII, Form 2, Pattern E; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**High Recycled Content**  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Acoustical Details**  
CAC backing may be available as a special order.

**Insulation Value**  
R Factor - 3.5 (BTU units); R Factor - 0.62 (Watts units)

**Design Considerations**  
Use fixture trim kit around all lights, diffusers, and other ceiling penetrations to avoid exposed suspension system and panel edges. Panel sizes less than 24" × 24" are not recommended for full-field installations.

Border panels in a seismic installation will not be accessible. To ensure border panels are accessible in other areas, consult installation instructions Section 3.7.2.

Physical product samples for standard and custom colors are available upon request. Please refer to the physical product sample prior to making a final selection. While we strive to ensure exact color matches, various factors such as differences in materials, texture, substrate porosity, painting processes, lighting, and observer subjectivity can all affect how paint colors appear on ceiling and wall panels, suspension systems, and trim products. Due to these and other differences, ceiling and wall panels, trim products, and suspension systems with the same color name will coordinate but may not be an exact color match. Product is dye-lotted. Order sufficient initial quantities and attic stock to minimize possible color variation.

**Installation Consideration**  
Lyra® Concealed panels must be installed on a square, level suspension system as tolerance is near zero.

**Cleaning and Disinfecting**  
Cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Square Feet/Carton**  
8430 - 0.55 LBS/SF; 75 SF/CTN  
8431 - 0.55 LBS/SF; 72 SF/CTN  
8433, 8432 - 0.55 LBS/SF; 96 SF/CTN  
8434 - 0.55 LBS/SF; 64 SF/CTN

**Minimum Order Quantity**  
1 carton