

# Declare.

---

## Lyra™ PB and Lyra™ Direct-Apply Ceiling Panels

### Armstrong World Industries, Inc.

**Final Assembly:** Hilliard, Ohio, USA

**Life Expectancy:** 30 Year(s)

**End of Life Options:** Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

#### Ingredients:

---

Fiberglass; Starch Acrylic Binder; Modified Vegetable Oil; Calcium Carbonate; Polyvinyl acetate; Polyvinyl alcohol; Plasticizer; Siloxane; Surfactant (< 1%)<sup>1</sup>; Tetra Hydro Ester; Caprolactum; Acrylic Ester; Propenoic Copolymer; Pentanediol; Propenoic Acid; Anti-foam agent; Citric Acid; Phosphine oxide; Acrylic Copolymer; Glycol acrylate; Propeonic Salt; Siloxane

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

**Living Building Challenge Criteria:** Compliant

---

#### I-13 Red List:

- |   |                             |
|---|-----------------------------|
| <input type="checkbox"/> LBC Red List Free                | % Disclosed: 99% at 100ppm  |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared                         |                             |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

ARM-0015

EXP. 01 NOV 2022

Original Issue Date: 2016