



Lyra® PB Ceiling Panels
Armstrong World Industries

Final Assembly: Hilliard, Ohio, USA
Life Expectancy: 30 Year(s)
Embodied Carbon: 0.681kg CO2eq
Declared Unit: square foot
End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Landfill

Ingredients:

Glass, oxide, chemicals; Starch, polymer with 2-propenoic acid, graft, sodium salt; Calcium Carbonate; Aluminum hydroxide; Fats and Glyceridic oils, vegetable, polymd., oxidized; Mineral Wool; Polyvinyl acetate; Limestone; Acrylic Acid; Polyvinyl alcohol; Aluminum Trihydrate; Tetra Hydro Ester; Propanol; Caprolactum; Phosphine oxide; Titanium dioxide; Siloxane; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; 2-Propenoic acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-; Clay; Calcium carbonate; Water; Diatomaceous Earth; Quartz; Mica; Silica; Polyethylene Wax; Blue Tint; Glycol acrylate; Propenoic Copolymer; Sodium Salt; Attapulgitic Clay; Citric Acid; Tetrahydrofurfuryl alcohol; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Amorphous Silica; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Black Tint; Methylpropanoate; 2-Propenoic acid, 2-phenoxyethyl ester; Acrylic Copolymer

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0015
EXP. 01 JAN 2026
Original Issue Date: 2016