

MESA™ /MESA™ Second Look®

Square Lay-in & Tegular
fine texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Mesa™ panels with Suprafine® XL® 9/16" suspension system

See more photos at:
armstrongceilings.com/photogallery

Fine-textured panels with scored visual options; Offers standard or Total Acoustics® panel performance.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics performance
- Mesa™ panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Fine-textured visual
- Excellent sound-blocking option
- Mold- and mildew-resistant surface
- USDA Certified Biobased Product – 100%
- Non-directional visual reduces installation time and scrap (excludes Second Look items)
- Product can be recycled through the Armstrong Ceilings Recycling Program
- 30-Year Limited System Warranty against visible sag, mold, and mildew

COLOR




White
(WH)

FACE VIEW



Mesa™ Second Look® II panel – Scoring created nominal 24" x 24" squares

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Mesa™
2. Mesa™ with Suprafine® 9/16" suspension system

MESA™ / MESA™ Second Look®

Square Lay-in & Tegular
fine texture

USDA
CERTIFIED
BIOBASED
PRODUCT
PRODUCT 100%

SUSTAIN™
High Performance
Sustainable Ceiling Systems

Declare.

GREENGUARD
Gold Certified
(details below)

LEED® WELL™ LBC
UP TO 56% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$


armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	DURABILITY	Recycled Content	Recycle Program	30-Yr Warranty
				NRC + CAC	NRC										
MESA™	1	680	24 × 24 × 3/4"	0.60	33	N/A	Class A	0.85	*	*	*	*	*	*	*
15/16" Square Lay-in		683	24 × 48 × 3/4"	0.60	33	N/A	Class A	0.85	*	*	*	*	*	*	*
15/16" Angled Tegular	13	681	24 × 24 × 3/4"	0.60	35	GOOD	Class A	0.85	*	*	*	*	*	*	*
		686	24 × 24 × 3/4"	0.60	38	GOOD	Class A	0.85	*	*	*	*	*	*	*
		684	24 × 48 × 3/4"	0.60	35	GOOD	Class A	0.85	*	*	*	*	*	*	*
9/16" Beveled Tegular	29, 44, 48, 52, 56	682	24 × 24 × 3/4"	0.60	35	GOOD	Class A	0.85	*	*	*	*	*	*	*
		687	24 × 24 × 3/4"	0.60	38	GOOD	Class A	0.85	*	*	*	*	*	*	*
		685	24 × 48 × 3/4"	0.60	35	GOOD	Class A	0.85	*	*	*	*	*	*	*
3/4" Thick – 15/16" Square Lay-in, 15/16" & 9/16" Tegular															
Made-to-Order Sizes			Width	Length	N/A	N/A	N/A	Class A	0.85	*	*	*	*	*	*
MESA™			12" - 30"	18" - 72"											
MESA™ Second Look® II	11	688	24 × 48 × 3/4"	0.60	35	GOOD	Class A	0.85	*	*	*	*	*	*	*
15/16" Angled Tegular															

4-6 WEEKS order to ship

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS

NOTE: It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type III, Form 2, Pattern C E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG UL 2818



Design Consideration
Do not mix Mesa™ Second Look® panels with standard Mesa panels in the same room. It is not recommended to install Silhouette® or Interlude® grid with Second Look® panels.

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
680, 681, 682 – 1.02 lbs/SF; 48 SF/ctn
683, 684, 685 – 1.02 lbs/SF; 64 SF/ctn
686, 687 – 1.40 lbs/SF; 48 SF/ctn
688 – 1.02 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
680M, 683M, 682M, 681M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.