# MESA™/MESA™ Second Look®

Square Lay-in & Tegular fine texture







CAD/Revit® drawings at: armstrongceilings.com/cadrevit



See more photos at: armstrongceilings.com/photogallery

Mesa™ panels with Suprafine® XL® 9/16" suspension system

Fine-textured panels with scored visual options; Offers standard or Total Acoustics® panel performance.

#### **KEY SELECTION ATTRIBUTES**

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels:
   NRC + CAC = Total Acoustics performance
- Mesa" panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Fine-textured visual

- · Excellent sound-blocking option
- · Mold- and mildew-resistant surface
- USDA Certified Biobased Product – 100%
- Non-directional visual reduces installation time and scrap (excludes Second Look items)
- Product can be recycled through the Armstrong Ceilings Recycling Program
- · 30-Year Limited System Warranty
- against visible sag, mold, and mildew
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

#### COLOR



#### FACE VIEW



Mesa™ Second Look® II panel - Scoring created nominal 24" x 24" squares

 $\label{eq:def:DETAILS} \textbf{ (Other Suspension Systems compatible. Refer to listing on next page.)}$ 





- 1. Mesa
- 2. Mesa™ with Suprafine® 9/16" suspension system

Armstrong®
World Industries

# MESA™/MESA™ Second Look®

Square Lay-in & Tegular fine texture







|   | PERFORMANCE SELECTION Dots represent high level of performance. |   |   |  |   |   |   |   |  | \$\$\$\$   |   |  |  |
|---|---|---|---|--|---|---|---|---|--|--|---|--|--|
| ensions<br>nes)   | UL Clas<br>Acou   | ssified<br>stics  | Total Acoustics   | Fire Performance   | Light Reflect   | Anti-Mold/ gage   | Sag<br>Resistant<br>Resistant   | Certified Low<br>VOC Emissions  | Scratch  | Recycled<br>Content  | Recycle<br>Program  | 30-Yr Warranty   |  |
| 24 × 3/4"   | 0.60  | 33  | N/A   | Class<br>A   | 0.85  | •   | •   | ۰   | 0  | ۰  | •   | ۰  |  |
| 48 × 3/4"   | 0.60  | 33  | N/A   | Class<br>A   | 0.85  | ٠   | ٠   | ٠   | 0  | ٠  | •   | •  |  |
| 24 × 3/4"   | 0.60  | 35  | GOOD  | Class<br>A   | 0.85  | •   | ٠   | ٠   | 0  | ٠  | •   | •  |  |
| 24 × 3/4"   | 0.60  | 38  | GOOD  | Class<br>A   | 0.85  | ٠   | ٠   | •   | 0  | 0  | •   | ٠  |  |
| 48 × 3/4"   | 0.60  | 35  | GOOD  | Class<br>A   | 0.85  | ٠   | ٠   | •   | 0  | 0  | ٠   | ٠  |  |
| 24 × 3/4"   | 0.60  | 35  | GOOD  | Class<br>A   | 0.85  | ٠   | •   | •   | 0  | 0  | •   | ٠  |  |
| 24 × 3/4"   | 0.60  | 38  | GOOD  | Class<br>A   | 0.85  | ٠   | •   | •   | 0  | •  | ٠   | ٠  |  |
| 48 × 3/4"   | 0.60  | 35  | GOOD  | Class<br>A   | 0.85  | ٠   | •   | •   | 0  | 0  | •   | ٠  |  |
| 5/16" Square Lay-in, 15/                                | 16" & 9/1   | 6" Tegula   | ır  |  |   |   |   |   |  |  |   |  |  |
| Length 18" - 72"  | N/A   | N/A   | N/A   | Class<br>A   | 0.85  | ٠   | ٠   | ٠   | ٠  | ٠  | ٠   | ٠  |  |
| 48 × 3/4"   | 0.60  | 35  | GOOD<br>(iii))  | Class<br>A   | 0.85  | ٠   | ٠   | 0   | 0  | 0  | ٠   | •  |  |
| ation of sound absorption<br>0.75; CAC 35+) BEST (NRC 0 | and sound<br>0.80+; CAC   | d blocking<br>35+)  | g in one p  | roduct.  |   |   |   |   |  |  |   |  |  |
| n.7   | '5; CAC 35+) BEST (NRC (  | '5; CAC 35+) BEST (NRC 0.80+; CAC ended to install Silhouette® or Inter | (95; CAC 35+) BEST (NRC 0.80+; CAC 35+) ended to install Silhouette® or Interlude® grid | (5; CAC 35+) BEST (NRC 0.80+; CAC 35+)  ended to install Silhouette® or Interlude® grid with Sec | ended to install Silhouette® or Interlude® grid with Second Loo | (5; CAC 35+) BEST (NRC 0.80+; CAC 35+)  ended to install Silhouette® or Interlude® grid with Second Look® panel | (nrc 0.80+; cac 35+)  ended to install Silhouette® or Interlude® grid with Second Look® panels. | (5; CAC 35+) BEST (NRC 0.80+; CAC 35+)  ended to install Silhouette® or Interlude® grid with Second Look® panels. | ended to install Silhouette® or Interlude® grid with Second Look® panels.  9/16"   9/16"   1   1   1   1   1   1   1   1   1 | ended to install Silhouette® or Interlude® grid with Second Look® panels.  9/16" / | ended to install Silhouette® or Interlude® grid with Second Look® panels. | ended to install Silhouette® or Interlude® grid with Second Look® panels.  9/16"   9/16"   1   1   1   1   1   1   1   1   1 |  |

## PHYSICAL DATA

Material Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or

ASTM E1264 Classification Type A, Form A1.2, Pattern E; Fire Class A

Humidity/Sag Resistance HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

less. Smoke Developed Index of 50 or less (UL® labeled).

Prelude®

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

#### VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol

Silhouette 1/8" Reveal

Suprafine®

## Acoustical Performance

Silhouette® 1/4" Reveal

CAC testing conducted using Prelude® suspension system for 15/16" edge detail and Silhouette® suspension system for 9/16" edge detail.

#### High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

#### Insulation Value

R Factor - 1.6 (BTU units) R Factor - 0.28 (Watts units)

### Design Consideration

Do not mix Mesa Second Look panels with standard Mesa panels in the same room. It is not recommended to install Silhouette or Interlude grid with Second Look panels.

# 30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton 680, 681, 682 – 1.02 LBS/SF; 48 SF/CTN 683, 684, 685 – 1.02 LBS/SF; 64 SF/CTN 686, 687 – 1.40 LBS/SF; 48 SF/CTN 688 – 1.02 LBS/SF; 64 SF/CTN

## Minimum Order Quantity

1 carton, excludes made-to-order panels

### Metric Items Available

Interlude®

680M, 683M, 682M, 681M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

