



## MetalWorks™ Linear - Classics, Synchro®, & Diverge® in Std Painted, Sequels™, or Effects™ finish Armstrong World Industries

**Final Assembly:** Montreal, Quebec, Canada; Johnstown, Ohio, USA; Guangdong, China

**Life Expectancy:** 30 Year(s)

**Embodied Carbon:** 5.36kg CO2eq ▲

**Declared Unit:** 1ft2

**End of Life Options:** Salvageable/Reusable in its Entirety, Recyclable (100%)

### Ingredients:

Galvanized Steel; Steel Alloy; Steel Alloy; Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with 1,3-butanediol; Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with ammonia-ethylene oxide reaction product distn. residues, compds. with diethylenetriamine and triethylenetetramine; 1,3-Benzenedicarboxylic acid, polymer with 2,2-dimethyl-1,3-propanediol and hexanedioic acid; Titanium dioxide; Tint; Nepheline syenite; **Naphtha**; Acetic acid ethenyl ester, polymer with 1-ethenyl-2-pyrrolidinone; Polyurethane foams; Silica, amorphous, fumed, cryst.-free; Hexanedioic acid, bis(2-methoxyethyl) ester; Cellulose pulp; Mica; Cellulose; 1,2,4-Trimethylbenzene; Glass oxide; Linseed Oil; 1,3-Benzenedicarboxylic acid; Petroleum distillates; 2-Oxepanone, homopolymer; ethyl 2-cyano-3-ethoxyacrylate; **1,3,5-Triglycidyl-s-triazinetriene**; Mineral Wool; PVA; Barium sulfate; Poly[oxy(methyl-1,2-ethanedyl)],  $\alpha$ -hydro- $\omega$ -hydroxy-; Black Tint; Aluminum; 2-Butoxyethanol; 2-Propenoic acid, polymer with ethenylbenzene; 2-Propenoic acid, 2-methyl-, polymer with ethyl 2-propenoate and methyl 2-methyl-2-propenoate; Phosphate; 2-Propanol, 1-methoxy-, acetate; Amorphous Silica; 2-Pentanone, 4-hydroxy-4-methyl-; Glass, oxide, chemicals; Xylene; Phenol, 4,4'-(1-methylethylidene)bis[2,6-dibromo-, polymer with (chloromethyl)oxirane and 4,4'-(1-methylethylidene)bis[phenol]; Octadecane, 1-isocyanato-; 1,3,5-Trimethylbenzene; C.I. Pigment Brown 24; C.I. Pigment Yellow 42; Polyacrylic acid; Glycol Ether; Mica-group minerals; Undisclosed (< 0.1%); Carbon black; Cyclopentanecarboxylic acid, pentadecyl ester; **Urethane (Ethyl carbamate)**; C.I. Pigment Black 1; Amorphous silica; 2,4,8,10-Tetraoxa-3,9-diphosphaspiro[5.5]undecane, 3,9-bis[2,4-bis(1,1-dimethylethyl)phenoxy]-; 2(3H)-Benzothiazolethione, zinc salt; Aluminum hydroxide; **Isophorone Diisocyanate**; Polyethylene Terephthalate; Isopropyl alcohol; 2-Ethyl-1-Hexanol; **Cumene**; Silica gel, pptd., cryst.-free; Diiron Trioxide; Undisclosed (< 0.1%); Undisclosed (< 0.1%); Talc; Ethanone, 2-hydroxy-1,2-diphenyl-; bis(2,4-dicumylphenyl) neopentyl diphosphite; 3,9-bis[2,4-bis(1-methyl-1-phenylethyl)phenoxy]-2,4,8,10-tetraoxa-3,9-diphosphaspiro[5.5]undecane

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

**Living Building Challenge Criteria:** Compliant

#### I-13 Red List:

- LBC Red List Free % Disclosed: 99.7% at 100ppm  
 LBC Red List Approved VOC Content: Not Applicable  
 Declared

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

ARM-0102  
EXP. 01 SEP 2026  
Original Issue Date: 2024

