


METALWORKS™ SecureLock™

Lay-in
smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



MetalWorks™ SecureLock™ 24" x 24" panel with P4 perforation in White

Tamper-resistant ceiling system from 18-gauge galvanized steel panels.

KEY SELECTION ATTRIBUTES

SecureLock™ Lay-in

- Point-load tested to withstand up to 850 lbs, and a minimum of 430 lbs
- Concealed locking
- Installs on a heavy-duty Prelude® XL® suspension system
- Protection against contraband concealment
- 18-gauge electrogalvanized steel

TYPICAL APPLICATIONS

- Correctional facilities
- Judicial facilities/courthouses
- Non-accessible areas
- Healthcare - psychiatric and juvenile wards
- Transportation
- Maximum security areas

COLORS


Due to printing limitations, shade may vary from actual product.




* Premium finish options

PERFORATION OPTIONS

(1/2 scale shown)



DETAILS



1. MetalWorks™ SecureLock™ Perforated

METALWORKS™ SecureLock™

Lay-in
smooth texture

RECYCLED
CONTENT

LEED V5

UP TO
31%

COMMON MATERIALS FRAMEWORK

Human Health

Climate Health

Ecosystem Health

3rd Party CDPH

Circular Economy

OCCUPANT EXPERIENCE

Acoustics

VISUAL SELECTION Contact ASOrder@armstrongceilings.com for custom options.

	Item No. ♦	Dimensions (Inches) W x L	Perforations
METALWORKS™ SecureLock™ 15/16" Lay-in	5488 _WH	24" x 24"	P1, P4

♦ Add 2-letter perforation suffix to item number when specifying or ordering (e.g., 5488 P1 WH).
NOTE: 24" x 48" custom panels are available by contacting TechLine at 1 877 276-7876.

PERFORMANCE

Dots represent high level of performance.

Fire Performance	Light Reflect (White only)	DURABILITY
Class A	0.75 (P1)	Wash • Scrub • Impact • Soil •

ACOUSTICAL INFORMATION

Perforation	NRC with acoustical fleece	NRC with 1" fiberglass infill †
P1 Unperforated	N/A	N/A
P4 SecureLock Perforation	0.10	0.80

† Maximum NRC achieved with acoustical infill (Item 8200T10).


For infill panel information, visit armstrongceilings.com/mwaccessories

ACCESSORIES

Item No.	Description	Dimensions (Inches)	Pieces/Carton
5396	24" x 24" Hold-Down Border Clips – 18-gauge	22-1/8"	Bulk
5594	Compression Strut	60"	Bulk
5596	Security Screws	–	100
5597	Security Screwdriver (to be used with item 5596)	–	1
5598	Tek Screws	–	100
5650WH	C Channel – 18-gauge	120"	Bulk
5398	Access Door – 18-gauge	24 x 24 x 1"	Bulk
5965P1WH	24" x 24" Exit Panel Unperforated	24 x 24 x 1"	8
5965P4WH	24" x 24" Exit Panel Perforated	24 x 24 x 1"	8
8200T10	1" Fiberglass Infill Panel	24 x 24 x 1"	12

SUSPENSION SYSTEMS

15/16"



Prelude® XL®

PHYSICAL DATA

Material

Electrogalvanized Steel – thickness 18-gauge

Surface Finish

Factory-applied powder-coated finish (post-coated)

Fire Performance

Class A: ASTM E84 and CAN/ULC S102. Flame Spread Index 25 or less. Smoke Developed Index 50 or less.

Unperforated – Type XX, Pattern G

Perforated – Type XX, Pattern C

Design/Installation Considerations

Panels installed in correctional facilities are recommended for supervised areas. For detailed impact and point-load test results, contact TechLine at 1 877 276-7876.

Warranty

Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton

5488P1WH – 2.24 lbs/SF; 32 SF/ctn
5488P4WH – 1.97 lbs/SF; 32 SF/ctn