

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## Committed to Sustainability

Armstrong World Industries leads in delivering solutions that meet today's most stringent industry sustainability standards. We are committed to environmental responsibility in all aspects of our business, and carbon reduction is part of our 2030 Company goals and ambitions.

We were one of the first companies to create and publish the Environmental Product Declaration (EPD) in the ceiling industry. We have over a decade of experience using Life Cycle Assessment (LCA) to evaluate environmental impacts of our products starting with design, to raw materials, and through our operations. We are constantly working to optimize our operations and products to reduce their environmental impact. We believe the use of LCA and our commitment to transparency of our products' carbon footprint is critical to contributing to decarbonization of the built environment.

## Contents:


- Performance features like acoustics, light reflectance, and durability
- Product application and use
- Product ingredients and their sources
- How the product is produced
- LCA results, including global warming potential and primary energy usage
- Total impacts over the product life cycle

## For more information visit

[armstrongceilings.com/transparency](http://armstrongceilings.com/transparency)

## Life Cycle Impact Categories (A1-A3) for 1 ft<sup>2</sup>

Cradle-to-Gate environmental impacts for 1 ft<sup>2</sup> of MetalWorks™ Aluminum Ceiling & Wall Panels



**Embodied Carbon (GWP)  
(excluding biogenic carbon)**  
7.03E+00 kg CO<sub>2</sub> eq.



**Acidification Potential**  
1.70E-02 kg SO<sub>2</sub> eq.



**Photochem Ozone  
Creation Potential**  
1.78E-01 kg O<sub>3</sub> eq.



**Eutrophication Potential**  
6.15E-04 kg N eq.



**Ozone Depletion Potential**  
2.52E-09 kg CFC 11 eq.



**ADP<sub>(fossil)</sub>**  
1.20E+00 MJ surplus energy



MetalWorks™ Torsion Spring Ceiling Panels

# MetalWorks™ Aluminum Ceiling & Wall Panels

## Interior and Exterior Panel with Acoustical Options

### 1. CONTENT OF THE EPD

|                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EPD PROGRAM AND PROGRAM OPERATOR NAME, ADDRESS, LOGO, AND WEBSITE                                                                                                                                                                                                                                              | ASTM International – 100 Barr Harbor Drive, West Conshohocken, PA, 19428, USA                                                                                                                                                                                                                              |
| GENERAL PROGRAM INSTRUCTIONS AND VERSION NUMBER                                                                                                                                                                                                                                                                | ASTM Program Operator for Product Category Rules (PCR) and Environmental Product Declarations (EPDs), General Program Instructions, Version: 8.0, Revised 04/29/20                                                                                                                                         |
| MANUFACTURER NAME AND ADDRESS                                                                                                                                                                                                                                                                                  | Armstrong World Industries<br>2500 Columbia Avenue<br>Lancaster, PA 17603                                                                                                                                                                                                                                  |
| DECLARATION NUMBER                                                                                                                                                                                                                                                                                             | EPD959                                                                                                                                                                                                                                                                                                     |
| DECLARED PRODUCT & DECLARED UNIT                                                                                                                                                                                                                                                                               | 0.093m <sup>2</sup> (1ft <sup>2</sup> ) of installed ceiling panel, with a product reference service life (RSL) and building estimated service life of 75 years.                                                                                                                                           |
| REFERENCE PCR AND VERSION NUMBER                                                                                                                                                                                                                                                                               | PCR for Building-Related Products and Services – Part A: LCA Calculation Rules and Report Requirements, UL 10010, UL v.4.0, March 2022<br>PCR Guidance for Building-Related Products and Services – Part B: Metal Ceiling Panel and Interior Wall Panel EPD Requirements UL 10010-12 (ULE, V1.0 Jan. 2020) |
| DESCRIPTION OF PRODUCT'S INTENDED APPLICATION AND USE (AS IDENTIFIED WHEN DETERMINING PRODUCT RSL)                                                                                                                                                                                                             | MetalWorks™ Aluminum Ceiling and Wall Panels                                                                                                                                                                                                                                                               |
| PRODUCT RSL DESCRIPTION (IF APPL.)                                                                                                                                                                                                                                                                             | N/A                                                                                                                                                                                                                                                                                                        |
| MARKETS OF APPLICABILITY                                                                                                                                                                                                                                                                                       | North America                                                                                                                                                                                                                                                                                              |
| DATE OF ISSUE                                                                                                                                                                                                                                                                                                  | April 1, 2025                                                                                                                                                                                                                                                                                              |
| PERIOD OF VALIDITY                                                                                                                                                                                                                                                                                             | 5 years                                                                                                                                                                                                                                                                                                    |
| EPD TYPE                                                                                                                                                                                                                                                                                                       | Product-Specific                                                                                                                                                                                                                                                                                           |
| DATASET VARIABILITY                                                                                                                                                                                                                                                                                            | Industry Average Only                                                                                                                                                                                                                                                                                      |
| EPD SCOPE                                                                                                                                                                                                                                                                                                      | Cradle to Gate with Options                                                                                                                                                                                                                                                                                |
| YEAR(S) OF REPORTED MANUFACTURER PRIMARY DATA                                                                                                                                                                                                                                                                  | 2023                                                                                                                                                                                                                                                                                                       |
| LCA SOFTWARE & VERSION NUMBER                                                                                                                                                                                                                                                                                  | Sphera FE 2024                                                                                                                                                                                                                                                                                             |
| LCI DATABASE(S) & VERSION NUMBER                                                                                                                                                                                                                                                                               | Sphera FE version 10.9.0.31 (Schema 8007)                                                                                                                                                                                                                                                                  |
| LCIA METHODOLOGY & VERSION NUMBER                                                                                                                                                                                                                                                                              | TRACI 2.1                                                                                                                                                                                                                                                                                                  |
| The sub-category PCR review was conducted by:                                                                                                                                                                                                                                                                  | Lindita Bushi, PhD (Chair)<br>Tom Gloria, PhD<br>Olivia Palmer                                                                                                                                                                                                                                             |
| This declaration was independently verified in accordance with ISO 14025: 2006. The UL Environment "Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report," serves as the core PCR.<br><input type="checkbox"/> INTERNAL <input checked="" type="checkbox"/> EXTERNAL | Tim Brooke, ASTM International                                                                                                                                                                                                                                                                             |
| This EPD conforms with (select one):                                                                                                                                                                                                                                                                           | <input checked="" type="checkbox"/> ISO 21930:2017<br><input type="checkbox"/> EN 15804:2013+A1:2014<br><input type="checkbox"/> EN 15804:2013+A2:2019                                                                                                                                                     |
| This life cycle assessment was conducted in accordance with ISO 14044 and the reference PCR by:                                                                                                                                                                                                                | Armstrong World Industries, Inc.                                                                                                                                                                                                                                                                           |
| This life cycle assessment was independently verified in accordance with ISO 14044 and the reference PCR by:                                                                                                                                                                                                   | Thomas P. Gloria, PhD<br>Industrial Ecology Consultants<br>                                                                                                                                                           |
| LIMITATIONS                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                            |

Environmental declarations from different programs (ISO 14025) may not be comparable.

Comparison of the environmental performance of Metal Ceiling and Wall System Products using EPD information shall be based on the product's use and impacts at the building level, and therefore EPDs may not be used for comparability purposes when not considering the building energy use phase as instructed under this PCR.

Full conformance with this PCR allows EPD comparability only when all stages of a life cycle have been considered. However, variations and deviations are possible.

Example of variations: Different LCA software and background LCI datasets may lead to differences in results for upstream or downstream of the life cycle stages declared.

The owner of the declaration shall be liable for the underlying information and evidence; ASTM, or its affiliates, shall not be liable with respect to manufacturer information, life cycle assessment data, and evidence.

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 2. GENERAL INFORMATION

### 2.1 DESCRIPTION OF ORGANIZATION

Armstrong World Industries, Inc. (AWI) is a leader in the design and manufacture of innovative commercial and residential ceiling, wall and suspension system solutions in the Americas. At home, at work, in healthcare facilities, classrooms, stores, or restaurants, Armstrong World Industries offers interior solutions that help to enhance comfort, save time, improve building efficiency and overall performance, and create beautiful spaces.

### 2.2 PRODUCT DESCRIPTION

MetalWorks™ aluminum ceiling and wall panels provide excellent sound absorption and durability including impact-, scratch-, and soil-resistance. MetalWorks™ panels are available in a wide range of standard and custom sizes, shapes, and perforated panels.

#### 2.2.1 Product-Specific EPD

This declaration represents manufacturer-specific average for aluminum ceiling and wall panels. Multiple products within the aluminum product line were analyzed and a weighted average was calculated.

#### 2.2.2 Product Identification

MetalWorks™ aluminum ceiling and wall panels are available in a wide range of standard and custom sizes, shapes, and perforated panels.

Relevant product codes are as follows:

Construction Specifications Institute:

07 42 13 Metal Wall Panels

09 51 00 Acoustical Ceilings

09 51 33 Acoustical Metal Pan Ceilings

09 54 00 Specialty Ceilings

09 54 23 Linear Metal Ceilings

09 78 13 Metal Interior Wall Paneling

UNSPSC:

30161602 Ceiling Panels

#### 2.2.3 Product Specification

Technical specifications are provided in Section 2.5. This declaration covers MetalWorks™ aluminum ceiling and wall panels with weighted average calculation within the product line that differ by shape, size, and finishes.


# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options


## 2.2.4 Flow Diagram

MetalWorks™ Aluminum Ceiling & Wall Panels are manufactured from Aluminum coil or sheet. Depending on customer specifications, the aluminum may be pre-finished prior to cutting, shaping, forming, perforated or post-finished after cutting, shaping, forming, perforated as required by product specification. Please see both flow diagrams below.

### Pre-finished Flow Diagram



### Post-finished Flow Diagram



# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 2.3 PRODUCT AVERAGE

### 2.3.2 Product-Specific EPD

This EPD is specific to MetalWorks™ aluminum ceiling and wall panels. A weighted average approach was applied. Inputs were developed based on 2023 production volumes and weights for MetalWorks™ products.

## 2.4 APPLICATION

The products covered by this EPD are designed to be installed in a suitable metal grid system.

## 2.5 MATERIAL COMPOSITION

Major raw materials used in ceiling panel manufacturing are summarized in the table below.

**TABLE 1. MATERIAL COMPOSITION**

| Material                  | MetalWorks™ Aluminum Ceiling & Wall Panels |
|---------------------------|--------------------------------------------|
| Aluminum                  | 85-95%                                     |
| Acoustic Infill/Fleece    | 0-5%                                       |
| Coatings                  | 0-5%                                       |
| Metal Components/Hardware | 0-5%                                       |

## 2.6 TECHNICAL REQUIREMENTS

**TABLE 2. TECHNICAL DATA**

| Property                                                              | Test Method           | MetalWorks™ Aluminum Ceiling & Wall Panels |
|-----------------------------------------------------------------------|-----------------------|--------------------------------------------|
| Sound absorption coefficient (NRC)                                    | ASTM C423             | 0.65 to 0.95                               |
| Sound Transmission Class (STC)                                        | ASTM E413, ASTM E90   | –                                          |
| Sound attenuation between rooms sharing a common ceiling plenum (CAC) | ASTM E1414, ASTM E413 | –                                          |
| Light reflectance                                                     | ASTM E1477            | Varies based on color                      |
| Flame spread/smoke development                                        | ASTM E84, ASTM E1264  | Class A                                    |

## 2.7 PROPERTIES OF DECLARED PRODUCT AS DELIVERED

The final EPD is available on the Armstrong website ([armstrongceilings.com/epd](http://armstrongceilings.com/epd)) and is under the Finish category in the EC3 Tool ([buildingtransparency.org](http://buildingtransparency.org)).

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 3. METHODOLOGICAL FRAMEWORK

This study provides life cycle inventory and environmental impacts relevant to Armstrong® suspended ceilings. The LCA follows an attributional approach as outlined in ISO 21930 Section 7.1.1 – see also PCR Part A-6.

### 3.1 DECLARED UNIT

The declaration refers to the declared unit of 0.093 m<sup>2</sup> (1 ft<sup>2</sup>) of installed ceiling panel, as defined by the PCR.

### 3.2 FUNCTIONAL/DECLARED UNIT PROPERTIES

TABLE 3. FUNCTIONAL OR DECLARED UNIT PROPERTIES

| Product             | Declared Unit<br>m <sup>2</sup> (ft <sup>2</sup> ) | Declared Thickness<br>cm (in) | Surface Weight<br>kg/0.093 m <sup>2</sup> (lb/ft <sup>2</sup> ) | Density<br>kg/m <sup>3</sup> (lb/ft <sup>3</sup> ) |
|---------------------|----------------------------------------------------|-------------------------------|-----------------------------------------------------------------|----------------------------------------------------|
| MetalWorks Aluminum | 0.093 (1)                                          | 0.106 (0.0417)                | 1.04 (2.23)                                                     | 2712.632 (169.34)                                  |

### 3.3 SYSTEM BOUNDARY

The scope of the study includes production, installation, and end of life. Production of capital equipment, facilities, and infrastructure required for manufacture are outside the scope of this assessment. Details of inclusions and exclusions from the system boundary are listed below.

| Includes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Excludes                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>– Raw materials production (A1)</li> <li>– Inbound transport of raw materials to production facility (A2)</li> <li>– Manufacturing of panels (A3)</li> <li>– Electricity and fuel combustion (A3)</li> <li>– Packaging of final products (A3)</li> <li>– Transportation to the job site (A4)</li> <li>– Installation and installation waste (A5)</li> <li>– Deconstruction – manual, no impact (C1)</li> <li>– Transport (C2)</li> <li>– Waste Processing (C3)</li> <li>– Disposal (C4)</li> </ul> | <ul style="list-style-type: none"> <li>– Construction of capital equipment and other infrastructure flows</li> <li>– Maintenance and operation of support equipment</li> <li>– Human labor and employee transport</li> <li>– Manufacture and transport of packaging materials not associated with final product</li> <li>– Use Phase (B1 to B7)</li> <li>– Benefits and loads beyond the system boundary (D)</li> </ul> |

### 3.4 PRODUCT-SPECIFIC CALCULATIONS FOR END-OF-LIFE PHASE (MODULES C1-C4)

At this time, there is no industry consensus for product-specific assumption behind reported scenarios for information in modules C1-C4. Armstrong facilitates ceiling panels recycling through our Takeback program. The recovery data is based on internal averages for commingled ceiling panels that arrived at Armstrong factories from the construction and demolition site at end of product life. Remaining panels were assumed to be landfilled as per standard industry practice.

### 3.5 REFERENCE SERVICE LIFE AND ESTIMATED BUILDING SERVICE LIFE

In accordance with the PCR, the Reference Service Life (RSL) and building estimated service life for this study was assumed to be 75 years.

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

### 3.6 ALLOCATION

Allocation at the manufacturing plant was based on the surface-based production volume (ft²). This is the basis on which products are processed and sold, regardless of product weight. No burdens are allocated across the system boundary with secondary material, secondary fuel, or recovered energy flows arising from waste. Allocation of background data (energy and materials) was taken from the Sphera LCA FE database.

### 3.7 CUT-OFF RULES

No known flows are deliberately excluded from this EPD. The system boundary was defined based on relevance to the goal of the study. For the processes within the system boundary, all available energy and material flow data have been included in the model. In cases where no matching life cycle inventories are available to represent a flow, proxy data have been applied based on conservative assumptions regarding environmental impacts.

### 3.8 DATA SOURCES

Primary data for this study was collected from the manufacturing facility for 2023 and datasets for materials upstream from manufacturing were obtained from the Sphera FE database version 10.9.0.31.

### 3.9 DATA QUALITY

The data quality ranges from good to very good. The temporal quality of the data is very good with both manufacturing-specific data and GaBi background data from 2024. Because primary and secondary data were collected specifically to the location of manufacture when possible, geographical representativeness is considered to be good.

### 3.10 PERIOD UNDER REVIEW

All the primary data in the scope of this analysis was collected from Armstrong manufacturing facilities during 2023.

### 3.11 COMPARABILITY AND BENCHMARKING

We do not have any data on comparable non-competitive products to report.

### 3.12 ESTIMATES AND ASSUMPTIONS

The datasets for materials upstream from manufacturing are from the GaBi database. When inventories were not available for materials, conservative proxy datasets were chosen based on similarity of material. Additionally and consistent with the PCR, the following assumptions in Table 5 related to transport, installation, and deconstruction procedures were made.

TABLE 5. TRANSPORT, INSTALLATION, AND DECONSTRUCTION PROCEDURES

|                                                              |                                                     |
|--------------------------------------------------------------|-----------------------------------------------------|
| Product transport from point of manufacture to building site | Mode: Diesel-powered truck/trailer Distance: 800 km |
| Product transport from building site to waste processing     | Mode: Diesel-powered truck/trailer Distance: 35 km  |
| Installation & deconstruction procedures                     | Manual (no operational energy use)                  |

### 3.13 UNITS

Units commonly used in the North American market are included in addition to the required SI units.

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 4. TECHNICAL INFORMATION AND SCENARIOS

All data is reported as a weighted average across our ceiling plant locations.

### 4.1 MANUFACTURING

The manufacturing process has been described in a simple flow chart in Section 2.2.4. When a product is manufactured at multiple locations, a volume-based averaging of the input parameters approach was used. Any manufacturing waste was reported in the primary data for this study.

### 4.2 PACKAGING

Armstrong® ceiling panels are well packaged in a variety of wooden panels, rigid corrugate, and stretch wrap. Stacks of material are banded to wooden pallets for shipping.

The US Corrugated Packaging Alliance (CPA) dataset was used in the LCA study. This dataset was developed from the Life Cycle Assessment of U.S. Average Corrugated Panel. The U.S. average corrugated panel studied in the LCA consists of 66.8% liner board and 33.2% corrugated medium with an average basis weight of 131.6 lb./1000 ft<sup>2</sup> (msf 0.643 kg/m<sup>2</sup>). The industry average container-board utilized about 52% recovered fiber, primarily old, corrugated containers (OCC), with the balance supplied mostly by kraft and semi-chemical pulp.

The data set covers all relevant process steps/technologies over the supply chain of the represented cradle to gate inventory with a very good overall data quality. The inventory is based on industry data and is completed where necessary, with secondary data.

### 4.3 TRANSPORTATION

The following information specifies any transport after the manufacturing gate. Details of type of transport, type of vehicle, distance, type, and amount of energy carrier are listed. These values are consistent with industry standard assumptions.

**TABLE 6. TRANSPORT TO THE BUILDING SITE (A4)**

| Material                                    | Unit                   | MetalWorks™ Aluminum Ceiling & Wall Panels |
|---------------------------------------------|------------------------|--------------------------------------------|
| Fuel type                                   | –                      | Diesel                                     |
| Liters of fuel (Diesel)                     | L/100km/m <sup>3</sup> | 35                                         |
| Vehicle type                                | –                      | Truck                                      |
| Transport distance                          | km                     | 800                                        |
| Capacity utilization (including empty runs) | %                      | 78                                         |
| Gross density of products transported       | kg/m <sup>3</sup>      | 2,713                                      |
| Capacity utilization volume factor          | –                      | 1                                          |

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 4.4 PRODUCT INSTALLATION

The ceiling system must be installed in accordance with Armstrong Ceilings installation guidelines. Our ceiling system installation brochure, “Installing Suspended Ceilings”, is a general application overview, covering essential steps of a basic suspended ceiling installation. Installation instructions can be downloaded from product line web pages.

The information in Table 7 shall be provided for all construction products to specify the end-of-life scenarios used for packaging or to support the development of the end-of-life scenarios for packaging at the construction works level where the module is not declared. Scenarios shall only model processes, for example, recycling systems that have been proven to be economically and technically viable.

It is assumed that the on-site scrap material will be sent to a landfill within 35 km (21.7 miles) of the jobsite. Production, transport, waste processing and disposal of 7% of installation waste are included in module A5, calculations for waste at the construction site.

**TABLE 7. INSTALLATION INTO THE BUILDING (A5)**

| Name                                                                                                                           | MetalWorks™ Aluminum Ceiling & Wall Panels | Unit               |
|--------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|--------------------|
| Ancillary materials                                                                                                            | 0                                          | kg                 |
| Net freshwater consumption specified by water source and fate (X m³ river water evaporated, X m³ city water disposed to sewer) | 0                                          | m³                 |
| Other resources                                                                                                                | 0                                          | kg                 |
| Electricity consumption                                                                                                        | 0                                          | kWh                |
| Other energy carriers                                                                                                          | 0                                          | MJ                 |
| Product loss per declared unit                                                                                                 | 0                                          | kg                 |
| Waste materials at the construction site before waste processing, generated by product installation                            | 0                                          | kg                 |
| Output materials resulting from on-site waste processing                                                                       | 0                                          | kg                 |
| Mass of packaging waste specified by type                                                                                      |                                            |                    |
| Plastic                                                                                                                        | 0.00001                                    | kg                 |
| Metal                                                                                                                          | 0.000                                      | kg                 |
| Cardboard                                                                                                                      | 0.00005                                    | kg                 |
| Wood                                                                                                                           | 0.265                                      | kg                 |
| Biogenic carbon contained in packaging                                                                                         | 0.04                                       | kg CO <sub>2</sub> |
| Direct emissions to ambient air, soil and water                                                                                | 0                                          | kg                 |
| VOC emissions                                                                                                                  | > 0.05                                     | mg/m³              |

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 4.5 USE

A product's RSL depends on the product properties and reference in-use conditions. The default RSL and building estimated service life assumed in this PCR is 75 years for both ceiling and wall products.

## 4.6 DISPOSAL

### End of Life

The end-of-life phase for the ceiling panels was included in the study. End-of-life impacts include recycling of ceiling and wall panels.

TABLE 8. END OF LIFE (C1-C4)

| Name                                              |                                             | MetalWorks™ Aluminum Ceiling & Wall Panels | Unit/ft <sup>2</sup> |
|---------------------------------------------------|---------------------------------------------|--------------------------------------------|----------------------|
| Collection process (specified by type)            | Collected separately                        | 0                                          | kg                   |
|                                                   | Collected with mixed construction waste     | 0                                          | kg                   |
| Recovery (specified by type)                      | Reuse                                       | 0                                          | kg                   |
|                                                   | Recycling                                   | 1.008                                      | kg                   |
|                                                   | Incineration                                | 0                                          | kg                   |
|                                                   | Incineration with energy recovery           | 0                                          | kg                   |
|                                                   | Energy conversion (specify efficiency rate) | 0                                          | kg                   |
| Disposal (specified by type)                      | Product for final disposal (landfill)       | 0.0312                                     | kg                   |
| Removals of biogenic carbon (excluding packaging) |                                             | 0.000                                      | kg CO <sub>2</sub>   |

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 5. ENVIRONMENTAL INDICATORS DERIVED FROM LCA

### 5.1 LCA RESULTS FROM LCIA

The Life Cycle Assessment (LCA) was performed according to ISO 14040 guidelines and follows the specific PCR instructions. The cradle-to-gate with options LCA consists of raw material production, transport of raw materials to production facility prior to processing, manufacturing of ceiling and wall panels, packaging; transportation to job site and installation, and end of life including disposal or recycling to Armstrong factories.

(X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

**TABLE 9. DESCRIPTION OF THE SYSTEM BOUNDARY MODULES\***

| EPD Type                    | Production          |           |               | Construction      |                  | Use                                                                        |             |        |             |               |                        |                | End Of Life    |           |                  |          | Benefits and Loads Beyond System Boundary |
|-----------------------------|---------------------|-----------|---------------|-------------------|------------------|----------------------------------------------------------------------------|-------------|--------|-------------|---------------|------------------------|----------------|----------------|-----------|------------------|----------|-------------------------------------------|
|                             | A1                  | A2        | A3            | A4                | A5               | B1                                                                         | B2          | B3     | B4          | B5            | B6                     | B7             | C1             | C2        | C3               | C4       | D                                         |
|                             | Raw material supply | Transport | Manufacturing | Transport to site | Assembly/Install | Use                                                                        | Maintenance | Repair | Replacement | Refurbishment | Operational Energy Use | Deconstruction | Deconstruction | Transport | Waste processing | Disposal | Reuse, Recovery, Recycling Potential      |
|                             |                     |           |               |                   |                  | B6 Operational Energy Use of Building Integrated System During Product Use |             |        |             |               |                        |                |                |           |                  |          |                                           |
|                             |                     |           |               |                   |                  | B7 Operational Water Use of Building Integrated System During Product Use  |             |        |             |               |                        |                |                |           |                  |          |                                           |
| Cradle to Gate with Options | X                   | X         | X             | X                 | X                | MND                                                                        | MND         | MND    | MND         | MND           | MND                    | MND            | X              | X         | X                | X        | MND                                       |

\* Results for modules A1-A3 results are aggregated, as described in the PCR.

### 5.2 LCA RESULTS FROM LCIA

Life cycle impacts reported below are based on TRACI 2.1 methodology. Results are provided in reference to the declared unit. For the other impact categories, results are presented in the tables below using the ISO 21930 standard and for the declared unit. Because products include biobased content, they store or sequester carbon. Table 11 includes both Global Warming Potential (GWP) excluding biogenic and GWP including biogenic carbon. LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks. These six impact categories are globally deemed mature enough to be included in Type III environmental declarations. Other categories are being developed and defined and LCA should continue making advances in their development. However, the EPD users shall not use additional measures for comparative purposes.

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

**TABLE 10. TRACI 2.1 IMPACT ASSESSMENT FOR 0.093 m<sup>2</sup> (1 FT<sup>2</sup>) OF METALWORKS™ ALUMINUM CEILING & WALL PANELS\***

| MetalWorks™ Aluminum Ceiling & Wall Panels |                        |          |          |          |          |          |          |          |
|--------------------------------------------|------------------------|----------|----------|----------|----------|----------|----------|----------|
| Parameter                                  | Unit                   | A1       | A2       | A3       | A4       | A5       | C2       | C4       |
| GWP, excluding biogenic                    | kg CO <sub>2</sub> eq. | 3.77E+00 | 1.44E-02 | 3.24E+00 | 8.30E-02 | 3.36E-02 | 1.50E-02 | 5.03E-02 |
| ODP                                        | kg CFC 11 eq.          | 2.52E-09 | 4.30E-17 | 1.98E-14 | 2.47E-16 | 7.54E-16 | 4.48E-17 | 7.18E-17 |
| AP                                         | kg SO <sub>2</sub> eq. | 1.54E-02 | 4.14E-05 | 1.56E-03 | 3.88E-04 | 1.14E-04 | 4.31E-05 | 1.73E-05 |
| EP                                         | kg N eq.               | 5.00E-04 | 4.33E-06 | 1.10E-04 | 3.45E-05 | 2.15E-05 | 4.52E-06 | 1.41E-06 |
| SFP                                        | kg O <sub>3</sub> eq.  | 1.38E-01 | 9.37E-04 | 3.93E-02 | 8.92E-03 | 1.06E-04 | 9.76E-04 | 3.59E-04 |
| FFD                                        | MJ Surplus             | 5.32E+00 | 2.74E-02 | 6.70E+00 | 1.58E-01 | 2.59E-02 | 2.86E-02 | 9.70E-03 |

\* Modules C1 and C3 are null

## 5.3 LCA RESULTS FROM LCI

**TABLE 11. LCA RESULTS - RESOURCE USE FOR 0.093 m<sup>2</sup> (1 FT<sup>2</sup>) OF METALWORKS™ ALUMINUM CEILING & WALL PANELS\***

| MetalWorks™ Aluminum Ceiling & Wall Panels |                                                                      |                |          |          |          |          |          |          |          |
|--------------------------------------------|----------------------------------------------------------------------|----------------|----------|----------|----------|----------|----------|----------|----------|
| Parameter                                  | Parameter <sup>2</sup>                                               | Unit           | A1       | A2       | A3       | A4       | A5       | C2       | C4       |
| RPre                                       | Renewable primary resources used as energy carrier (fuel)            | MJ, LHV        | 1.61E+01 | 8.53E-03 | 2.84E+00 | 4.90E-02 | 5.31E-02 | 8.89E-03 | 4.62E-03 |
| RPRm                                       | Renewable primary resources with energy content used as material     | MJ, LHV        | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| NRPRE                                      | Non-renewable primary resources used as an energy carrier (fuel)     | MJ, LHV        | 5.13E+01 | 1.93E-01 | 4.84E+01 | 1.11E+00 | 2.08E-01 | 2.01E-01 | 6.99E-02 |
| NRPRM                                      | Non-renewable primary resources with energy content used as material | MJ, LHV        | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| SM                                         | Secondary materials                                                  | kg             | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| RSF                                        | Renewable secondary fuels                                            | kg             | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| NRDF                                       | Non-renewable secondary fuels                                        | m <sup>3</sup> | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| RE                                         | Recovered Energy                                                     | MJ, LHV        | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| FW                                         | Use of net fresh water                                               | m <sup>3</sup> | 5.21E-02 | 2.84E-05 | 7.40E-03 | 1.63E-04 | 1.02E-04 | 2.95E-05 | 9.93E-06 |

\* Modules C1 and C3 are null

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

**TABLE 12. LCA RESULTS - OUTPUT FLOWS AND WASTE CATEGORIES FOR 0.093 m<sup>2</sup> (1 FT<sup>2</sup>) OF METALWORKS™ ALUMINUM CEILING & WALL PANELS\***

| MetalWorks™ Aluminum Ceiling & Wall Panels |                                                                                 |      |          |          |          |          |          |          |          |
|--------------------------------------------|---------------------------------------------------------------------------------|------|----------|----------|----------|----------|----------|----------|----------|
| Parameter                                  | Description                                                                     | Unit | A1       | A2       | A3       | A4       | A5       | C2       | C4       |
| HWD                                        | Hazardous waste disposed                                                        | kg   | 1.69E-05 | 2.60E-11 | 7.40E-09 | 1.49E-10 | 2.63E-09 | 2.71E-11 | 1.16E-11 |
| NHWD                                       | NHWD Non-hazardous waste disposed                                               | kg   | 9.81E-01 | 1.92E-05 | 1.62E-02 | 1.10E-04 | 1.71E-01 | 2.00E-05 | 5.84E-02 |
| RWD                                        | Radioactive waste disposal                                                      | kg   | 9.97E-04 | 5.81E-07 | 7.07E-04 | 3.34E-06 | 4.90E-06 | 6.06E-07 | 3.56E-07 |
| HLRW                                       | High-level radioactive waste, conditioned, to final repository                  | kg   | 1.20E-06 | 6.89E-10 | 8.45E-07 | 3.96E-09 | 4.26E-09 | 7.18E-10 | 4.09E-10 |
| ILLRW                                      | Intermediate- and low-level radioactive waste, conditioned, to final repository | kg   | 9.96E-04 | 5.81E-07 | 7.06E-04 | 3.34E-06 | 4.90E-06 | 6.05E-07 | 3.56E-07 |
| CRU                                        | Components for re-use                                                           | kg   | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| MR                                         | Materials for recycling                                                         | kg   | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 1.94E-02 | 0.00E+00 | 1.11E+00 |
| MER                                        | Materials for energy recovery                                                   | kg   | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |
| EE                                         | Recovered energy exported from the product system                               | MJ   | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 | 0.00E+00 |


\* Modules C1 and C3 are null

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 6. LCA: INTERPRETATION

The ceiling life cycle covered in this study concluded that the ceiling panel manufacturing process and raw materials in the ceiling panel have the greatest impact on “carbon footprint” as represented by Global Warming Potential [GWP].



# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 7. ADDITIONAL ENVIRONMENTAL INFORMATION

### 7.1 ENVIRONMENT AND HEALTH DURING MANUFACTURING

Armstrong World Industries has a comprehensive environmental, health, and safety management program. Risk reduction begins in the product design process. All products go through a safety, health, and environmental review prior to sale. Armstrong also has a long-standing commitment to the safety and health of all our employees.

Armstrong World Industries is equally committed to reducing our environmental impact. As with safety goals, each manufacturing facility has environmental initiatives focused on responsible use of energy and water, and on waste reduction.

### 7.2 ENVIRONMENT AND HEALTH DURING INSTALLATION

All recommendations shall be utilized as indicated by SDS and installation guidelines. Specific product SDS and installation instructions can be downloaded at: [armstrongceilings.com/pdbupimages-clg/217521.pdf](http://armstrongceilings.com/pdbupimages-clg/217521.pdf)

### 7.3 ENVIRONMENTAL ACTIVITIES AND CERTIFICATIONS

All environmental certifications can be found at: [armstrongceilings.com](http://armstrongceilings.com)

### 7.4 FURTHER INFORMATION

Additional Information can be found at: [armstrongceilings.com](http://armstrongceilings.com)

## 8. PROJECT REPORT AND SUPPORTING DOCUMENTATION

This study provides life cycle inventory and environmental impacts relevant to Armstrong® suspended ceilings. This report is intended to fulfill the reporting requirements in Section 5 of ISO 14044 and Product Category Rules Guidance for Building-Related Products and Services UL® Environments (2021) Part B: Interior Wall Panel EPD Requirements, UL® Environment, v.2 04/2021..

Armstrong World Industries has a robust internal Quality Assurance process that is based on industry-accepted best practices and is led by a team of quality professionals who have been certified by the American Society for Quality. The process involves several hundred different measures made throughout the manufacturing processes. In addition, our products are UL® labeled for fire and acoustical performance – a process which involves strict oversight by Underwriters Laboratories. The Armstrong Ceilings acoustical laboratory is ISO 17025 certified and is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

# MetalWorks™ Aluminum Ceiling & Wall Panels

Interior and Exterior Panel with Acoustical Options

## 9. REFERENCES

Armstrong World Industries. [2025]. MetalWorks™ Aluminum Ceiling & Wall Panels Life Cycle Assessment Report [Internal unpublished report]

J. Bare, TRACI: the Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts 2.1 EPA/600/R-12/554 2012

Sphera LCA FE Software, Sphera, 2024

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products and services

ISO 14025 - Environmental labeling and declarations Type III environmental declarations Principles and procedures

ISO 14040 - Environmental management – Life Cycle Assessment – Principles and framework, Amd 1: 2020

ISO 14044 - Environmental management – Life Cycle Assessment – Requirements and guidelines, Amd 1: 2017 / Amd 2:2020

UL Product Category Rules for Building-Related Products and Services Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report, UL 10010, v3.2; December 2018

UL Product Category Rules for Building-Related Products and Services Part B: Metal Ceiling Panel and Interior Wall Panel EPD Requirements UL 10010-12 (ULE, V1.0 Jan. 2020)