

OPTIMA® PB Shapes  
for DESIGNFLEX®  
with Plant-based Binder  
Tegular  
fine texture



## DESIGNFLEX® CEILING SYSTEMS

### PERSONALIZE YOUR DESIGN!

Mix and match different sizes, shapes, colors, and materials to reinvent your ceiling. More at: [armstrongceilings.com/designflex](http://armstrongceilings.com/designflex)



Optima PB Shapes panels with Suprafine XM 9/16" suspension system



See more patterns at: [armstrongceilings.com/patterngallery](http://armstrongceilings.com/patterngallery)

Fine-textured ceiling panels available in shapes and made-to-order sizes with Sustain® performance. Available to ship in 3 weeks.

### KEY SELECTION ATTRIBUTES

- DesignFlex® options include shapes and made-to-order sizes available to ship in 3 weeks
- Mix and match – Shapes also available with Calla®, Lyra®, Ultima®, MetalWorks™, and WoodWorks® panels
- Optima® PB panels are manufactured with a plant-based binder and are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Excellent sound absorption – NRC 0.95
- Light reflectance – 0.88
- Shaped lights and diffusers are available from our DesignFlex® partners. Our lighting partners for TechZone® and MEP partners also provide products that are compatible with the DesignFlex® system; other standard modular and pendant fixtures can also be used with this ceiling system
- Washable, Scratch-resistant, Soil-resistant
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant
- 10-Year Limited System Warranty against visible sag, mold, and mildew

### COLOR



White  
(WH)

### DETAILS



1. Optima® PB Shapes Tegular
2. Optima® PB Shapes Tegular with Suprafine® XM 9/16" suspension system

# OPTIMA® PB Shapes for DESIGNFLEX®

with Plant-based Binder  
Tegular  
fine texture



Declare.

LEED® WELL® LBC

71% RECYCLED CONTENT

Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes



LOCATION DEPENDENT

Start your design process with a visit to our online pattern gallery at: [armstrongceilings.com/patterngallery](http://armstrongceilings.com/patterngallery)

See dozens of pre-designed patterns and colors online in our pattern gallery. We've provided all of the details – from takeoffs showing 2' or 4' on-center spacing to panels, suspension, trims, and accessories. Installation instructions answer questions typically associated with unique ceiling installations. Lighting and air diffusers can also be easily integrated. If you can't find the ceiling pattern you envision for your next space online, call us and we'll help you create a design to personalize your space – 1 877 276-7876.




These 9 Optima® PB Shapes with Square Tegular edges are available with Suprafine® XM 9/16" suspension:

## 45° SHAPES

### Triangles

2' Main Beam Spacing



Item No. Description/  
Dimensions  
(Inches)

100200 Triangle  
24 x 48 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

Right Triangle –  
2' Main Beam Spacing




100207 Right Triangle –  
24 x 24 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

Right Triangle –  
4' Main Beam Spacing



100208 Right Triangle –  
48 x 48 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

## 60° SHAPES

### Triangles

2' Main Beam Spacing



Item No. Description/  
Dimensions  
(Inches)

100201 Triangle  
24 x 24 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

4' Main Beam Spacing




100202 Triangle  
48 x 48 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -


Right Triangle –  
2' Main Beam Spacing



100205 Right Triangle –  
Left 24 x 48 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -



100206 Right Triangle –  
Right 24 x 48 x 1"


Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

## 75° SHAPES

### Triangles

2' Main Beam Spacing




Item No. Description/  
Dimensions  
(Inches)

100203 Triangle  
24 x 12 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

4' Main Beam Spacing



100204 Triangle  
48 x 24 x 1"

Total Acoustics¹

NRC + CAC = NRC + CAC  
0.95 N/A -

MORE ITEMS ►

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS

9/16"



## PARTNER COMPANIES

For more information on our partner companies, please visit [armstrongceilings.com/partners](http://armstrongceilings.com/partners)

Compatible with:  
Axis Geometrix™ Lighting,  
JLC-Tech FLEX® and T-BAR LED®  
Lights and Price® diffusers.



Shaped infill panels are available for applicable lighting fixtures. Add **L I N E** to the end of any Shape panel item number to order. Metal diffuser infills are available from the diffuser manufacturer.

## PHYSICAL DATA

### Material

Fiberglass with DuraBrite® acoustically transparent membrane

### Surface Finish

DuraBrite with factory-applied latex paint

### Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL\* labeled).

### ASTM E1264 Classification

Type B, Form B2, Pattern E; Fire Class A

### Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

### Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

### VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol

### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

### Seismic Restraint

Suprafine® XM for Shapes suspension systems have been engineered, tested, and approved for use with DesignFlex® Shapes panels for application in all seismic areas when installed per Armstrong® Ceilings installation instructions. For more details, visit [armstrongceilings.com/shapesinstallation](http://armstrongceilings.com/shapesinstallation)

### Insulation Value

R Factor – 2.2 (BTU units); R Factor – 0.39 (Watts units)

### Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

### 10-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

### Weight; Pieces/ Carton

100203 – 0.4 LBS/PC; 24 PCS/CTN  
100201 – 0.8 LBS/PC; 12 PCS/CTN  
100207 – 0.8 LBS/PC; 24 PCS/CTN  
100208 – 3.2 LBS/PC; 12 PCS/CTN  
100200, 100204 – 1.6 LBS/PC; 12 PCS/CTN  
100205, 100206 – 1.6 LBS/PC; 24 PCS/CTN  
100202 – 3.2 LBS/PC; 6 PCS/CTN

### Minimum Order Quantity

1 carton

TechLine 877 276-7876

[armstrongceilings.com/optimashapes](http://armstrongceilings.com/optimashapes)

**Armstrong®**  
World Industries

DESIGNFLEX® SHAPES

# OPTIMA® PB Shapes for DESIGNFLEX®

with Plant-based Binder  
Regular  
fine texture



Declare.

LEED® WELL™ LBC

71% RECYCLED CONTENT

Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes

energy management  
construction waste mgmt  
regional materials  
design for flexibility  
EPD  
recyclable/extended producer resp.  
biobased materials  
recycled content  
sourcing of raw materials  
material ingredient reporting  
low emitting materials  
lighting quality  
acoustics

LOCATION DEPENDENT

PANEL OPTIONS (shown in finish view from below ceiling)

These 10 Optima® PB Shapes with Square Tegular edges are available with Suprafine® XM 9/16" suspension:

## 45° SHAPES

### Parallelograms

2' Main Beam Spacing	Item No.	Description/ Dimensions (Inches)
	100213	Right Parallelogram 24 x 48 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
	100214	Left Parallelogram 24 x 48 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		

## 60° SHAPES

### Parallelograms

2' Main Beam Spacing	Item No.	Description/ Dimensions (Inches)
	100215	Right Parallelogram 24 x 24 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
	100216	Left Parallelogram 24 x 24 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
4' Main Beam Spacing	Item No.	Description/ Dimensions (Inches)
	100217	Right Parallelogram 48 x 48 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
	100218	Left Parallelogram 48 x 48 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		


## 75° SHAPES

### Parallelograms

2' Main Beam Spacing	Item No.	Description/ Dimensions (Inches)
	100219	Right Parallelogram 24 x 12 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
	100220	Left Parallelogram 24 x 12 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
4' Main Beam Spacing	Item No.	Description/ Dimensions (Inches)
	100221	Right Parallelogram 48 x 24 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		
	100222	Left Parallelogram 48 x 24 x 1"
Total Acoustics¹		
NRC + CAC = NRC CAC		
0.95 N/A -		

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
GOOD (NRC 0.60-0.65; CAC 35+) BETTER (NRC 0.70-0.75; CAC 35+) BEST (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS



## PARTNER COMPANIES

For more information on our partner companies, please visit [armstrongceilings.com/partners](http://armstrongceilings.com/partners)

Compatible with:  
Axis Geometrix™ Lighting,  
JLC-Tech FLEX® and T-BAR LED®  
Lights and Price® diffusers.



Shaped infill panels are available for applicable lighting fixtures. Add **L I N E** to the end of any Shape panel item number to order. Metal diffuser infills are available from the diffuser manufacturer.

## PHYSICAL DATA

**Material**  
Fiberglass with DuraBrite® acoustically transparent membrane

**Surface Finish**  
DuraBrite with factory-applied latex paint

**Fire Performance**  
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL® labeled).

**ASTM E1264 Classification**  
Type B, Form B2, Pattern E; Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Anti-Mold/Mildew**  
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol

**High Recycled Content**  
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Seismic Restraint**  
Suprafine® XM for Shapes suspension systems have been engineered, tested, and approved for use with DesignFlex® Shapes panels for application in all seismic areas when installed per Armstrong® Ceilings installation instructions. For more details, visit [armstrongceilings.com/shapesinstallation](http://armstrongceilings.com/shapesinstallation)

**Insulation Value**  
R Factor - 2.2 (BTU units)  
R Factor - 0.39 (Watts units)

**Cleaning and Disinfecting**  
Cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

**10-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

**Weight; Pieces/Carton**  
100219, 100220 - 0.8 LBS/PC; 24 PCS/CTN  
100215, 100216 - 1.6 LBS/PC; 12 PCS/CTN  
100213, 100214, 100221, 100222 - 3.2 LBS/PC; 12 PCS/CTN  
100217, 100218 - 6.4 LBS/PC; 6 PCS/CTN

**Minimum Order Quantity**  
1 carton

TechLine 877 276-7876  
[armstrongceilings.com/optimashapes](http://armstrongceilings.com/optimashapes)

**Armstrong®**  
World Industries

# OPTIMA® PB Shapes for DESIGNFLEX®


with Plant-based Binder  
Tegular  
fine texture



Declare.

LEED®  
WELL® LBC

71%  
RECYCLED  
CONTENT



Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes



LOCATION DEPENDENT


## PANEL OPTIONS (shown in finish view from below ceiling)

These 4 Optima® PB Shapes with Square Tegular edges are available with Suprafine® XM 9/16" suspension:

### 45° SHAPES

#### Trapezoids

2' Main Beam Spacing



Item No. 100209  
Description/Dimensions (Inches)  
Trapezoid 24 x 96 x 1"


Total Acoustics¹

$$\begin{matrix} \text{NRC} & + & \text{CAC} & = & \text{NRC} \\ \text{0.95} & & \text{N/A} & & \text{CAC} \end{matrix}$$

### 60° SHAPES

#### Trapezoids

2' Main Beam Spacing



Item No. 100210  
Description/Dimensions (Inches)  
Trapezoid 24 x 48 x 1"


Total Acoustics¹

$$\begin{matrix} \text{NRC} & + & \text{CAC} & = & \text{NRC} \\ \text{0.95} & & \text{N/A} & & \text{CAC} \end{matrix}$$

### 75° SHAPES

#### Trapezoids

2' Main Beam Spacing




Item No. 100211  
Description/Dimensions (Inches)  
Trapezoid 24 x 24 x 1"

Total Acoustics¹

$$\begin{matrix} \text{NRC} & + & \text{CAC} & = & \text{NRC} \\ \text{0.95} & & \text{N/A} & & \text{CAC} \end{matrix}$$

4' Main Beam Spacing



Item No. 100212  
Description/Dimensions (Inches)  
Trapezoid 48 x 48 x 1"

Total Acoustics¹


$$\begin{matrix} \text{NRC} & + & \text{CAC} & = & \text{NRC} \\ \text{0.95} & & \text{N/A} & & \text{CAC} \end{matrix}$$

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

## SUSPENSION COMPONENTS System utilizes Suprafine® XM suspension components including angle brackets, corner brackets, main beams, cross tees, and perimeter clips.



Right Angle Bracket




Left Angle Bracket




Double Angle Bracket



Corner Bracket



Axiom® Perimeter  
Corner Clip



Perimeter Angle Clip

## SUSPENSION SYSTEMS

9/16"



Suprafine® XM  
for Shapes

## PARTNER COMPANIES For more information on our partner companies, please visit [armstrongceilings.com/partners](http://armstrongceilings.com/partners)

Compatible with:  
Axis Geometrix™ Lighting,  
JLC-Tech FLEX® and T-BAR LED®  
Lights and Price® diffusers.



Shaped infill panels are available for applicable lighting fixtures. Add **L I N E** to the end of any Shape panel item number to order. Metal diffuser infls are available from the diffuser manufacturer.

## PHYSICAL DATA

### Material

Fiberglass with DuraBrite® acoustically transparent membrane

### Surface Finish

DuraBrite with factory-applied latex paint

### Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL® labeled).

### ASTM E1264 Classification

Type B, Form B2, Pattern E; Fire Class A

### Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

### Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

### VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard®, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol

### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

### Seismic Restraint

Suprafine® XM for Shapes suspension systems have been engineered, tested, and approved for use with DesignFlex® Shapes panels for application in all seismic areas when installed per Armstrong® Ceilings installation instructions. For more details, visit [armstrongceilings.com/shapesinstallation](http://armstrongceilings.com/shapesinstallation)

### Insulation Value

R Factor – 2.2 (BTU units)  
R Factor – 0.39 (Watts units)

### Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning)

### 10-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at [armstrongceilings.com/warranty](http://armstrongceilings.com/warranty)

### Weight; Pieces/ Carton

100211 – 1.2 LBS/PC; 12 PCS/CTN  
100210 – 2.4 LBS/PC; 12 PCS/CTN  
100209, 100212 – 4.8 LBS/PC; 6 PCS/CTN

### Minimum Order Quantity

1 carton