OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance
Sustainable
Ceiling Systems
(PB Suffix Only)



Optima Tegular 24" × 48" panels with Suprafine 9/16" suspension system

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

DESIGNFlex®
A New World of Choice
for Ceiling Systems

plus capabilities
to do more



armstrongceilings.com/capabilities
See more photos at:
armstrongceilings.com/photogallery

Fine-textured panels with more large-size, standard panel options than any other product family. Offers high sound absorption.


KEY SELECTION ATTRIBUTES

- DesignFlex® options include shapes and made-to-order sizes available to ship in 3 weeks
- Optima® PB panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Items with PB suffix are manufactured with a plant-based binder
- Outstanding acoustical performance for open plan areas, both Articulation Class 180-190 and NRC 0.90-1.00
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Mold- and mildew-resistant surface
- Energy saving high light-reflective finish
- Non-directional visual reduces scrap and installation time
- Sag-resistant large-size panels
- Compatible with TechZone® Ceiling Systems
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- Available with factory-cut holes for USAI® trimless downlight fixture integration
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant

COLOR

White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Optima® Square Tegular
2. Optima® Tegular with Prelude® 15/16" suspension system
3. Optima® Tegular with Interlude® XL® HRC 9/16" suspension system
4. Optima® Tegular with Silhouette® 9/16" suspension system with 1/8" reveal
5. Suprafine® ML, XL®, and XL® HRC with Blizzard White finish

TechLine 877 276-7876
armstrongceilings.com/optima

Armstrong®
World Industries

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance Sustainable Ceiling Systems
(PB Suffix Only)

Declare.
(PB Suffix Only)

RECYCLED CONTENT
UP TO **71%**

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK	
Human Health	Climate Health — EPD
	Ecosystem Health — EPD
	Circular Economy ✓
OCCUPANT EXPERIENCE	Acoustics ✓

VISUAL SELECTION

PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches) W × L × H		UL Classified Acoustics NRC + CAC =	Total Acoustics[1]	Articulation Class AC	Fire Performance	Light Reflect	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels: Fog	DURABILITY: Wash	DURABILITY: Impact	DURABILITY: Scratch	DURABILITY: Soil	30-Yr Warranty
OPTIMA® 15/16" Square Tegular	8	1402	6 × 48 × 1"		N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1406	6 × 60 × 1"		N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3264	12 × 24 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3278	20 × 60 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3250 3250PB	24 × 24 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3354	24 × 24 × 1"		0.90 •	26	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3253	24 × 24 × 1-1/2"		1.00 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3252 3252PB	24 × 48 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3281	24 × 72 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3282	24 × 96 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3258	30 × 30 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3286	30 × 60 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3255 3255PB	48 × 48 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•

MORE ITEMS ▶

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
Optima items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

PHYSICAL DATA

Material
3354 – Fiberglass with DuraBrite® acoustically transparent membrane; CAC backing
All other items – Fiberglass with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type B, Form B2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
(PB suffix items only)
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Acoustical Details
Some items have CAC backing. CAC backing may be available as a special order. A CAC value of 37 can be achieved by backloading fiberglass products with item 769 or 770.

Insulation Value
3253 – R Factor – 6.0 (BTU units)
R Factor – 1.05 (Watts units)
3281, 3282 – R Factor – 3.0 (BTU units)
R Factor – 0.53 (Watts units)
All other items – R Factor – 4.0 (BTU units)
R Factor – 0.70 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1402 – 0.55 LBS/SF; 24 SF/CTN
1406 – 0.55 LBS/SF; 30 SF/CTN
3250, 3250PB – 0.46 LBS/SF; 48 SF/CTN
3252, 3252PB – 0.55 LBS/SF; 96 SF/CTN
3282 – 0.42 LBS/SF; 96 SF/CTN
3264 – 0.55 LBS/SF; 48 SF/CTN
3253 – 0.64 LBS/SF; 32 SF/CTN
3255, 3255PB – 0.55 LBS/SF; 96 SF/CTN
3258 – 0.55 LBS/SF; 75 SF/CTN
3278, 3286 – 0.55 LBS/SF; 100 SF/CTN
3281 – 0.55 LBS/SF; 72 SF/CTN
3354 – 0.47 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
3250M, 3252M, 3253M, 3354M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

FIBERGLASS – Standard

TechLine 877 276-7876
armstrongceilings.com/optima

Armstrong® World Industries

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems
(PB Suffix Only)

Declare.
(PB Suffix Only)

RECYCLED CONTENT
UP TO
71%

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK
Human Health
Climate Health — EPD
Ecosystem Health — EPD
Circular Economy ✓
OCCUPANT EXPERIENCE
Acoustics ✓

VISUAL SELECTION

PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics NRC	+ CAC =	Total Acoustics[1]	Articulation Class AC	Fire Performance	Light Reflect	Bio-Block Anti-Mold/ Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels: Fog	DURABILITY: Wash	Impact	Scratch	Soil	30-Yr Warranty
OPTIMA® 9/16" Square Tegular	26, 43, 47, 51, 55	**1410**	4 × 48 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1411	4 × 60 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1413	6 × 12 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1415	6 × 42 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1403	6 × 48 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1417	6 × 54 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1407	6 × 60 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1409	6 × 96 × 1"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3263	12 × 24 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3290	12 × 48 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		1414	12 × 96 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
Optima items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

FIBERGLASS – Standard

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance Sustainable Ceiling Systems
(PB Suffix Only)

Declare®
(PB Suffix Only)

RECYCLED CONTENT
UP TO **71%**

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK
Human Health — Climate Health: EPD; Ecosystem Health: EPD; Circular Economy: ✓
OCCUPANT EXPERIENCE — Acoustics: ✓

VISUAL SELECTION

PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)		UL Classified Acoustics NRC + CAC =	Total Acoustics[1]	Articulation Class AC	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels: Fog	DURABILITY: Wash	Impact	Scratch	Soil	30-Yr Warranty
OPTIMA® 9/16" Square Tegular	26, 43, 47, 51, 55	**3276**	20 × 54 × 1"		0.95 •	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3266	20 × 56 × 1"		0.95 •	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3277	20 × 60 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3279	21 × 24 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3251 3251PB	24 × 24 × 1"		0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3254	24 × 24 × 1-1/2"		1.00 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•

MORE ITEMS ▶

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
Optima items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.

SUSPENSION SYSTEMS

15/16" Prelude®

9/16" Silhouette® 1/4" Reveal; Silhouette 1/8" Reveal; Suprafine®; Interlude®

Blizzard White – Suspension System Finish
A color and texture coordinated suspension system to complement Optima® ceiling panels for a monolithic look and feel.
Available for: Prelude® XL® and XL® HRC, Suprafine® ML, XL, and XL® HRC, Silhouette® XL® 1/4" and 1/8" Reveal, Interlude® XL® HRC

ACCESSORIES (must be ordered separately)

435 Stabilizer Clip (3/4" & 1")

Recommended for panels 60" and greater in length
NOTE: Panels 60" up to 96" – One clip near midpoint of each long edge.
Panels 96" and over – Two clips at 1/3 points of each long edge.

PHYSICAL DATA

Material
3355 – Fiberglass with DuraBrite® acoustically transparent membrane; CAC backing
All other items – Fiberglass with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type B, Form B2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
(PB suffix items only)
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content.
Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC.

Insulation Value
3254 – R Factor – 6.0 (BTU units)
R Factor – 1.05 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System.
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1403 – 0.55 LBS/SF; 24 SF/CTN
1407 – 0.55 LBS/SF; 30 SF/CTN
1409 – 0.55 LBS/SF; 96 SF/CTN
1410 – 0.55 LBS/SF; 16 SF/CTN
1411 – 0.55 LBS/SF; 20 SF/CTN
1413 – 0.55 LBS/SF; 6 SF/CTN
1414, 3263, 3290 – 0.55 LBS/SF; 48 SF/CTN
1415 – 0.55 LBS/SF; 21 SF/CTN
3251, 3251PB – 0.46 LBS/SF; 48 SF/CTN
1417 – 0.55 LBS/SF; 27 SF/CTN
3254 – 0.64 LBS/SF; 32.5 SF/CTN
3276 – 0.55 LBS/SF; 75 SF/CTN
3277 – 0.55 LBS/SF; 100 SF/CTN
3266 – 0.55 LBS/SF; 62.22 SF/CTN
3279 – 0.45 LBS/SF; 42 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
3251M, 3254M, 3256M, 3257M, 3355M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

FIBERGLASS – Standard

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems
(PB Suffix Only)

Declare.
(PB Suffix Only)

RECYCLED CONTENT
UP TO 71%

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK
Human Health
Climate Health EPD
Ecosystem Health EPD
Circular Economy ✓
OCCUPANT EXPERIENCE
Acoustics ✓

VISUAL SELECTION

PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics NRC	+ CAC =	Total Acoustics[1]	Articulation Class AC	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels: Fog	DURABILITY: Wash	Impact	Scratch	Soil	30-Yr Warranty
OPTIMA® 9/16" Square Tegular	26, 43, 47, 51, 55	3355	24 × 24 × 1"	0.90 •	26	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3280	24 × 42 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3257 3257PB	24 × 48 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3265 3265PB	24 × 60 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3261 3261PB	24 × 72 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3262 3262PB	24 × 96 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3283	27 × 30 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3268	28 × 30 × 1"	0.95* •	N/A	N/A	190* •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3269	28 × 60 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3259	30 × 30 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3284	30 × 54 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3289	30 × 56 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3285	30 × 60 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3287	42 × 48 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3288	44 × 48 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
		3256 3256PB	48 × 48 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A •	•	•	•	•	•	•
		3249	48 × 54 × 1"	0.95 •	N/A	N/A	190 •	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. Optima items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.
* These items are not UL® classified.

FIBERGLASS – Standard

OPTIMA®
OPTIMA® PB
with Plant-based Binder
Tegular
fine texture

SUSTAIN®
High Performance
Sustainable Ceiling Systems
(PB Suffix Only)

Declare®
(PB Suffix Only)

RECYCLED CONTENT
UP TO **71%**

LEED V5
Ecomedes Data

COMMON MATERIALS FRAMEWORK	
Human Health	Climate Health EPD
	Ecosystem Health EPD
	Circular Economy ✓
OCCUPANT EXPERIENCE	Acoustics ✓

VISUAL SELECTION


PERFORMANCE SELECTION
Dots represent high level of performance. $$$$

armstrongceilings.com/suspdwgs	Dimensions (Inches)	UL Classified Acoustics NRC + CAC =	Total Acoustics[1]	Articulation Class AC	Fire Performance	Light Reflect	Bio-Block Anti-Mold/Mildew	Humi-Guard+ Sag Resistant	Certified Low VOC Emissions	CleanAssure™ Disinfectable Panels: Fog	DURABILITY: Wash	Impact	Scratch	Soil	30-Yr Warranty
	Non-PB 1" Thick – 15/16" & 9/16" Square Tegular														
Made-to-Order Sizes OPTIMA® Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com 1 Ctn Min FASTSIZE 3 WEEKS order to ship	Width (short side): 4" – 6", 6-1/16" – 48" Length (long side): 9" – 96", 9" – 120"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
	PB 1" Thick – 15/16" & 9/16" Square Tegular														
	4" – 6", 6-1/16" – 24", 24-1/16" – 29-15/16", 30" – 48" 9" – 72", 9" – 96", 24-1/16" – 72", 30" – 60"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•
	Non-PB 1-1/2" Thick – 15/16" & 9/16" Square Tegular														
	4" – 6", 6-1/16" – 48" 9" – 96", 9" – 120"	N/A	N/A	N/A	N/A	Class A	0.88 •	•	•	N/A	•	•	•	•	•	•

[1] Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.
Optima items with the PB suffix are included in the Sustain® portfolio and carry Declare® certification.


SUSPENSION SYSTEMS

15/16"




Prelude®


9/16"




Silhouette® 1/4" Reveal



Silhouette 1/8" Reveal



Suprafine®



Interlude®

Blizzard White – Suspension System Finish
A color and texture coordinated suspension system to complement Optima® ceiling panels for a monolithic look and feel.
Available for: Prelude® XL® and XL® HRC, Suprafine® ML, XL®, and XL HRC, Silhouette® XL® 1/4" and 1/8" Reveal, Interlude® XL® HRC

ACCESSORIES (must be ordered separately)

435



Stabilizer Clip (3/4" & 1")

Recommended for panels 60" and greater in length
NOTE: Panels 60" up to 96" – One clip near midpoint of each long edge.
Panels 96" and over – Two clips at 1/3 points of each long edge.

PHYSICAL DATA

Material
3355 – Fiberglass with DuraBrite® acoustically transparent membrane; CAC backing
All other items – Fiberglass with DuraBrite acoustically transparent membrane

Surface Finish
DuraBrite scrim with factory-applied latex paint

Fire Performance
Clas A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL labeled).

ASTM E1264 Classification
Type B, Form B2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
(PB suffix items only)
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content
Contains greater than 50% total recycled content.
Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC.

Insulation Value
3254 – R Factor – 6.0 (BTU units)
R Factor – 1.05 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System.
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
3283 – 0.55 LBS/SF; 57.5 SF/CTN
3249, 3256, 3256PB, 3257, 3257PB, 3262, 3262PB – 0.55 LBS/SF; 96 SF/CTN
3259 – 0.64 LBS/SF; 75 SF/CTN
3261, 3261PB – 0.55 LBS/SF; 72 SF/CTN
3265, 3265PB, 3285 – 0.55 LBS/SF; 100 SF/CTN
3268 – 0.55 LBS/SF; 70 SF/CTN
3269 – 0.55 LBS/SF; 93.33 SF/CTN
3284 – 0.55 LBS/SF; 90 SF/CTN
3287 – 0.55 LBS/SF; 112 SF/CTN
3288 – 0.55 LBS/SF; 117.33 SF/CTN
3355 – 0.47 LBS/SF; 48 SF/CTN
3289 – 0.40 LBS/SF; 93.33 SF/CTN
3280 – 0.55 LBS/SF; 84 SF/CTN

Minimum Order Quantity
1 carton

Metric Items Available
3251M, 3254M, 3256M, 3257M, 3355M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

FIBERGLASS – Standard

TechLine / 1 877 276-7876
armstrongceilings.com/optima
BPCS-4648-925

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute®; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL is a registered trademark of UL LLC; USAI Lighting is a registered trademark of USAI Lighting, LLC; Revit® is a registered trademark of Autodesk, Inc.; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2025 AWI Licensing LLC

Armstrong® World Industries