


EXPOSED TEE SUSPENSION SYSTEMS

Accessories


2" Beam End Retaining Clip – Joins main beam or cross tee to wall molding and web of suspension system with no visible pop rivets.

ALBERC2 (aluminum) – 200 pcs
FZALBERC2 (aluminum) – 50 pcs
BERC2 (steel) – 200 pcs
FZBERC2 (steel) – 50 pcs




BERC – Beam End Retaining Clip – Joins web of main beam or cross tee to wall molding with no visible pop rivets.

BERC – 200 pcs
FZBERC – 50 pcs




Seismic Joint Clip – Main Beam – Allows the ceiling to be divided at a splice on the main beam to accommodate the IBC mandate for ceiling areas greater than 2500 SF to have seismic separation joints. ES4 expansion sleeve is used to cover 3/4" gap.

SJMR15 for 15/16" – 100 pcs
FZSJMR15 for 15/16" – 50 pcs
SJMR9 for 9/16" – 100 pcs
FZSJMR9 for 9/16" – 50 pcs




Seismic Joint Clip Cross Tee – Offers a tested seismic solution for separation joints in Seismic Category D, E, and F installations.

SJCG (PeakForm®) – 200 pcs
FZSJCG (PeakForm®) – 50 pcs
SJCSI (square bulbs) – 200 pcs
FZSJCSI (square bulbs) – 50 pcs




Expansion Sleeves

ES4 – for 15/16" Prelude® – 100 pcs
FZES4 – 50 pcs
ES49 – for 9/16" Suprafine® – 100 pcs
FZES49 – 50 pcs
ES76004 – for 1/4" Silhouette® – 200 pcs
FZES76004 – 50 pcs
ES76008 – for 1/8" Silhouette – 200 pcs
FZES76008 – 50 pcs




AXSJ-Axiom® Slip Joint – Used to join two acoustical ceiling systems on seismic D, E, F installations. Can also be used to join two different ceiling systems. Hanger wire holes every 6", beginning 3" from each end. AXSJ – 120" LFT




STAC – Single Tee Adapter Clip – Used to create code compliant non-seismic and seismic C and D, E, F off-module main beam to cross tee connections.
STAC – 120 pcs
FZSTAC – 50 pcs



GC3WG90 – Grip Clip 3-Way – Joins main beams to cross tee via locking barbs without pop rivets or screws.
GC3WG90 – 250 pcs
FZGC3WG90 – 50 pcs



XTACAG – Cross Tee Adapter Clip – Used to attach field-cut cross tees to main beams
XTACAG – 100 pcs
FZXTACAG – 50 pcs




GCWA – Grip Clip Wall Attachment – Joins main beam or cross tee to wall molding via locking barbs without pop rivets or screws.
GCWA – 250 pcs
FZGCWA – 50 pcs




Closure Clips
MCC4G for Silhouette® 1/4" reveal – 200 pcs
FZMCC4G – 50 pcs
MCC8 for Silhouette 1/8" reveal – 200 pcs
FZMCC8 – 50 pcs
IES3 for Interlude® – 200 pcs
FZIES3 – 50 pcs

C1430 – Variable Placement Hook Clip – Attach to T-Bar to create special length tees and position anywhere along the main beams.
C1430 – 200 pcs
FZC1430 – 50 pcs




DLCC – Direct Load Ceiling Clip – To hang suspension system below existing 15/16" grid face, transferring weight directly to hanger wire; may be used to preserve the fire rating of an existing ceiling and to support heavy accessories.

DLCC – 250 pcs
FZDLCC – 50 pcs




UPCAG – Partition Clip – Fastens partition track section to suspension system for secure attachment; clip for 9/16" or 15/16" suspension system.

UPCAG – 200 pcs
FZUPCAG – 50 pcs



UTC – Uptight Clip – For tight suspension system attachment to 1-1/2" channel; bridging under HVAC ducts; can be used to install the suspension system tight to wood joists.

UTC – 250 pcs
FZUTC – 50 pcs




Channel Beam Splice – Used to suspend main beams to 1-1/2" black iron carrying channels.

CBS4A (4") – 200 pcs; FZCBS4 – 50 pcs
CBS6A (6") – 200 pcs; FZCBS6 – 50 pcs
CBS8A (8") – 200 pcs; FZCBS8 – 50 pcs
CBS10A (10") – 150 pcs; FZCBS10 – 50 pcs
CBS12A (12") – 150 pcs; FZCBS12 – 50 pcs
For 2" Black Iron
CBS2004A (4") – 75 pcs; FZCBS2004A – 50 pcs
CBS2006A (6") – 75 pcs; FZCBS2006A – 50 pcs
CBS2008A (8") – 75 pcs; FZCBS2008A – 50 pcs



SH12 – PeakForm® Support Hanger – For suspension systems 12" knock-out at 12" O.C.
SB12 Square Bulb Support Hanger – 12 pcs/bundle
SB12G90 Square Bulb Support – 12 pcs/bundle
SH12 Hanger – 12 pcs/bundle



Adjustable Grid Spacer Clip – Used to space two parallel main beams for light fixtures, air diffusers, etc.; allows for 1/4" adjustments with three different clips.

GSC9 Main Beam Center Line Spacing FZGSC9 – 50 pcs
2 1/2" – 8 1/2" – 100 pcs
GSC12 Main Beam Center Line Spacing FZGSC12 – 50 pcs
5 1/2" – 11 1/2" – 100 pcs
GSC16 Main Beam Center Line Spacing FZGSC16 – 50 pcs
9 1/2" – 15 1/2" – 100 pcs




DWC – Drywall Clip – Allows for a "second" ceiling to be installed below a drywall ceiling; attach through installed drywall to supporting structure; DWC-approved for use in UL® Designs P237, P239, P240, and P241.


DWC – 250 pcs
FZDWC – 50 pcs



7876 – Field Rout Tool – 1 pc
7876RK – Field Rout Tool Repair Kit – 1 pin and 1 punch
ARPLUG – Cross Tee Plug Clip – 80 pcs




TZYK/TZBC – TechZone® Yoke & Brace
TZYK TechZone Yoke – 100 pcs
FZTZYK TechZone Yoke – 50 pcs
TZBC TechZone Brace – 100 pcs




435A/436A – Optima® Panel Stabilizer Clips

435A Stabilizer Clips for 3/4" – 1" panels – 50 pcs
436A Stabilizer Clips for 1-1/2" panels – 50 pcs



440A/441A/442A/443/522A – Vector® Clips

440A Ultima® Panel Border Clip – 50 pcs
441A Optima® Panel Border Clip – 50 pcs
442A Hold-Down Clip – 50 pcs
443 Border Clips for Calla® Vector® – 50 pcs
522A Mid-point Clip – 50 pcs



EXPOSED TEE SUSPENSION SYSTEMS

Accessories

LEED® WELL | LBC

UP TO 30% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting materials

lighting quality

acoustics

Calculate sustainability with Ecomedes


armstrongceilings.com/ecomedes

LOCATION DEPENDENT

7866 – Bullnose Corner Cover – For nominal 7/8" molding; snap over molding to trim outside corners; fits 1" radius block; 2" legs.


7864 – Bullnose Corner Cover – For nominal 7/8" molding; fits 3/4" radius block; 2" legs.

7866 – 100 pcs
FZ7866 – 50 pcs
7864 – 100 pcs
FZ7864 – 50 pcs




7867 – Field-Cut Corner Cover – For nominal 15/16" molding; cut to fit irregular corner conditions; 2" legs.

7867 – 100 pcs
FZ7867 – 50 pcs




7869 – Inside/Outside Corner Cover – For nominal 7/8" angle molding; 1-3/4" legs.

7869 – 50 pcs




7863 – Outside Corner Cover – For nominal 7/8" angle molding; snap over molding to trim outside corners; 2" legs.

7863 – 100 pcs
FZ7863 – 50 pcs




7865 – Outside Corner Cover – For nominal 9/16" angle molding; snap over molding to trim outside corners; 2" legs.

7865 – 100 pcs
FZ7865 – 50 pcs




Shadow Molding – Inside Corner – Snaps over molding to easily trim inside corner:

7874IC use with 7874 – 100 pcs; FZ7874IC – 50 pcs
7861 use with 7873 – 100 pcs; FZ7861 – 50 pcs
8771C use with 7877 – 100 pcs; FZ8771C – 50 pcs
7878IC use with 7878 – 100 pcs; FZ7878IC – 50 pcs




Shadow Molding – Outside Corner – snaps over molding to easily trim outside corner:

7874OC use with 7874 – 100 pcs; FZ7874OC – 50 pcs
7862 use with 7873 – 100 pcs; FZ7862 – 50 pcs
7877OC use with 7877 – 100 pcs; FZ7877OC – 50 pcs
7878OC use with 7878 – 100 pcs; FZ7878OC – 50 pcs




LFC – Fixture Clip – Prefinished White for use at corners of light fixture modules on 9/16" exposed tee suspension systems (Suprafine®, Interlude®, Silhouette®); increases corner size to 15/16" which adapts light fixtures designed for the 15/16" suspension system; used when fixtures are not positively attached to the suspension system.

LFC – 50 pcs;
FZLFC – 50 pcs



414AG – Retention Clip – Attaches to main beams and cross tees behind lay-in ceiling; helps prevent accidental panel displacement by basketballs and other forces from below the ceiling.



414AG – 100 pcs
FZ414AG – 50 pcs



UHDCA – Universal Hold-Down Clip – Attaches to top bulb of the suspension system to hold 1/16" to 5/8" lay-in panel in place; helps to prevent ceiling panel fluttering at entryways.


UHDCA – 1,000 pcs
FZUHDCA – 50 pcs

CHDC – Clear Hold-Down Clip – 50 pcs




BHDC – Border Hold-Down Clip – Attaches to Angle Molding to hold down perimeter panels. Made of Stainless Steel.

BHDC – 100 pcs



DW58LT – Transition Clip for 5/8" Drywall – Facilitates transition from drywall to acoustical ceiling; one-sided hold-down clip; eliminates need for drywall bead. Locking tabs provide secure location for DGS tees.

DW50LT – Transition Clip for 1/2" Drywall – 125 pcs
FZDW50LT – 50 pcs




7425 – 24" Stabilizer Bar – 100 pcs

7431 – 30" Stabilizer Bar – 100 pcs


7445 – 48" Stabilizer Bar – 100 pcs

Used to maintain uniform spacing of suspension system components (main beams and cross tees).



7891 – 12 Gauge Soft Hanger Wire (12' length) – Used to hang suspended ceilings from structural deck.

7891 – 140 pcs



EHDC50A – Exterior Hold-Down Clip for 1/2" lay-in ceiling panels and drywall;

EHDC58AG – Exterior Hold-Down Clip for 5/8" lay-in ceiling panels and drywall;


EHDC75A – Exterior Hold-Down Clip for 3/4" lay-in ceiling panels and drywall;

locks under bulb of suspension system member to prevent upward movement.

EHDC50A – 125 pcs; FZEHDC50A – 50 pcs


EHDC58AG – 125 pcs; FZEHDC58AG – 50 pcs

EHDC75A – 125 pcs; FZEHDC75A – 50 pcs




GA7327 – Grid Adapter – Allows for easy directional changes of Prelude® Main beams; 27" long component has two different end details. One end has a SuperLock™ clip with a rout 3" from the end, opposite end has an XL® clip with override end detail. This enables the adapter to be connected to either end of a Prelude main beam or plugged into a rout location on a main beam or cross tee.

GA7327 – 60 pcs




WS12 – Hanger Wire Splice – Splices 12-gauge hanger wire; recommended for renovation applications; provides easy adjustment of ceiling height.

WS12 – 1,000 pcs
FZWS12 – 50 pcs



BACG90A – Wind Uplift Clip – 250 pcs
FZBAGG90A – 50 pcs



12 lb. Aircraft Cable and Connectors

AC1210 – 10' length

AC1215 – 15' length

AC1220 – 20' length

ACHC – Cable Quick Loop Connector

1 pc