

TRANSITION MOLDINGS

Acoustical-to-Drywall Transition Molding



▲ Acoustical-to-Drywall Transition Molding

Transition moldings save time and money and are easier to install.

KEY SELECTION ATTRIBUTES

- Fewer parts and pieces; combines acoustical molding with drywall taping flange
- Pre-punched vertical web to improve screw attachment
- Knurled and slotted integral taping flange on items 7901, 7902, 7904, 7905, 7906, 7907, 7908 accommodates taping and finishing
- Protective film on the face of the wall molding flange of 7904PF and 7905PF facilitates faster, easier mudding, sanding, and taping
- Compatible with all types of framing including Armstrong® Drywall Grid and ShortSpan®

VISUAL SELECTION

	Item No.	Flange	Length	Reveal	Pcs/ Ctn	Lin. Ft./ Ctn.	
Shadow Reveal Transition Molding	7901	9/16"	120"	3/8"	12	120	
	7902	15/16"	120"	3/8"	12	120	
	7911	9/16"	120"	3/8 x 1/4"	12	120	
	7912	15/16"	120"	3/8 x 1/4"	12	120	
F Vertical Transition Molding	7906	1/2"	120"		12	120	
	7913	9/16"	120"		12	120	
	7914	15/16"	120"		12	120	

TRANSITION MOLDINGS

Acoustical-to-Drywall Transition Molding

LEED WELL LBC

UP TO **61% RECYCLED CONTENT**

Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

Well Building Standard™ (WELL)
Living Building Challenge® (LBC)

VISUAL SELECTION

Item No.	Flange	Length	Transition Height	Pcs/ Ctn	Lin. Ft./ Ctn.
7903 Flush Transition Molding	9/16"	120"	1"	12	120
7904 7904PF*	15/16"	120"	N/A	12	120
7905 7905PF*	9/16"	120"	N/A	12	120


Item No.	Flange	Length	Reveal	Pcs/ Ctn	Lin. Ft./ Ctn.
7907 Tegular Transition Molding	9/16"	120"	15/16"	12	120
7908	15/16"	120"	15/16"	12	120
7909 Step Transition Molding	15/16"	120"	1"	12	120
7910	9/16"	120"	1"	12	120

* Protective film applied to face of wall molding flange for easier finishing.

ACCESSORIES


2" Beam End Retaining Clip – Joins main beam or cross tee to wall molding and web of suspension system with no visible pop rivets.

ALBERC2 (aluminum) – 200 pcs
FZALBERC2 (aluminum) – 50 pcs
BERC2 (steel) – 200 pcs
FZBERC2 (steel) – 50 pcs





Knurled Angle Molding – Hemmed with prefinished exposed flanges.

KAM10 – 10 pcs
KAM12 – 10 pcs





INSTALLATION DETAILS

Drywall to Acoustical (Acoustical Flange with 3/8" reveal) 7901 – 9/16" and 7902 – 15/16"



Drywall to Acoustical 1" Step 7910 – 9/16" and 7909 – 15/16"



TRANSITION MOLDINGS

Acoustical-to-Drywall Transition Molding

LEED® WELL™ | LBC

UP TO **61% RECYCLED CONTENT**

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/excise producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics



Calculate sustainability with GreenGenie™
armstrongceilings.com/greengenie

Well Building Standard™ (WELL)
Living Building Challenge® (LBC)



LOCATION DEPENDENT

INSTALLATION DETAILS (CONTINUED)


Drywall to Acoustical (1" Inverted T) 7903




Drywall to Acoustical Flush Transition 7904/7904PF – 15/16" and 7905/7905PF – 9/16"





F Vertical Transition Molding Flush 7906



Drywall-to-Acoustical Regular 7907 – 9/16" and 7908 – 15/16"



Drywall to Acoustical (Acoustical Flange with 3/8" x 1/4" reveal) 7911 – 9/16" and 7912 – 15/16"



Stepped 7913 – 9/16" and 7914 – 15/16"

