

# PRELUDE® Plus XL® Fire Guard™ PRELUDE® XL® for Exterior Applications Exposed Tee Suspension System



Prelude® Plus XL® suspension system

A 15/16" suspension system for severe environmental performance.

## KEY SELECTION ATTRIBUTES

- Seismic Rx® Suspension System saves time and money; ICC-ES approach to installations (ESR-1308)
- Prelude® Plus XL® Fire Guard™ and Prelude® XL® for Exterior Applications are part of the Sustain™ portfolio and meets the most stringent industry sustainability compliance standards today – White only
- Systems conform to ASTM C635 for Severe Environmental Performance
- Rotary-stitched during manufacture for torsional strength and stability
- 10-Year Limited Warranty; 30-Year Limited Warranty with HumiGuard® Plus or HumiGuard® Max products
- XL® staked-on end detail provides secure locked connection
- PeakForm® profile increases strength and stability
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (Cleaning and CDC-approved disinfecting options available on [armstrongceilings.com/cleaning](http://armstrongceilings.com/cleaning))
- SuperLock™ main beam clip engineered for secure connection and fast, accurate alignment
- 10-Year replacement items available



## PRELUDE® XL® For Exterior Applications

- Minimum G90 hot-dipped galvanized steel with prefinished G90 steel capping
  - Suitable for wind uplift applications with appropriate bracing
- PRELUDE® Plus XL® Fire Guard™**
- Systems are minimum G60 hot-dipped galvanized steel with prefinished aluminum capping for enhanced corrosion resistance

## TYPICAL APPLICATIONS

### PRELUDE Plus XL Fire Guard


- Locker rooms
- Food preparation areas

### PRELUDE XL For Exterior Applications

- Non-exposed exterior corridors
- Drive-thru areas
- Indoor parking garages
- Use with Woodworks® Linear Solid Wood Panels for Exterior

## COLORS






### Fire Guard™ Only



### Exterior Only



## VISUAL SELECTION

				HANGER SPACING* LBS/LF			PERFORMANCE					PACKAGING	
	Item No. ♦	Description	Dimensions (Inches)	2 Ft.	4 Ft.	5 Ft.	Fire Guard™ 	Seismic Category 	CleanAssure™ Disinfectable Grid   			Pieces/ Carton	LF/ Carton
PRELUDE® Plus XL® Fire Guard™ (Red Numbers are Fire Guard items)	HD8201_ _	12' HD Main Beam	144 x 15/16 x 1-11/16"	12.75	16.73	N/A	*	*	*	*	*	20	240
	XL8240_ _	4' Cross Tee	48 x 15/16 x 1-1/2"	12.75	N/A	N/A	*	*	*	*	*	60	240
	XL8223_ _	2' Cross Tee	24 x 15/16 x 1-1/2"	38.63	N/A	N/A	*	*	*	*	*	60	120
Molding	HD7801_ _	10' Hemmed Angle Molding (7/8")	120 x 7/8 x 7/8"	N/A	N/A	N/A	N/A	N/A	*	*	*	30	300

\* Simple Span  
♦ Add 2-letter color suffix to item number when specifying or ordering. (ex. HD7801G90A B L)

Dots represent high level of performance.

ASTM Class  
HD - Heavy-duty  
ID - Intermediate-duty  
LD - Light-duty

TechLine 877 276-7876  
[armstrongceilings.com/preludeplus](http://armstrongceilings.com/preludeplus)

**Armstrong®**  
World Industries

PRELUDE® Plus XL® Fire Guard™  
PRELUDE® XL®  
for Exterior Applications  
Exposed Tee Suspension System



LEED® WELL™ LBC

UP TO 30% RECYCLED CONTENT

energy management  
construction waste mgmt  
regional materials  
design for flexibility  
EPD  
recyclable/ biobased materials  
producer resp.

biobased materials  
recycled content  
sourcing of raw materials  
material ingredient reporting  
low emitting/ materials  
lighting quality  
acoustics

Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE

PACKAGING

	Item No. ♦	Description	Dimensions (Inches)	HANGER SPACING* LBS/LF			CleanAssure™ Disinfectable Grid					Pieces/ Carton	LF/ Carton
				2 Ft.	4 Ft.	5 Ft.	Fire Guard™ DEF	Seismic Category	Fog	Spray	Wipe		
PRELUDE XL® for Exterior Applications 15/16"	7301G90A_ _	12' HD Main Beam	144 x 15/16 x 1-11/16"	N/A	16.50	6.92	N/A	*	*	*	*	20	240
	XL7341G90A_ _	4' Cross Tee	48 x 15/16 x 1-11/16"	N/A	16.59	N/A	N/A	*	*	*	*	60	240
	XL7321G90A_ _	2' Cross Tee	24 x 15/16 x 1-11/16"	N/A	74.38	N/A	N/A	*	*	*	*	60	120
Molding	HD7801G90_ _	10' Hemmed Angle Molding (7/8")	120 x 7/8 x 7/8"	N/A	N/A	N/A	N/A	N/A	*	*	*	30	300
Accessories	BACG90A	Wind Uplift Clip (2")	N/A	N/A	N/A	N/A	N/A	N/A	*	*	*	20	N/A
	UHDC	Universal Hold-down Clip	N/A	N/A	N/A	N/A	N/A	N/A	*	*	*	1,000	N/A

\* Simple Span  
♦ Add 2-letter color suffix to item number when specifying or ordering. (ex. HD7801G90A B L)

Dots represent high level of performance.


ASTM Class  
HD - Heavy-duty  
ID - Intermediate-duty  
LD - Light-duty

DETAILS



PRELUDE XL  
Main Beam

PRELUDE XL  
Cross Tee



PHYSICAL DATA

**Design Considerations**  
All acoustical grid and Axiom trim accessories (a.k.a. clips) are supplied as unpainted items. Exposed clips will need to be field painted after installation, if required for the project. This ensures accessories meet the tested performance criteria and adhere to AWI installation instructions and warranted products or systems.

