

# SUSPENSION SYSTEM MOLDINGS

LEED® WELL | LBC

UP TO 30% RECYCLED CONTENT

energy management  
 construction waste mgmt  
 regional materials  
 design for flexibility  
 EPD  
 recyclable/producer resp.  
 bio-based materials  
 recycled content  
 sourcing of raw materials  
 material ingredient reporting  
 low emitting materials  
 lighting quality  
 acoustics


Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

Angle molding, shadow molding, channel molding, and other wall moldings are an important detail in the design and installation of each ceiling system. Wall moldings offer a unique solution to each ceiling system by maintaining a consistent look and performance to each design.

## Shadow Molding:

Hemmed with prefinished exposed flanges




| Item No. | Length | (A) Flange | (B) Height | (C) Reveal | LFT/CTN |
|----------|--------|------------|------------|------------|---------|
| 7823*    | 120"   | 2"         | 1-1/4"     | 3/4"       | 100     |
| 7871     | 120"   | 3/4"       | 15/16"     | 3/4"       | 300     |
| 7873     | 120"   | 9/16"      | 15/16"     | 3/8"       | 300     |
| 7874     | 120"   | 9/16"      | 15/16"     | 1/4"       | 300     |
| 7875     | 120"   | 3/4"       | 15/16"     | 1/2"       | 300     |
| 7877*    | 120"   | 15/16"     | 15/16"     | 1/4"       | 300     |
| 7878*    | 120"   | 15/16"     | 15/16"     | 3/8"       | 300     |
| 7897*    | 120"   | 15/16"     | 15/16"     | 1/2"       | 300     |

\* Suitable for IBC Category D, E, F installations.

NOTE: Shadow molding can be rotated to be used with either flange.

## Shadow Molding:

Hemmed with prefinished exposed flanges



| Item No. | Length | (A) Flange | (B) Height | (C) Reveal | (D) Reveal | LFT/CTN |
|----------|--------|------------|------------|------------|------------|---------|
| 7888     | 120"   | 15/16"     | 15/16"     | 3/8"       | 1/4"       | 300     |
| 7889     | 120"   | 9/16"      | 15/16"     | 3/8"       | 1/4"       | 300     |

## Shadow Molding:

(Compatible with Seismic Rx® and BERC 2)




| Item No. | Length | (A) Flange | (B) Height | (C) Reveal | LF/CTN |
|----------|--------|------------|------------|------------|--------|
| 7877*    | 120"   | 15/16"     | 15/16"     | 1/4"       | 300    |
| 7878*    | 120"   | 15/16"     | 15/16"     | 3/8"       | 300    |
| 7897*    | 120"   | 15/16"     | 15/16"     | 1/2"       | 300    |

\* Suitable for IBC Category D, E, F installations.


NOTE: Shadow molding can be rotated to be used with either flange.

## Shadow Molding:

Inside and outside corners



Inside Corner



Outside Corner

| Item No. | Description                     |
|----------|---------------------------------|
| 7874IC   | Inside Corner for 7874 Molding  |
| 7874OC   | Outside Corner for 7874 Molding |
| 7861     | Inside Corner for 7873 Molding  |
| 7862     | Outside Corner for 7873 Molding |
| 7877IC   | Inside Corner for 7877 Molding  |
| 7877OC   | Outside Corner for 7877 Molding |
| 7878IC   | Inside Corner for 7878 Molding  |
| 7878OC   | Outside Corner for 7878 Molding |

NOTE: Shadow molding can be rotated to be used with either flange (Corners will not work with rotated moldings).

# SUSPENSION SYSTEM MOLDINGS

LEED® WELL | LBC

UP TO 30% RECYCLED CONTENT

energy management

construction waste mgmt

regional materials

design for flexibility

EPD

recyclable/extended producer resp.

biobased materials

recycled content

sourcing of raw materials

material ingredient reporting

low emitting materials

lighting quality

acoustics


Calculate sustainability with Ecomedes  
armstrongceilings.com/ecomedes

LOCATION DEPENDENT

Angle molding, shadow molding, channel molding, and other wall moldings are an important detail in the design and installation of each ceiling system. Wall moldings offer a unique solution to each ceiling system by maintaining a consistent look and performance to each design.

## Angle Molding:

Hemmed with prefinished exposed flanges




| Item No. ♦     | Length | (A)<br>Flange | (B)<br>Height | LF/<br>CTN |
|----------------|--------|---------------|---------------|------------|
| 7800_ _ *      | 144"   | 7/8"          | 7/8"          | 360        |
| 7800HRC        | 144"   | 7/8"          | 7/8"          | 360        |
| 7802           | 120"   | 7/8"          | 7/8"          | 300        |
| 7803_ _ ♦      | 144"   | 7/8"          | 7/8"          | 360        |
| 7804_ _ **     | 144"   | 9/16"         | 7/8"          | 360        |
| 7804HRC        | 144"   | 9/16"         | 7/8"          | 360        |
| 780410         | 120"   | 9/16"         | 7/8"          | 300        |
| 7805           | 120"   | 1-1/2"        | 1-1/2"        | 300        |
| 7807_ _ ***    | 120"   | 2"            | 1"            | 100        |
| 7808_ _ ***    | 120"   | 2"            | 2"            | 100        |
| 780812         | 144"   | 2"            | 2"            | 120        |
| 7809           | 144"   | 15/16"        | 15/16"        | 360        |
| 7813           | 120"   | 3"            | 1"            | 200        |
| 7850           | 144"   | 1-1/8"        | 7/8"          | 360        |
| HD7801_ _ **** | 120"   | 7/8"          | 7/8"          | 300        |
| HD7801G90      | 120"   | 7/8"          | 7/8"          | 300        |
| SS7801         | 120"   | 7/8"          | 7/8"          | 300        |
| AL7801         | 120"   | 7/8"          | 7/8"          | 300        |
| SWA9854HRC     | 144"   | 1-1/4"        | 15/16"        | 144        |
| SWA9878HRC     | 144"   | 7/8"          | 15/16"        | 144        |


- \* Available in Black, Light Grey, Grey Stone, Medium Taupe, Ivory, and White
- \*\* Available in Black, Light Grey, Grey Stone, Medium Taupe, Ivory, White, Silver Grey, Silver Satin, and Gun Metal Grey
- \*\*\* Available in Silver Grey and Gun Metal Grey
- \*\*\*\* Available in Black, Gun Metal Grey, Natural Aluminum, Silver Satin, Silver Grey, White Aluminum
- ♦ When specifying or ordering items with a color or finish, add the two-letter suffix to the end of the item number (e.g. 7807WH)
- ♦ Pre-punched

## Slip-on Molding:

For glue-up tile



| Item No. | Length | (A)<br>Flange | (B)<br>Height | LFT/<br>CTN |
|----------|--------|---------------|---------------|-------------|
| 7842     | 120"   | 1/2"          | 5/8"          | 400         |
| 7843     | 120"   | 1/2"          | 3/4"          | 400         |



# SUSPENSION SYSTEM MOLDINGS

LEED® WELL™ LBC

UP TO 30% RECYCLED CONTENT

energy management  
 construction waste mgmt  
 regional materials  
 design for flexibility  
 EPD  
 recyclable/ biobased materials  
 recycled content  
 sourcing of raw materials  
 material ingredient reporting  
 low emitting materials  
 lighting quality  
 acoustics

Calculate sustainability with Ecomedes  
[armstrongceilings.com/ecomedes](http://armstrongceilings.com/ecomedes)


LOCATION DEPENDENT

Angle molding, shadow molding, channel molding, and other wall moldings are an important detail in the design and installation of each ceiling system. Wall moldings offer a unique solution to each ceiling system by maintaining a consistent look and performance to each design.


## Fascia Molding: Prefinished exposed flanges




| Item No. | Length | (A) Flange | (B) Height | LF/ CTN |
|----------|--------|------------|------------|---------|
| 7814     | 120"   | 1"         | 4"         | 50      |
| 7816     | 120"   | 1"         | 6"         | 50      |
| 7818     | 120"   | 1"         | 8"         | 50      |



## Flex Molding: Steel base with flexible vinyl facing, minimum bending radius 6"




| Item No. ♦    | Length | (A) Flange | (B) Height | (C) Reveal | LF/ CTN |
|---------------|--------|------------|------------|------------|---------|
| <b>Angle</b>  |        |            |            |            |         |
| 7880_ _ *     | 96"    | 1"         | 1"         | N/A        | 96      |
| 7882_ _ *     | 96"    | 7/8"       | 15/16"     | N/A        | 96      |
| 7884_ _ *     | 96"    | 15/16"     | 15/16"     | N/A        | 96      |
| 7885_ _ *     | 96"    | 9/16"      | 1"         | N/A        | 96      |
| 7887          | 96"    | 2"         | 1-1/2"     | N/A        | 96      |
| <b>Shadow</b> |        |            |            |            |         |
| 7890          | 96"    | 3/4"       | 1-5/8"     | 3/4"       | 96      |
| 7898          | 96"    | 9/16"      | 1"         | 3/8"       | 96      |




\* Available in Black and White.


## Reverse Angle Molding: Hemmed with prefinished exposed flanges




| Item No. | Length | (A) Flange | (B) Height | LF/ CTN |
|----------|--------|------------|------------|---------|
| 7857     | 144"   | 15/16"     | 15/16"     | 360     |
| 7858     | 144"   | 1-9/16"    | 15/16"     | 240     |




## F Molding: For 1/2" and 5/8" drywall




| Item No. | Length | (A) Width | (B) Face | (C) Flange | LF/ CTN |
|----------|--------|-----------|----------|------------|---------|
| 7852     | 120"   | 1/2"      | 1-1/16"  | 7/8"       | 200     |
| 7856     | 120"   | 5/8"      | 1-3/16"  | 7/8"       | 200     |



## Channel Molding: Hemmed with prefinished exposed flanges



| Item No. ♦ | Length | (A) Flange | (B) Height | (C) Reveal | LF/ CTN |
|------------|--------|------------|------------|------------|---------|
| 7830       | 120"   | 15/16"     | 1-15/16"   | 15/16"     | 160     |
| 7831       | 120"   | 15/16"     | 1-9/16"    | 15/16"     | 200     |
| 7834       | 120"   | 15/16"     | 1-1/4"     | 1/2"       | 240     |
| 7835_ _ ** | 120"   | 7/8"       | 1-3/4"     | 9/16"      | 200     |
| 7835SC *** | 11"    | 7/8"       | 1-3/4"     | 9/16"      | 150     |



\*\* Available in Gun Metal Grey and Silver Grey  
 \*\*\* Unpainted spreader channel