



Suspension Systems (Prelude, Suprafine, Interlude, Silhouette) Armstrong World Industries

Final Assembly: Aberdeen, Maryland, USA; Las Vegas, Nevada, USA; Benton Harbor, Michigan, USA

Life Expectancy: 30 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Galvanized Steel; Xylene; Barium sulfate; White Tint; Proprietary Ingredient (< 0.056%)¹; **Naphtha**; Petroleum distillates; 1,2,4-Trimethylbenzene; **1,3,5-Triglycidyl-s-triazinetriene**; 2-Butoxyethanol; C.I. Pigment Brown 24; Ethanol; UNS A96063 Aluminum Alloy; Black Tint; Butanol; Isobutyl alcohol

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-------------------------------|
| ☐ LBC Red List Free | % Disclosed: 99.94% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0088
EXP. 01 SEP 2026
Original Issue Date: 2023

