

ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Regular
fine texture



**TOTAL
ACOUSTICS®**
Sound Absorption (NRC)
+ Sound Blocking (CAC)




SUSTAIN®
High Performance
Sustainable
Ceiling Systems



Ultima Health Zone Regular panels with Suprafine 9/16" suspension system

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Perfect for education, office, and healthcare spaces

Fine texture mineral fiber ceiling; combines exceptional acoustical performance, sustainability, and functionality attributes in one go anywhere ceiling panel that is especially durable and aesthetically pleasing for every healthy space.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability and cleanability – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- Ultima® Health Zone™ panels are part of the Sustain® portfolio and meet the most stringent industry sustainability compliance standards today
- Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems (Item 1937)
- Long-lasting water-repellency; washable and scrubbable

- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth
- 10-Year replacement panel available for item 1936
- Made in the U.S.A. of domestic and global content
- Build America, Buy America (BABA) Act compliant



TYPICAL APPLICATIONS

- Healthcare:
- Patient rooms
 - Treatment rooms
 - Nurses' stations
 - Emergency rooms
 - Corridors
 - Lavatories and restrooms
 - Kitchen/food prep areas
- Education
- Office
- Clean Rooms (Item 1937)

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Ultima® Health Zone™ High NRC panel with Suprafine® XL® 9/16" suspension system
2. Ultima® Health Zone™ High NRC Square Tegular panel with Prelude® XL® 15/16" suspension system
3. Ultima® Health Zone™ High NRC Square Tegular with Interlude® XL® HRC 9/16" suspension system

ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Tegular
fine texture



RECYCLED
CONTENT

UP TO
76%

LEED V5

Ecomedes Data

COMMON MATERIALS FRAMEWORK

Human Health	Declare Label	Climate Health	EPD
	HPD	Ecosystem Health	EPD
	3rd Party CDPH	Circular Economy	✓
OCCUPANT EXPERIENCE		Acoustics	✓

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
--------------------------------	------------	----------	---------------------

ULTIMA® Health Zone™
High NRC



15/16" Beveled Tegular



ULTIMA Health Zone



15/16" Beveled Tegular



Made-to-Order Sizes

ULTIMA Health Zone

ULTIMA Health Zone High NRC

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

* Item provides Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems

PERFORMANCE SELECTION

\$\$\$

UL Classified Acoustics				Total Acoustics ¹				Articulation Class				Fire Performance				Light Reflect				Bio-Block+ Humi-Guard+ Sag Resistant				CleanAssure™ Disinfectable Panels				DURABILITY				30-yr Warranty
NRC	CAC	NRC	CAC	NRC	CAC	NRC	CAC	AC	AC	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class	Class
0.80	35	BEST	170	Class	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
0.80	35	BEST	170	Class	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
0.70	38	BETTER	N/A	Class	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
0.70	38	BETTER	N/A	Class	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
N/A	N/A	N/A	N/A	Class	0.86	+	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*

3/4" or 7/8" Thick – 9/16" & 15/16" Beveled Tegular

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

Width (short side)

Length (long side)

4" – 30"

12" – 72"

SUSPENSION SYSTEMS

15/16"




Prelude®
AL Prelude® Plus XL®
SS Prelude Plus XL




Clean Room™
(Steel or Aluminum)

9/16"




Silhouette® XL®
1/4" Reveal



Silhouette XL
1/8" Reveal



Suprafine®



Interlude® XL® HRC

PHYSICAL DATA

Material

Wet-formed mineral fiber with DuraBrite® acoustically transparent water-repellent membrane

Surface Finish

DuraBrite with factory-applied latex paint

Fire Performance

Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL* labeled).

ASTM E1264 Classification

Type A, Form A2.2, Pattern E; Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew

Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance

CAC testing conducted using Prelude suspension system for 15/16" edge profile and Silhouette® 9/16" profile.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Application Considerations

For Clean Room installations, use full-size panels. Testing for Clean Room 5 (Class 100) was completed with full-size 15/16" gasketed suspension system. For Clean Rooms that require field-cut perimeter panels, use Lay-in panels (1935) or Tegular panels (1937) with Lay-in field-cut panels at the perimeter.

Insulation Value

R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

Cleaning and Disinfecting

Cleaning and CDC-recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight: Square Feet/Carton

1936, 1937 – 1.08 LBS/SF; 48 SF/CTN
1447, 1446 – 1.0 LBS/SF; 40 SF/CTN

Minimum Order Quantity

1 carton