

ULTIMA® Health Zone™
ULTIMA® Health Zone™ High NRC

Square Lay-in
fine texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



▲ Ultima® Health Zone™ Square Lay-in panels with Prelude® XL® 15/16" suspension system

Perfect for office, education, and healthcare spaces

Fine texture mineral fiber ceiling; combines exceptional acoustical performance, sustainability, and functionality attributes in one go anywhere ceiling panel that is especially durable and aesthetically pleasing for every healthy space.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics Performance
- Meets or exceeds USDA/FSIS, FGI, HIPAA and ANSI S12.60 guidelines
- Anti-Bacterial/Mold/Mildew – BioBlock® Plus performance resists the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface
- Exceptional durability and cleanability – impact-, scratch-, and soil-resistant
- CleanAssure™ – safe for use with disinfectant cleaners
- Clean + Simple – Ultima® panels are part of the Sustain® portfolio and are free of Red List chemicals for better indoor air quality
- Clean Room Performance up to ISO Class 5 (Class 100) using gasketed Clean Room™ suspension systems
- Long-lasting water-repellency; washable and scrubbable
- Energy-saving, high light-reflective finish
- 30-Year Limited System Warranty against visible sag, mold, mildew, and bacterial growth

TYPICAL APPLICATIONS

- Healthcare:
- Patient rooms
 - Treatment rooms
 - Nurses' stations
 - Emergency rooms
 - Corridors
 - Lavatories and restrooms
 - Kitchen/food prep areas
- Education
- Office
- Clean Rooms (item 1935)

COLOR



White
(WH)

DETAILS



1. Ultima® Health Zone™ Square Lay-in
2. Ultima® Health Zone™ High NRC Square Lay-in panels with Clean Room™ 15/16" suspension system

ULTIMA® Health Zone™ ULTIMA® Health Zone™ High NRC

Square Lay-in
fine texture

USDA
CERTIFIED
BIOBASED
PRODUCT 95%

SUSTAIN*
High Performance
Sustainable Ceiling Systems

Declare.

GREENGUARD
Gold Certified
(details below)

LEED®
WELL™ LBC

UP TO **76%** RECYCLED
CONTENT

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
ULTIMA® Health Zone™ High NRC	1, 6	1445	24 x 24 x 7/8" □
15/16" Square Lay-in		1448*	24 x 48 x 7/8" □
ULTIMA Health Zone	1, 6	1935	24 x 24 x 3/4" □
15/16" Square Lay-in		1938*	24 x 48 x 3/4" □

Made-to-Order Sizes	Width	Length
ULTIMA Health Zone	4" – 6"	12" – 72"
	6-1/2" – 30"	12" – 72"
	30-1/2" – 48"	4" – 30"

1 Ctn Min
FASTSIZE
3 WEEKS
order to ship

Visit the product page online and see "Configure an Item" to verify capabilities. Questions? email Techline@armstrongceilings.com

1 Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.

GOOD (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

* Item does not have painted edges


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics	Total Acoustics ¹	Articulation Class	Fire Performance	Light Reflect	Anti-Bacterial/Mold/Mildew	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY	Recycle Program
0.80 •	35 •	BEST ()))	170 •	Class 0.86 A •	+	•	•	•	•
0.80 •	35 •	BEST ()))	170 •	Class 0.86 A •	+	•	•	•	•
0.70 •	38 •	BETTER ()))	N/A •	Class 0.86 A •	+	•	•	•	•
0.70 •	38 •	BETTER ()))	N/A •	Class 0.86 A •	+	•	•	•	•
N/A	N/A	N/A	N/A	Class 0.86 A •	+	•	•	•	•

3/4" or 7/8" Thick – 15/16" Square Lay-in

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent water-repellent membrane

Surface Finish
DuraBrite with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Bacterial/Mold/Mildew
Ceiling tiles with BioBlock® Plus performance resist the growth of odor and stain-producing bacteria as well as mold and mildew on the ceiling tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude suspension system.

Primary (Embodied) Energy
See all LCA information on our EPDs.

High Recycled Content
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



Insulation Value
R Factor – 2.9 (BTU units)
R Factor – 0.445 (Watts units)

Cleaning and Disinfecting
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning

30-Year Performance Guarantee & Warranty
When installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1448, 1938 – 1.08 lbs/SF; 48 SF/ctn
1445 – 1.0 lbs/SF; 40 SF/ctn
1935 – 1.0 lbs/SF; 48 SF/ctn

Minimum Order Quantity
1 carton

TechLine / 1 877 276-7876
armstrongceilings.com/healthzone
BPCS-4066-1122

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge® (LBC) are registered trademarks of the International Living Future Institute; WELL™ and WELL Building Standard are trademarks of the International WELL Building Institute; UL and UL Certified are trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates. © 2022 AWI Licensing LLC

Armstrong®
CEILING & WALL SOLUTIONS



MINERAL FIBER – Standard