



Ultima® Ceiling Panels Armstrong World Industries

Final Assembly: Pensacola, Florida, USA; Marietta, Pennsylvania, USA

Life Expectancy: 30 Year(s)

Embodied Carbon: 0.327kg CO₂eq 

Declared Unit: square foot

End of Life Options: Take Back Program (Armstrong Ceiling Recycling Program), Recyclable (100%)

Ingredients:

Mineral Fiber; Perlite; Clay; Corn Starch; Cellulose; Calcium Carbonate; Limestone; Aluminum hydroxide; Calcium carbonate; Dolomite; Glass, oxide, chemicals; Polyvinyl acetate; Titanium dioxide; Kaolin; Amorphous Silica; Acrylic Acid; Propanol; 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-; Aluminum Trihydrate; Zinc borate; Polyvinyl alcohol; Quartz; Fatty acids, coco, polymers with benzoic acid, pentaerythritol and phthalic anhydride; White Tint; Paraffin Wax; Polyethylene Wax; Benzenesulfonic acid, 5-benzoyl-4-hydroxy-2-methoxy-; Sodium Salt; Polyethylene; Styrene Polymer; Silisic Salt; Water; Citric Acid; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Ester; Methyl Polymer; Attapulgit Clay

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| ☒ LBC Red List Free | % Disclosed: 100% at 100ppm |
| ☐ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

ARM-0026
EXP. 01 SEP 2026
Original Issue Date: 2016

